PoDI / NHS FHWA PROJECT OF ■ NO □ YES DIVISION INTEREST (PoDI)? NATIONAL HIGHWAY SYSTEM? ■ NO □ YES

BOULDER COUNTY

CONSTRUCTION BID PLANS OF PROPOSED FEDERAL AID PROJECT NO. STU C070-043 **BOULDER CANYON TRAIL EXTENSION**

CONSTRUCTION PROJECT CODE NO. 19888

Related Projects:

P. E. UNDER PROJECT:

Project Number

Project Code:

XXXXXXXXX ER 119A-065

R.D.W. Projects:
R.D.W. Project Description

F.O.R.

NOVEMBER, 2016

TABULATION OF LENGTH & DESIGN DATA

| STATION | BOULDER CANYON TRAIL | | | |
|--|----------------------|-------|--|--|
| | FEET | MILES | | |
| BEGIN PROJECT STU C070-043 = STA. 102+50.00 SH 119 M.P. 38.36 END PROJECT STU C070-043 = STA. 139+52.71 | 3702.71 | 0.70 | | |
| SH 119 M.P. 38.94 PROJECT LENGTH | 3702.71 | 0.70 | | |

| DESIGN DATA | SH 119 | Boulder Canyon Trail |
|---------------------------|---------|---------------------------------|
| DESIGN SPEED | 45 MPH | 16 MPH TYPICAL |
| | | 20 MPH - GRADES > 4% |
| POSTED SPEED | 40 MPH | 15 MPH |
| MANUAL IN CRAPE | F 000/ | 50/ DAVED TOAH |
| MAXIMUM GRADE | 5.00% | 5% PAVED TRAIL 3% UNPAVED TRAIL |
| MINIMUM GRADE | 0.50% | 0.50% |
| MINIMONI GRADE | 0.50% | 0.30 % |
| MINIMUM S.S.D. HORIZONTAL | 360 FT. | 100 FT. |
| | | |
| MINIMUM S.S.D. VERTICAL | 360 FT. | 100 FT. |
| | | |
| CLEAR ZONE (TANGENT) | 20 FT. | 5 FT. |
| | | |



PROJECT LOCATION MAP



INDEX OF SHEETS

| 9 | SHE | ET I | <u> </u> | TITLE |
|----|-----|------|------------|--|
| | | 1 | | TITLE SHEET |
| | | 2 | | STANDARD PLANS LIST |
| ; | 3 | - | 4 | GENERAL NOTES |
| | 5 | _ | 10 | TYPICAL SECTIONS |
| 1 | 1 | _ | 12 | SURVEY CONTROL DIAGRAM |
| 1 | 3 | _ | 17 | SUMMARY OF APPROXIMATE QUANTITIES |
| | | 18 | | SUMMARY OF EARTHWORK |
| | | 19 | | TABULATION OF REMOVALS, RESETS AND ADJUSTMENTS |
| | | 20 | | TABULATION OF SURFACING QUANTITIES |
| | | 21 | | TABULATION OF CONCRETE ITEMS |
| | | 22 | | TABULATION OF GUARDRAIL AND FENCING |
| | | 23 | | SURVEY TABULATION |
| 2 | 4 | - | 25 | GEOMETRY PLANS |
| 2 | 26 | _ | 32 | TRAIL PLANS |
| 3 | 33 | _ | 40 | TRAIL PROFILES |
| 4 | 1 | _ | 43 | TYPE 7 GUARDRAIL DETAILS |
| | | 44 | | UTILITY POTHOLE LOG |
| 4 | 5 | - | 55 | PEDESTRIAN BRIDGE PLANS |
| 5 | 6 | - | 67 | CONCRETE BOX CULVERT UNDERCROSSING PLANS |
| 6 | 8 | - | 69 | RAILING DETAILS |
| 7 | 0 | - | 71 | ENGINEERING GEOLOGY |
| | | 72 | | TABULATION OF GROUND NAIL WALL AND ROCK REINFORCEMENT |
| 7 | '3 | - | 76 | GROUND NAIL WALL PLANS |
| | | 77 | | ROCK REINFORCEMENT DETAILS |
| | | 78 | | TABULATION OF DRAINAGE QUANTITIES |
| | | 79 | | DRAINAGE GENERAL NOTES |
| | | 80 | | DRAINAGE DETAILS |
| | | - | 87 | STRUCTURE PROFILES |
| - | 88 | - | 94 | STORMWATER MANAGEMENT PLAN |
| 9 | 95 | - | 101 | EROSION CONTROL PLANS |
| 4. | 03 | 102 | 109 | TABULATIONS OF SIGNS AND PAVEMENT MARKINGS SIGNING AND PAVEMENT MARKING PLANS |
| | | - | | |
| ' | 10 | - | 111 | TRAFFIC CONTROL TARILLATION |
| 4 | | 112 | 110 | TRAFFIC CONTROL TABULATION |
| | | - | 116 121 | SUGGESTED CONSTRUCTION PHASING TYPICAL SECTIONS SUGGESTED CONSTRUCTION PHASING PLANS |
| , | | | 121 | TEMPORARY TRAFFIC SIGNAL PLANS |
| | | 122 | 1.10 | |
| 17 | 23 | - | 140 | CROSS SECTIONS |

Print Date: 11/17/2016 Sheet Revisions File Name: 19888DES_Title.dgn Date: Comments Init. Horiz. Scale: 1:1 Vert. Scale:





| As Constructed | Contract Information | Project No./Code | | |
|----------------|--|------------------|--|--|
| No Revisions: | Resident Engineer: | STU C070-043 | | |
| Revised: | Project Engineer: | 19888 | | |
| Void: | PROJECT STARTED: / / ACCEPTED: / / Comments: | Sheet Number 1 | | |

| PLAN NUMBER | NEW OF | | PAGE NUMBER |
|----------------|--------|---|---|
| M-607-1 | | WIRE FENCES AND GATES (3 SHEETS) | |
| M-607-2 | | CHAIN LINK FENCE (3 SHEETS) | 103-105 |
| M-607-3 | | BARRIER FENCE | 106 |
| M-607-4 | | DEER FENCE, GATES, AND GAME RAMPS (5 SHEETS). (REVISED ON APRIL 30, 2015) | 107-109 |
| M-607-10 | | PICKET SNOW FENCE | 110 |
| M-607-15 | | ROAD CLOSURE GATE (9 SHEETS) | 111-119 |
| M-608-1 | | CURB RAMPS (7 SHEETS) (REVISED ON JUNE 16, 2014) | 120-125 |
| M-609-1 | | CURBS, GUTTERS, AND SIDEWALKS (4 SHEETS) (REVISED JULY 24, | ^{ON} 2012). 126 129 |
| M-611-1 | | CATTLE GUARD (2 SHEETS) | 130-131 |
| M-611-2 | | DEER GUARD (2 SHEETS) (NEW DN APRIL 30, 2015) | |
| M-613-1 | | ROADWAY LIGHTING (4 SHEETS) | 132-135 |
| M-614-1 | | RUMBLE STRIPS (3 SHEETS) | 136-138 |
| M-614-2 | | SAND BARREL ARRAYS (2 SHEETS) | 139-140 |
| M-615-1 | | EMBANKMENT PROTECTOR TYPE 3 | 141 |
| M-615-2 | | EMBANKMENT PROTECTOR TYPE 5 | 142 |
| M-616-1 | | INVERTED SIPHON | 143 |
| M-620-1 | | FIELD LABORATORY CLASS 1 | 144 |
| M-620-2 | | FIELD LABORATORY CLASS 2 (2 SHEETS) | 145-146 |
| M-620-11 | | FIELD OFFICE CLASS 1 | 147 |
| M-620-12 | | FIELD OFFICE CLASS 2 | 148 |
| M-629-1 | | SURVEY MONUMENTS (2 SHEETS) | 149-150 |

COLORADO
DEPARTMENT OF TRANSPORTATION
M&S STANDARDS PLANS LIST
July 04, 2012

Revised on June 24, 2016

ALL OF THE M&S STANDARD PLANS, AS SUPPLEMENTED AND REVISED, APPLY TO THIS PROJECT WHEN USED BY DESIGNATED PAY ITEM OR SUBSIDIARY ITEM.

NEW OR REVISED STANDARD PLAN SHEETS APPLICABLE TO THIS PROJECT, INDICATED BY A MARKED BOX ■, WILL BE ATTACHED TO THE PLANS.

<u>NUMBER</u> TITLE NUMBER S-612-1 GROUND SIGN PLACEMENT (2 SHEETS) (REVISED ON DECEMBER 12, 2014). 158-159 S-614-1 S-614-2 S-614-3 S-614-4 S-614-5 FOR GROUND SIGNS (2 SHEETS) S-614-6 S-614-8 PEDESTRIAN PUSH BUTTON POST ASSEMBLY (REVISED ON MAY 24, 2016) . . 174 S-614-9 S-614-10 S-614-11 S-614-12 FLASHING BEACON AND SIGN INSTALLATIONS (3 SHEETS)..178-180 S-614-14 S-614-20 S-614-21 (REVISED ON MAY 24, 2016) S-614-22 S-614-40 TYPICAL TRAFFIC SIGNAL INSTALLATION DETAILS 184 188 (5 SHEETS) (REVISED ON JUNE 17, 2016) ALTERNATIVE TRAFFIC SIGNAL INSTALLATION DETAILS..... 189 192 S-614-40A 🗖 (4 SHEETS) (REVISED ON JUNE 17, 2016) S-614-41 S-614-42 S-614-43 TRAFFIC LOOP AND MISCELLANEOUS SIGNAL DETAILS......198-207 (10 SHEETS) S-614-44 PEDESTAL POLE SIGNALS (2 SHEETS) (REVISED ON JUNE 17, 2016) S-614-50 (REVISED ON JUNE 17, 2016) S-614-60 DYNAMIC SIGN MONOTUBE STRUCTURES (14 SHEETS)......220-233 (REVISED ON JUNE 17, 2016) S-627-1 TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION......239 258 S-630-1 (24 SHEETS) (REVISED DN JUNE 23, 2016) S-630-2 AND VERTICAL PANELS (REVISED ON JUNE 23, 2016) S-630-3 FLASHING BEACON (PORTABLE) DETAILS260 S-630-4 STEEL SIGN SUPPORT (TEMPORARY) INSTALLATION......261-262 DETAILS (2 SHEETS) S-630-5 PORTABLE RUMBLE STRIPS (TEMPORARY) (2 SHEETS) 263-264 (REVISED ON AUGUST 13, 2015 EMERGENCY PULL-OFF AREA (TEMPORARY)......265 S-630-6 ROLLING ROADBLOCKS FOR TRAFFIC CONTROL......266-268 S-630-7 (3 SHFFTS)

S STANDARD

PAGE

PLAN

NEW OR



Print Date: 11/16/2016

Drawing File Name: 19888DES_StdPlanList.dgn

Horiz. Scale: 1:1

Unit Information

Unit Leader Initials

lder V8I

Sheet Revisions

Date: Comments Init.





| | | | Call before you dig. | |
|----------------|-----------------------|-------------------|----------------------|--|
| As Constructed | BOULDER CANYON | I TRAIL EXTENSION | Project No./Code | |
| No Revisions: | STANDARD | STU C070-043 | | |
| Revised: | | Structure | 19888 | |
| | Detailer: ZDA | Numbers | | |
| Void: | Sheet Subset: GENERAL | Subset Sheets: | Sheet Number 2 | |

- 2. THE CONTRACTOR SHALL HAVE IN HIS POSSESSION ON SITE AT ALL TIMES ONE (1) STAMPED FOR CONSTRUCTION COPY OF THE PLANS AND SPECIFICATIONS WHICH HAVE BEEN APPROVED BY THE COUNTY, AND ONE COPY OF THE CDOT M&S STANDARDS (INCLUDING LATEST REVISIONS)
- 3. IN ACCORDANCE WITH SECTION 630.10 OF THE STANDARD SPECIFICATIONS, THIS PROJECT IS CLASSIFIED AS A SIGNIFICANT PROJECT.
- 4. THE CONTRACTOR SHALL NOTIFY THE OWNER AND ENGINEER OF ANY PROBLEM IN CONFORMING TO THE APPROVED PLANS FOR ANY ELEMENT OF THE PROPOSED IMPROVEMENTS PRIOR TO ITS CONSTRUCTION.
- 5. FOR PLAN QUANTITIES OF PAVEMENT MATERIALS, THE FOLLOWING RATES OF APPLICATIONS WERE USED:
 - AGGREGATE BASE COURSE

@ 133 LBS. PER CU. FT.

HOT MIX ASPHALT

@ 110 LBS. PER SQ. YD./INCH

- TACK COAT DILUTED EMULSIFIED ASPHALT (SLOW-SETTING) @ 0.1 GALS. PER SQ. YD. (DILUTED)
- 6. A TACK COAT OF EMULSIFIED ASPHALT (SLOW SETTING) IS TO BE APPLIED TO IMPROVE BOND AT THE FOLLOWING LOCATIONS:
 - BEFORE PLACING NEW PAVEMENT OVER EXISTING PAVEMENT
 - ALONG THE FACE OF ALL CURBS, GUTTERS, MANHOLES, ADJACENT EXISTING PAVEMENT, AND OTHER SURFACES AGAINST WHICH ASPHALT WILL BE PLACED
 - BETWEEN PAVEMENT COURSES WHEN ORDERED BY THE ENGINEER.
- 7. TACK COAT (DILUTED) FOR THIS PROJECT SHALL BE ONE PART EMULSIFIED ASPHALT (SLOW SETTING) AND ONE PART WATER.
- 8. THE CONTRACTOR SHALL SUBMIT A PAVING SCHEDULE TO THE ENGINEER AT LEAST 5 WORKING DAYS PRIOR TO THE PRE-PAVING CONFERENCE. PAVING SHALL NOT BEGIN UNTIL THE SCHEDULE HAS BEEN ACCEPTED IN WRITING BY THE ENGINEER.
- PRIOR TO PLACING HOT MIX ASPHALT PAVEMENT, THE PAVED SURFACE SHALL BE SWEPT AND CLEANED.
 THIS WILL NOT BE PAID FOR SEPARATELY, BUT SHALL BE INCLUDED IN THE COST OF THE HOT MIX ASPHALT
 PAVEMENT ITEMS.
- 10. ANY LAYER OF HOT MIX ASPHALT THAT IS TO HAVE A SUCCEEDING LAYER PLACED THEREON SHALL BE COMPLETED FULL WIDTH BEFORE SUCCEEDING LAYER IS PLACED.
- 11. WHERE NEW PAVEMENT IS TO ABUT EXISTING PAVEMENT, THE EXISTING PAVEMENT SHALL BE REMOVED TO A NEAT VERTICAL LINE USING A CUTTING SAW OR OTHER METHOD AS APPROVED BY THE ENGINEER. SAW CUTTING ASPHALT SHALL NOT BE PAID FOR SEPARATELY, BUT SHALL BE INCLUDED IN THE COST OF REMOVAL OF ASPHALT MAT
- 12. PRIOR TO PAVING, THE PAVEMENT SUBGRADE SHALL BE PROOF ROLLED WITH A PNEUMATIC TIRED VEHICLE LOADED TO AT LEAST 18 KIPS PER AXLE. AREAS WHICH DEFORM EXCESSIVELY UNDER THE WHEEL LOADS, AS DETERMINED BY THE ENGINEER, SHALL BE REMOVED AND REPLACED PRIOR TO PAVING. IT IS ESTIMATED THAT 20 HOURS OF ITEM 203-01100 PROOFROLLING WILL BE REQUIRED.
- 13. SULFATE EXPOSURE FOR CONCRETE ON THIS PROJECT IS CLASS 0. SEE SPECIFICATION SECTION 601, STRUCTURAL CONCRETE, AND THE PROJECT GEOTECHNICAL REPORT.
- 14. WATER SHALL BE USED AS A DUST PALLIATIVE WHERE REQUIRED. THE CONTRACTOR SHALL PROVIDE A WATER TRUCK ON-SITE FOR DUST CONTROL. LOCATIONS SHALL BE AS DIRECTED BY THE ENGINEER. WATER SHALL NOT BE PAID FOR SEPARATELY.
- 15. DEPTH OF MOISTURE-DENSITY CONTROL FOR THIS PROJECT SHALL BE AS FOLLOWS:
 - FULL DEPTH OF ALL EMBANKMENTS
 - FULL DEPTH FOR AGGREGATE BASE COURSE
 - 6 INCHES FOR BASES OF CUTS AND FILLS
- 16. EXCAVATION REQUIRED FOR COMPACTION OF BASES OF CUTS AND FILLS WILL BE CONSIDERED AS SUBSIDIARY TO THAT OPERATION AND WILL NOT BE PAID FOR SEPARATELY.

- 17. THE TYPES OF COMPACTION FOR THIS PROJECT SHALL BE T-99 FOR FINE GRAIN SOILS AND T-180 FOR AGGREGATE BASE COURSE.
- 18. THE CONTRACTOR SHALL KEEP THE WORK AREA DRY OF STANDING WATER AND SHALL KEEP THE EXCAVATION AREAS FREE FROM STORM RUN-OFF.
- 19. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE ACCEPTANCE AND CONTROL OF ALL SURFACE AND SUBSURFACE DRAINAGE AND GROUNDWATER ENTERING THE PROJECT AREA. THE CONTRACTOR SHALL KEEP THE WORK AREA DRY OF STANDING WATER AND SHALL KEEP THE EXCAVATION AREAS FREE FROM STORM RUN-OFF. REPAIR OF DAMAGES RESULTING FROM RUNOFF IS SOLELY THE RESPONSIBILITY OF THE CONTRACTOR AND SHALL BE INCLUDED IN THE WORK. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING A DEWATERING PERMING FROM THE STATE.
- 20. THE CONTRACTOR SHALL LIMIT CONSTRUCTION ACTIVITIES TO THOSE AREAS WITHIN THE LIMITS OF DISTURBANCE SHOWN ON THE PLANS. ANY DISTURBANCE BEYOND THESE LIMITS SHALL BE RESTORED TO ORIGINAL CONDITION BY THE CONTRACTOR AT THE CONTRACTOR'S EXPENSE. CONSTRUCTION ACTIVITIES IN ADDITION TO NORMAL CONSTRUCTION PROCEDURE SHALL INCLUDE THE PARKING OF VEHICLES OR EQUIPMENT, DISPOSAL OF LITTER, AND ANY OTHER ACTION WHICH WOULD ALTER EXISTING CONDITIONS.
- 21. ANY DAMAGE TO PRESENT HIGHWAY FACILITIES CAUSED BY THE CONTRACTOR SHALL BE REPAIRED IMMEDIATELY AND PRIOR TO CONTINUING OTHER WORK. ANY MUD OR OTHER MATERIAL TRACKED OR OTHERWISE DEPOSITED ON THE ROADWAY AND SIDEWALK SHALL BE REMOVED DAILY OR AS ORDERED BY THE INSPECTOR.
- 22. THE CONTRACTOR SHALL NOT PARK EQUIPMENT OVERNIGHT WITHIN THE CLEAR ZONE LIMITS WITHOUT APPROVED TRAFFIC CONTROL DEVICES IN PLACE.
- 23. CONTRACTOR IS RESPONSIBLE FOR DETERMINING AND OBTAINING A SUITABLE STAGING AREA.
- 24. PRIVATE DRIVEWAYS AND PARKING LOTS SHALL NOT BE USED AS TURNAROUNDS UNLESS WRITTEN PERMISSION IS OBTAINED FROM THE APPROPRIATE LAND OWNER.
- 25. THE CONTRACTOR SHALL PROVIDE AND MAINTAIN ACCESS TO PUBLIC STREETS AND TO PUBLIC AND PRIVATE PROPERTY ADJOINING THE PROJECT. THE CONTRACTOR WILL NOT BE ALLOWED TO SHUT OFF ACCESS TO ANY PROPERTY AND MUST COORDINATE THE WORK WITH THE PROPERTY OWNERS, FIELD FACILITY ACCESS AREAS SHALL BE PROVIDED WITH AN ALL-WEATHER SURFACE AND PLACED WITHIN THE PROJECT LIMITS UNLESS OTHERWISE APPROVED BY THE ENGINEER. THIS WORK SHALL NOT BE PAID FOR SEPARATELY, BUT SHALL BE INCLUDED IN THE COST OF THE WORK.
- 26. ALL EXISTING SURVEY MONUMENTATION DESIGNATED TO REMAIN SHALL BE PROTECTED FROM DAMAGE BY THE CONTRACTOR DURING CONSTRUCTION OPERATIONS. ANY MONUMENTS DISTURBED BY THE CONTRACTOR THAT ARE NOT DESIGNATED FOR RELOCATION, SHALL BE RESET AT THE CONTRACTOR'S EXPENSE. THE CONTRACTOR AND ENGINEER SHALL NOTE THOSE MONUMENTS IN THE FIELD PRIOR TO CONSTRUCTION.
- 27. UNLESS OTHERWISE SPECIFIED IN THE PLANS, ALL WASTE MATERIALS GENERATED WITHIN THE PROJECT LIMITS SHALL BE REMOVED FROM THE PROJECT AND DISPOSED OF BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE PROJECT. IT WILL BE THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN A DISPOSAL SITE AND REQUIRED PERMITS FOR ALL UNUSABLE MATERIALS.
- 28. IT IS ESTIMATED THAT THE FOLLOWING ITEMS WILL BE REQUIRED:

| ITEM NO. 201-00000 CLEARING AND GRUBBING | 1 (LUMP SUM) | ITEM NO. 240-00000 WILDLIFE BIOLOGIST | 16 (HOURS) | ITEM NO. 240-00010 REMOVAL OF NESTS | 8 (HOURS) |

ITEM NO. 240-00020 NETTING 100 (SQUARE YARDS)

MAINTENANCE OF THE SANITARY FACILITY SHALL INCLUDE CLEANING AT LEAST TWICE A WEEK.

NOTE: ALL ITEMS LISTED AND DESCRIBED HEREIN AS REQUIRED FOR THE COMPLETION OF THE PROJECT SHALL BE PLACED AS DIRECTED BY THE PROJECT ENGINEER.




Print Date: 11/16/2016

Drawing File Name: 19888DES_Gen Notes.dgn

Horiz. Scale: 1:1 Vert. Scale: As Noted

Unit Information Unit Leader Initials

MULLER







| | | | | | | | Call before you o | dig. | | | |
|---|----------------|-----------------------------|---------|-------------|------|--------|-------------------|------|--|--|--|
| | As Constructed | BOULDER CANYON TRAIL EXTENS | | | | | Project No./Code | | | | |
| ı | No Revisions: | GENERAL NOTES | | | | | STU C070-043 | | | | |
| | Revised: | Designer: | | Structure | | | 19888 | | | | |
| ı | | Detailer: | ZDA | Numbers | | | | _ | | | |
| | Void: | Sheet Subset: | GENERAL | Subset Shee | ets: | 1 of 2 | Sheet Number | 3 | | | |

M

29. PRIOR TO THE PERMANENT INCORPORATION OF STEEL OR IRON PRODUCTS INTO THE PROJECT, THE CONTRACTOR SHALL FURNISH TO THE PROJECT ENGINEER A WRITTEN STATEMENT SIGNED BY THE CONTRACTOR (SEE EXAMPLES IN THE FIELD MATERIALS MANUAL) THAT THE CERTIFICATIONS REQUIRED BY THE BUY AMERICA SPECIFICATION ARE ON FILE AND THE STEEL OR IRON PRODUCTS ARE IN COMPLIANCE WITH THE BUY AMERICA SPECIFICATION.

UTILITY GENERAL NOTES:

UTILITY LINES AS SHOWN ON THE PLAN SHEETS ARE PLOTTED FROM THE BEST AVAILABLE INFORMATION. (ASCE STANDARD QUALITY LEVEL C) THE CONTRACTOR'S ATTENTION IS DIRECTED TO SUBSECTION 105.11 OF THE STANDARD SPECIFICATIONS CONCERNING UTILITIES.

THE CONTRACTOR SHALL COMPLY WITH ARTICLE 1.5 OF TITLE 9, CRS ("EXCAVATION REQUIREMENTS") WHEN EXCAVATING OR GRADING IS PLANNED IN THE AREA OF UNDERGROUND UTILITY FACILITIES. THE CONTRACTOR SHALL NOTIFY ALL AFFECTED UTILITIES AT LEAST TWO (2) BUSINESS DAYS, NOT INCLUDING THE ACTUAL DAY OF NOTICE, PRIOR TO COMMENCING SUCH OPERATIONS. THE CONTRACTOR SHALL CONTACT THE UTILITY NOTIFICATION CENTER OF COLORADO (UNCC) AT PHONE NO. 1-800-922-1987, TO HAVE LOCATIONS OF UNCC REGISTERED LINES MARKED BY MEMBER COMPANIES. ALL OTHER UNDERGROUND FACILITIES SHALL BE LOCATED BY CONTACTING THE RESPECTIVE OWNER. UTILITY SERVICE LATERALS SHALL ALSO BE LOCATED PRIOR TO BEGINNING EXCAVATION OR GRADING.

KNOWN UTILITIES ARE:

CDOT CENTURY LINK CITY OF BOULDER XCEL ENERGY STORM SEWER TELEPHONE/FIBER OPTIC WATER SUPPLY ELECTRIC DISTRIBUTION

SEE THE UTILITY SPECIFICATION FOR CONTACT INFORMATION.

- 1. THE CONTRACTOR ASSUMES RESPONSIBILITY FOR THE PROTECTION OF ALL UTILITIES DURING THE WORK. REPAIR OF DAMAGE TO EXISTING UTILITIES DURING CONSTRUCTION SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. PRIOR TO ANY EXCAVATION, CONTACT THE UTILITY NOTIFICATION CENTER OF COLORADO (UNCC) AT 811 AT LEAST TWO WORKING DAYS PRIOR TO DIGGING.
- 2. THE INFORMATION SHOWN ON THESE PLANS CONCERNING TYPE AND LOCATION OF UTILITIES IS NOT GUARANTEED TO BE ACCURATE OR ALL INCLUSIVE. SOME UTILITIES MAY HAVE BEEN ADDED OR RELOCATED PRIOR TO CONSTRUCTION. ALSO, SERVICES TO INDIVIDUAL RESIDENCES, PLACES OF BUSINESS, AND OTHER PRIVATELY-OWNED UTILITY LINES ARE NORMALLY NOT SHOWN ON THE DRAWINGS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL LOCATIONS OF EXISTING STRUCTURES AND UTILITIES SHOWN ON THE DRAWINGS AND TO ASCERTAIN WHETHER ANY OTHER STRUCTURES AND UTILITIES MAY EXIST. EVERY REASONABLE MEANS SHALL BE USED, INCLUDING FIELD LOCATION OF THE UTILITY USING WHATEVER PROSPECTING MEANS ARE NECESSARY.
- 3. PROSPECTING FOR EXISTING UTILITIES WILL BE PAID FOR AS POTHOLING. USE OF THE TERM "POTHOLING" SHALL NOT BE CONSTRUED TO IMPLY ANY PARTICULAR METHOD OF PROSPECTING. IT IS ESTIMATED THAT 40 HOURS OF ITEM 203-01597 POTHOLING WILL BE NEEDED AS PART OF THIS PROJECT. POTHOLING OF AN AREA SHALL TAKE PLACE AT LEAST 10 DAYS PRIOR TO COMMENCEMENT OF CONSTRUCTION OPERATIONS IN THAT AREA. HOURS APPROVED FOR PAYMENT UNDER THIS PAY ITEM SHALL BE AT THE DISCRETION OF THE FNGINFER
- 4. THE CONTRACTOR SHALL LOCATE AND POTHOLE ALL POTENTIAL CONFLICTS BETWEEN EXISTING BURIED UTILITY FACILITIES AND THE PROPOSED CONSTRUCTION AS SHOWN ON THE PLANS OR BY FIELD LOCATION MARKINGS. IF CONFLICTS EXIST, MODIFY PROPOSED CONSTRUCTION PLANS TO AVOID ALL EXISTING BURIED UTILITY FACILITIES.
- 5. THE CONTRACTOR SHALL VERIFY AND DOCUMENT THE CONDITION OF EXISTING UTILITIES (VISIBLE FACILITIES) WITH THE ENGINEER AND REPRESENTATIVES FROM THE UTILITY COMPANIES PRIOR TO COMMENCEMENT OF CONSTRUCTION.
- 6. WITH NOTIFICATION OF THE RESPECTIVE OWNER, ADJUST RIMS OF ALL MANHOLES, CLEANOUTS, VALVE BOXES AND SURVEY MONUMENTS TO FINISH GRADE AND PATCH AFTER FINAL LIFT PAVING.

- 7. THE CONTRACTOR SHALL SUBMIT AN XCEL ENERGY BUILDER'S CALL LINE APPLICATION FOR EVERY XCEL ENERGY WORK ELEMENT THAT IS TO BE COORDINATED WITH THE PROJECT. THE REQUEST IS TO BE PROCESSED THROUGH XCEL ENERGY-BUILDER'S CALL LINE AT 1-800-628-2121.
- 8. THE CONTRACTOR SHALL REFER TO THE UTILITY SPECIFICATION AND UTILITY PLANS FOR COORDINATION REQUIRED FOR UTILITY RELOCATIONS.


SIGNING, STRIPING AND PAVEMENT MARKING NOTES:

- 1. SIGN POSTS SHALL BE 2" X 2" X 10' (14 GAUGE) GALVANIZED PERFORATED SQUARE STEEL TUBING.
- 2. SIGN POST BASES SHALL BE 2 1/4" X 2 1/4" (12 GAUGE, 2' IN LENGTH) GALVANIZED PERFORATED SQUARE STEEL TUBING.
- 3. BASES SHALL BE INCLUDED IN THE COST FOR SIGN POSTS. TOP OF BASES SHALL BE 3" ± ABOVE FINISHED GRADE. THE SIGN POST SHALL BE INSTALLED 4" INTO THE BASE AND BOLTED BOTH WAYS.
- 4. SIGN POST LOCATIONS SHALL BE APPROVED BY THE ENGINEER AND ROAD MAINTENANCE SIGN SHOP REPRESENTATIVE PRIOR TO INSTALLATION.
- 5. THICKNESS OF ALL SIGN PANELS SHALL BE 0.100"
- 6. FINAL PAVEMENT STRIPING SHALL BE EPOXY PER CDOT STANDARD SPECIFICATIONS.
- 7. ALL PAVEMENT MARKING SYMBOLS SHALL BE WHITE, PREFORMED THERMOPLASTIC, "PREMARK" OR EQUIVALENT.
- 8. PAVEMENT MARKING ARROWS SHALL BE ELONGATED.
- 9. PAVEMENT MARKINGS FOR BIKE LANES SHALL BE PER MUTCD FIG 9C-3 B WITH HELMETED BICYCLE SYMBOL.
- 10. PREFORMED THERMOPLASTIC INSTALLATION ON CONCRETE SHALL HAVE THE CONCRETE CURE REMOVED PRIOR TO INSTALLATION OR A BONDING AGENT APPLIED TO THE CONCRETE BEFORE INSTALLATION. INSTALLATION SHALL FOLLOW MANUFACTURER'S SPECIFICATIONS.

ENVIRONMENTAL GENERAL NOTES:

1. REMOVAL OF TREES AND SHRUBS SHALL BE CONDUCTED BETWEEN SEPTEMBER 1 AND FEBRUARY 15 TO AVOID IMPACTS TO ACTIVE BIRD NESTS. IF THE DESIGNATED TREES OR SHRUBS CANNOT BE REMOVED PRIOR TO FEBRUARY 16, THE TREES AND SHRUBS SHALL BE SURVEYED FOR ACTIVE NESTS BY AN EXPERIENCED BIOLOGIST BEFORE REMOVAL. IF ACTIVE NESTS ARE LOCATED, WORK ZONE BUFFERS MUST BE PROVIDED AROUND ACTIVE NESTS PER CURRENT USFWS AND CPW GUIDELINES. THESE SURVEY AND BUFFER REQUIREMENTS FOR MIGRATORY BIRD NESTS DO NOT APPLY IF THE VEGETATION REMOVAL WORK IS CONDUCTED OUTSIDE OF THE FEBRUARY 16 TO AUGUST 31 MIGRATORY BIRD SEASON.











| | | | | | | Call before you | aıg. | | | |
|----------------|--------------------------------|---------|-------------|------|--------|-----------------|------|--|--|--|
| As Constructed | BOULDER CANYON TRAIL EXTENSION | | | | | Project No./Cod | | | | |
| No Revisions: | | GENERA | L NOTE | S | | STU C070-04. | 3 | | | |
| Revised: | Designer: | SDB | Structure | | | 19888 | | | | |
| | Detailer: | ZDA | Numbers | | | | _ | | | |
| Void: | Sheet Subset: | GENERAL | Subset Shee | ets: | 2 of 2 | Sheet Number | 4 | | | |





TYPICAL SECTION NOTES


- 1. P.G.L. PROFILE GRADE LINE
- 2. THE CONTRACTOR WILL BE REQUIRED TO PLACE 4 INCHES OF TOPSOIL TO THIS LINE AFTER COMPLETION OF PAVING OPERATION.
- BREAKPOINTS IN SLOPES SHALL BE ROUNDED DURING CONSTRUCTION FOR A PLEASING APPEARANCE. *3.* ▲
- 4. SEE TRAIL PLANS FOR LOCATION OF CONTROL
- 2% TRAIL CROSS SLOPE (MAXIMUM, TYPICAL).SEE TRAIL PROFILE SHEETS FOR SLOPE DIRECTION 5. 🖊 TRANSITION AND LOCATIONS.
- DEPTH OF SCARIFICATION AND MOISTURE-DENSITY CONTROL AT BASES OF CUTS AND FILLS SHALL BE 6 INCHES MINIMUM.
- SLOPE VARIES IN SDME LOCATIONS, SEE CROSS SECTIONS.
- DESIRABLE WIDTH, WIDTH MAY BE REDUCED IN 8. \Diamond CONSTRAINED AREAS.
- APPROXIMATE THICKNESS (MINIMUM)
- PAVEMENT SHOWN ON EACH TYPICAL SECTION ARE REPRESENTATIVE OF A GENERAL CONDITION ONLY. SEE PAVEMENT SECTIONS SHOWN BELOW AND TRAIL PLAN SHEETS FOR EXACT STATION RANGES AND LOCATIONS OF THE DIFFERENT PAVEMENTS.



- 2" H.M.A. GRADING (S)(75)(PG58-28)
- 3.5" H.M.A. GRADING (S)(75)(PG 58-28)
- 6" AGGREGATE BASE COURSE

FULL DEPTH WIDENING - IN FRONT OF TYPE 7 BARRIERS AND ABOVE UNDERPASS.


ROADWAY PAVEMENT SECTION - SH 119



- 6" CONCRETE BIKEWAY
- 6" AGGREGATE BASE COURSE CLASS 6

PAVED SECTION

APPLIES STA. 102+50 - STA. 110+10 STA. 116+35 - STA. 136+90



6" CRUSHER FINES ■ (PAID FOR AS AGGREGATE BASE COURSE SPECIAL)

AASHTO M288 CLASS 3 GEOTEXTILE WEED BARRIER (WEED BARRIER SHALL NOT BE MEASURED AND PAID FOR SEPERATELY BUT SHALL BE INCLUDED IN THE BID COST OF AGGREGATE BASE COURSE (SPECIAL))


UNPAVED SECTION

APPLIES STA. 110+10 - STA. 116+35 STA. 136+90- STA. 139+53

PATH PAVEMENT SECTION

| ŧ | | | | | | | | <u>1 A 11</u> | TTAVEMENT SECTION | | |
|--------|--|-----|-------|-----------------|-------|----------|-------|----------------|--------------------------------------|--------|------------------|
| 쑤 | Print Date: 11/16/2016 | | | Sheet Revisions | | | _ | As Constructed | BOULDER CANYON TRAIL EXTENSION | 1 | Project No./Code |
| 莅 | Drawing File Name: 19888DES_Typical Sections.dgn | 1 ' | Date: | Comments | Init. | A COOL | | | TYPICAL SECTIONS | ⊢ | STU 0070 047 |
| J | Horiz. Scale: 1:10 Vert. Scale: As Noted | . — | | | | | ulder | No Revisions: | | | STU C070-043 |
| 016 | Unit Information Unit Leader Initials | | | | | | unty | Revised: | Designer: SDB Structure | | 19888 |
| 7/9 | MULLER | | | | | | | \/ - * -l- | Detailer: CZC Numbers | | Chart Number E |
| \geq | ENGINEERING COMPANY | | | | | Region 4 | | Void: | Sheet Subset: TYPICAL Subset Sheets: | I of 6 | Sheet Number 5 |

Canyon BW.tbl 08 PM Q:\2015 Projects\15-025.01 Boulder CDDT-DefaultPrinter_V8i.pltcfg CDDT V81



Numbers

Subset Sheets:

6

Sheet Number


CZC


TYPICAL

Detailer:

Sheet Subset:

Void:





TYPICAL SECTION NOTES

- 1. P.G.L. PROFILE GRADE LINE
- 2.

 THE CONTRACTOR WILL BE REQUIRED TO PLACE 4 INCHES OF TOPSOIL TO THIS LINE AFTER COMPLETION OF PAVING OPERATION.
- BREAKPOINTS IN SLOPES SHALL BE ROUNDED DURING CONSTRUCTION FOR A PLEASING APPEARANCE.
- 4. SEE TRAIL PLANS FOR LOCATION OF CONTROL LINE.
- 5. 2% TRAIL CROSS SLOPE (MAXIMUM, TYPICAL).SEE TRAIL PROFILE SHEETS FOR SLOPE DIRECTION TRANSITION AND LOCATIONS.
- 6. # DEPTH OF SCARIFICATION AND MOISTURE-DENSITY CONTROL AT BASES OF CUTS AND FILLS SHALL BE 6 INCHES MINIMUM.
- 7. * SLOPE VARIES IN SOME LOCATIONS, SEE CROSS SECTIONS.
- 8. \diamondsuit DESIRABLE WIDTH. WIDTH MAY BE REDUCED IN CONSTRAINED AREAS.
- 9. APPROXIMATE THICKNESS (MINIMUM)
- 10. PAVEMENT SHOWN ON EACH TYPICAL SECTION
 ARE REPRESENTATIVE OF A GENERAL CONDITION
 ONLY. SEE PAVEMENT SECTIONS SHOWN BELOW
 AND TRAIL PLAN SHEETS FOR EXACT STATION
 RANGES AND LOCATIONS OF THE DIFFERENT
 PAVEMENTS.

Print Date: 11/16/2016


Drawing File Name: 19888DES_Typical Sections.dgn

Horiz. Scale: 1:10

Vert. Scale: As Noted

Unit Information

Unit Leader Initials






| As Constructed | BOULDE | Project No./Code | | | | | |
|----------------|---------------|------------------|-------------|------|--------|--------------|---|
| No Revisions: | TY | PICAL | SECTI | DNS | | STU C070-043 | |
| Revised: | Designer: | | Structure | | | 19888 | |
| | Detailer: | CZC | Numbers | | | | |
| Void: | Sheet Subset: | TYPICAL | Subset Shee | ets: | 3 of 6 | Sheet Number | 7 |

BOULDER CANYON TRAIL

STA. 120+49 - 124+91



CONTRACTOR IS TO SAWCUT ALONG EXISTING WHITE STRIPE AND INSTALL CURB AND GUTTER SUCH THAT THE PANLINE OF THE GUTTER MATCHES THE EXISTING GRADE OF SH 119. THE SHARED ALPS INN DRIVEWAY / TRAIL TO BE CONSTRUCTED AT A FINISHED GRADE OF 2% FROM THE PROFILE GRADE LINE (P.G.L.). THE SLOPE IN BETWEEN THE BACK OF CURB AND EDGE OF DRIVEWAY / TRAIL IS VARIABLE, FROM APPROXIMATELY 2% TO 5:1.

TYPICAL SECTION NOTES 1. P.G.L. PROFILE GRADE LINE

APPEARANCE.

2.

4.

6. #

8.

9.

THE CONTRACTOR WILL BE REQUIRED TO PLACE 4 INCHES OF TOPSOIL TO THIS LINE AFTER COMPLETION OF PAVING OPERATION.

BREAKPOINTS IN SLOPES SHALL BE ROUNDED DURING CONSTRUCTION FOR A PLEASING

SEE TRAIL PLANS FOR LOCATION OF CONTROL

2% TRAIL CROSS SLOPE (MAXIMUM, TYPICAL).SEE TRAIL PROFILE SHEETS FOR SLOPE DIRECTION

DEPTH OF SCARIFICATION AND MOISTURE-DENSITY CONTROL AT BASES OF CUTS AND FILLS SHALL BE

SLOPE VARIES IN SOME LOCATIONS, SEE CROSS SECTIONS.

DESIRABLE WIDTH, WIDTH MAY BE REDUCED IN CONSTRAINED AREAS.

PAVEMENT SHOWN ON EACH TYPICAL SECTION ARE REPRESENTATIVE OF A GENERAL CONDITION ONLY. SEE PAVEMENT SECTIONS SHOWN BELOW AND TRAIL PLAN SHEETS FOR EXACT STATION RANGES AND LOCATIONS OF THE DIFFERENT PAVEMENTS

APPROXIMATE THICKNESS (MINIMUM)

TRANSITION AND LOCATIONS.

6 INCHES MINIMUM.


PAVEMENTS.

BOULDER CANYON TRAIL

STA. 125+33 - STA. 129+37


CO

Print Date: 11/16/2016 Drawing File Name: 19888DES_Typical Sections.dgn Horiz. Scale: 1:10 Vert. Scale: As Noted Unit Information Unit Leader Initials






| As Constructed | | TRAIL EXTENSION | | | Project No./Code | | | |
|----------------|----------------------------|-----------------|----------------------|-----|------------------|--------------|---|--|
| No Revisions: | TYF | PICAL | SECTIO | DNS | | STU C070-043 | i | |
| Revised: | Designer: | | Structure Numbers | | | 19888 | | |
| Void: | Detailer: Sheet Subset: | | | | 1 of 6 | Sheet Number | 8 | |




BOULDER CANYON TRAIL
STA. 129+37 - STA. 130+82




BOULDER CANYON TRAIL STA. 130+82 - STA. 131+00

TYPICAL SECTION NOTES

- 1. P.G.L. PROFILE GRADE LINE
- 2. ϕ THE CONTRACTOR WILL BE REQUIRED TO PLACE 4 INCHES OF TOPSOIL TO THIS LINE AFTER COMPLETION OF PAVING OPERATION.
- 3. A BREAKPOINTS IN SLOPES SHALL BE ROUNDED DURING CONSTRUCTION FOR A PLEASING APPEARANCE.
- 4. SEE TRAIL PLANS FOR LOCATION OF CONTROL LINE.
- 5. 2% TRAIL CROSS SLOPE (MAXIMUM, TYPICAL).SEE TRAIL PROFILE SHEETS FOR SLOPE DIRECTION TRANSITION AND LOCATIONS.
- 6. # DEPTH OF SCARIFICATION AND MOISTURE-DENSITY CONTROL AT BASES OF CUTS AND FILLS SHALL BE 6 INCHES MINIMUM.
- 7. * SLOPE VARIES IN SOME LOCATIONS, SEE CROSS SECTIONS.
- 8. \diamondsuit DESIRABLE WIDTH. WIDTH MAY BE REDUCED IN CONSTRAINED AREAS.
- 9. APPROXIMATE THICKNESS (MINIMUM)
- 10. PAVEMENT SHOWN ON EACH TYPICAL SECTION ARE REPRESENTATIVE OF A GENERAL CONDITION ONLY. SEE PAVEMENT SECTIONS SHOWN BELOW AND TRAIL PLAN SHEETS FOR EXACT STATION RANGES AND LOCATIONS OF THE DIFFERENT PAVEMENTS.



BOULDER CANYON TRAIL STA. 131+00 - STA. 131+75



BOULDER CANYON TRAIL

TA. 131+75 - STA. 131+75 - STA. 134+00


| Print Date: 11/16/2016 | |
|------------------------------------|-----------------------|
| Drawing File Name: 19888DES_Typica | al Sections.dgn |
| Horiz. Scale: 1:10 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| MUL ENGINEERIN | LER IG COMPANY |

| | Sheet Revisions | | | | | | | | | |
|-------|-----------------|--|--|--|--|--|--|--|--|--|
| Date: | Init. | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |





| As Constructed | BOULDI | Project No./C | ode | | | | |
|----------------|---------------|---------------|------------|--------------|--------|--------------|---|
| No Revisions: |] T` | YPICAL | | STU C070-043 | | | |
| Revised: | Designer: | SDB | Structure | | | 19888 | |
| | Detailer: | CZC | Numbers | | · | | |
| Void: | Sheet Subset: | TYPICAL | Subset She | ets: | 5 of 6 | Sheet Number | 9 |



Void:

Sheet Subset:

TYPICAL

Subset Sheets:

Sheet Number

10

zadkison 3:20:44 PM 0:\2015 Projects\15-025.01 Boulder Cany

Colorado Department of Transportation

1420 2nd Street Greeley, CD 80631 Phone: 970-350-2161

Region 4

| | MDG |
|-----|-------------------|
| 420 | FAX: 970-350-2223 |

| | Sheet Revisions | | | Sheet Revisions | | Sheet Revisions | | |
|------|-----------------|----------|------|-----------------|----------|-----------------|-------------|----------|
| Date | Description | Initials | Date | Description | Initials | Date | Description | Initials |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

| Project Control Diagram | | | | | | | | | |
|----------------------------------|----------------|--------------------|-----------|--|--|--|--|--|--|
| Title Sheet | | | | | | | | | |
| Project Number: ER 119A-065 | | | | | | | | | |
| Project Lo | cation: SH 11 | .9A Boulder Canyon | | | | | | | |
| | | | | | | | | | |
| Project Code: | Last Mod. Date | Subset | Sheet No. | | | | | | |
| 20258 06-16-15 3.01 of 3.02 3.01 | | | | | | | | | |

DEPARTMENT OF TRANSPORTATION OUARTER, SIXTEENTH, AND SECTION CORNERS STATE OF COLORADO STATE OF COLORADO


SHEET NO. INDEX OF SHEETS

3.01 3.02

Title Sheet Coordinate Tables

PROJECT CONTROL DIAGRAM

State Highway 119 MP 38.95 to 40.84 Sections 26, 27, 34, 35, 36 Township 1 North, Range 71 West of the 6th Principal Meridian County of Boulder



CONTROL MONUMENT

Note: For a complete listing of symbology used within this set of plans, please refer to the M-100-1 Standard Symbols of the Colorado Department of Transportation M&S Standards Publication dated July 2012. Existing features are shown as screened weight (gray scale). Proposed or new features are shown as full weight without screening.




Typical Control Monument Cap Not to Scale

NETWORK CONTROL MONUMENT

CM-MP - Control Point Monuments set by CDOT. They are CDOT Type 2 monuments, a $3^{1}/4^{11}$ dia. aluminum control monument cap (as shown) on a $3^{1} \times 3^{3}/4^{11}$ dia. aluminum security rod on a $3^{1} \times 3^{3}/4^{11}$ dia. smooth aluminum rod.

General Notes:

- 1. This Project Control Diagram is not a boundary survey of the adjoining property and is prepared for the Colorado Department of Transportation purposes only.
- 2. This plan set is subject to change and may not be the most current set. It is the user's responsibility to verify with CDOT that this set is the most current. The information contained on the attached drawing is not valid unless this copy bears an original signature of the Professional Land Surveyor hereon named.
- 3. Refer to the M-629-1 Survey Monuments of the Standard Plans dated July, 2012 found in The Colorado Department of Transportation, M & S Standards for typical survey monument descriptions.





Basis of Bearings: Bearings used in the calculations of coordinates are based on a grid bearing of S 48° 29'19" W from the Control Monument "CM 3974" (CDOT Type 2 Monument, MP 39.74), Section 26, Township 1 North, Range 71 West, Sixth P.M. and the Control Monument "CM 3991" (CDOT Type 2 Monument, MP 39.91), Section 35, Township 1 North, Range 71 West, Sixth P.M. as obtained from a Global Positioning System (GPS) survey based on the National Spatial Reference System (NSRS).

Basis of Elevations: Project elevations are GPS derived, using GEDID 12A, based on a NAVD 88 elevation of 1679.110m on NGS Benchmark "B 322 RESET" (Stamped "B 322 RESET 1955" NGS bench mark disk set in top of concrete monument).

COORDINATE DATUM: Project coordinates are modified Colorado State Plane North Zone NAD 83(2011) coordinates. The project seed point (CM 3969) coordinates are: Northing = 380520.658m, Easting = 930314.320m, and Elevation = 1701.747m. The ground scale factor used to modify the coordinates is 1.00030119695015. Project Coordinates are truncated by 350,000m in the Northing and 900,000m in the Easting.

To get from Project to State Plane coordinates: convert project coordinates to metric, add the truncation, subtract the seed point northing and easting, divide by the ground scale factor, then add the seed point northing and easting.

NOTICE: According to Colorado law you must commence any legal action based upon any defect in this survey within three years after you first discover such defect. In no event may any action based upon any defect in this survey be commenced more than ten years from the date of the certification shown hereon.

SURVEYOR STATEMENT (PROJECT CONTROL DIAGRAM)

I, Lee K Groves, a professional land surveyor licensed in the State of Colorado, do hereby state to the Colorado Department of Transportation this Project Control Diagram was prepared and the field survey it represents was performed under my responsible charge and, based upon my knowledge, information and belief is in accordance with applicable standards of practice defined by Colorado Department of Transportation publications. This statement is not a guaranty or warranty, either expressed or implied.

PLS No. 34169

ין סרכשי שייר ליינים אייר ליינים איינים ליינים איינים ליינים איינים איינים איינים איינים איינים איינים איינים א

-11

Colorado Department of Transportation



| | Sheet Revisions | | | Sheet Revisions | | Sheet Revisions | | | |
|------|-----------------|----------|------|-----------------|----------|-----------------|-------------|----------|---|
| Date | Description | Initials | Date | Description | Initials | Date | Description | Initials | i |
| | | | | | | | | | í |
| | | | | | | | | | i |
| | | | | | | | | | i |
| | | | | | | | | | i |
| | | | | | | | | | i |
| | | | | | | | | | i |
| | | | | | | | | | |

| Project Control Diagram | | | | | | | | |
|--|--|--|--|--|--|--|--|--|
| Coordinate Tables | | | | | | | | |
| Project Number: ER 119A-065 | | | | | | | | |
| Project Location: SH 119A Boulder Canyon | | | | | | | | |
| | | | | | | | | |
| reject Code Last Med Date Subset Sheet No. | | | | | | | | |



| | CHARN GEODETIC COORDINATE TABLE | | | | | | | | | | | |
|-------------|---------------------------------|--------------------|----------|----------|-------------|--------------|------------|---|--|--|--|--|
| | (adjusted field data) (meters) | | | | | | | | | | | |
| NAME | COORDINATES | S NAD 83(2011) | ELLIPS. | MAPPING | SCALE | NAD 83(2011) | ZONE 0501 | DESCRIPTION | | | | |
| MAMIL | LATITUDE | LONGITUDE | HEIGHT | ANGLE | OUALL | NORTHING | EASTING | BESOKII TICI | | | | |
| B322 RESET | 40°04'47.97652" N | 105°16'55.00193" W | 1663.576 | 0°08'27" | 0.999961264 | 387725.123 | 932999.902 | NGS Bench Mark Disk in concrete post | | | | |
| BILLINGSLEY | 40°00'22.22420" N | 105°20'55.72917" W | 1876.842 | 0°05'52" | 0.999965907 | 379516.913 | 927310.605 | NGS Horizontal Control Disk in rock outcrop | | | | |
| | | | | | | | | | | | | |



| ı | PROJECT COORDINATE SUMMARY TABLE (feet) | | | | | | | | | |
|---------|---|------------|-----------|----------------------|------------|--|--|--|--|--|
| NAME | PROJECT COORDINATES | | ELEV. | DESCRIPT | ION | | | | | |
| NAME | NORTHING | EASTING | (NAVD 88) | DESCRIPT | ION | | | | | |
| CM 3895 | 100226.100 | 96465.698 | 5744.473 | CDOT Type 2 Monument | (MP 38.95) | | | | | |
| CM 3907 | 99892.471 | 97031.939 | 5729.290 | CDOT Type 2 Monument | (MP 39.07) | | | | | |
| CM 3919 | 100019.747 | 97620.529 | 5716.600 | CDOT Type 2 Monument | (MP 39.19) | | | | | |
| CM 3951 | 99313.227 | 98956.487 | 5664.493 | CDOT Type 2 Monument | (MP 39.51) | | | | | |
| CM 3969 | 100133.191 | 99456.231 | 5633.154 | CDOT Type 2 Monument | (MP 39.69) | | | | | |
| CM 3974 | 100093.335 | 99760.529 | 5624.268 | CDOT Type 2 Monument | (MP 39.74) | | | | | |
| CM 3991 | 99530.724 | 100396.192 | 5589.755 | CDOT Type 2 Monument | (MP 39.91) | | | | | |
| CM 4043 | 99070.773 | 102636.703 | 5479.179 | CDOT Type 2 Monument | (MP 40.43) | | | | | |
| CM 4071 | 99548.114 | 103594.578 | 5441.698 | CDOT Type 2 Monument | (MP 40.71) | | | | | |
| CM 4084 | 99514.396 | 104266.320 | 5436.338 | CDOT Type 2 Monument | (MP 40.84) | | | | | |
| | | | | | | | | | | |



| | GEODETIC COORDINATE TABLE | | | | | | | | | |
|--------------------------------|---------------------------|--------------------|----------|----------|-------------|--------------|------------|------------------------|-----------|--|
| (adjusted field data) (meters) | | | | | | | | | | |
| NAME | COORDINATES NAD 83(2011) | | ELLIPS. | MAPPING | SCALE | NAD 83(2011) | ZONE 0501 | DESCRIPTION | | |
| NAME | LATITUDE | LONGITUDE | HEIGHT | ANGLE | I SCALE F | NORTHING | EASTING | DESCRIPTION | | |
| CM 3895 | 40°00'55.56179" N | 105°19'27.41851" W | 1735.791 | 0°06'49" | 0.999965234 | 380548.968 | 929403.078 | CDOT Type 2 Monument (| MP 38.95) | |
| CM 3907 | 40°00'52.25449" N | 105°19'20.15141" W | 1731.142 | 0°06'53" | 0.999965300 | 380447.308 | 929575.617 | CDOT Type 2 Monument | MP 39.07) | |
| CM 3919 | 40°00'53.50022" N | 105°19'12.58534" W | 1727.252 | 0°06'58" | 0.999965275 | 380486.090 | 929754.965 | CDOT Type 2 Monument (| MP 39.19) | |
| CM 3951 | 40°00'46.49291" N | 105°18'55.43852" W | 1711.321 | 0°07'09" | 0.999965415 | 380270.807 | 930162.043 | CDOT Type 2 Monument (| MP 39.51) | |
| CM 3969 | 40°00'54.58355" N | 105°18'48.99534" W | 1701.747 | 0°07'14" | 0.999965253 | 380520.658 | 930314.320 | CDOT Type 2 Monument (| MP 39.69) | |
| CM 3974 | 40°00'54.18345" N | 105°18'45.08649" W | 1699.027 | 0°07'16" | 0.999965261 | 380508.513 | 930407.042 | CDOT Type 2 Monument | MP 39.74) | |
| CM 3991 | 40°00'48.61169" N | 105°18'36.93430" W | 1688.484 | 0°07'21" | 0.999965372 | 380337.081 | 930600.734 | CDOT Type 2 Monument | MP 39.91) | |
| CM 4043 | 40°00'44.01916" N | 105°18'08.15974" W | 1654.696 | 0°07'40" | 0.999965464 | 380196.929 | 931283.438 | CDOT Type 2 Monument | MP 40.43) | |
| CM 4071 | 40°00'48.71385" N | 105°17'55.83857" W | 1643.232 | 0°07'48" | 0.999965370 | 380342.380 | 931575.311 | CDOT Type 2 Monument | MP 40.71) | |
| CM 4084 | 40°00'48.36558" N | 105°17'47.20853" W | 1641.573 | 0°07'53" | 0.999965377 | 380332.105 | 931779.997 | CDOT Type 2 Monument | MP 40.84) | |
| | | | | | | | | | | |



| INDEX | CONTRACT | CONTRACT ITEM | ROADWAY | | | | | | | | | | | | PROJECT TOTALS | | |
|-------------|----------------|---|---------|-------|-----------|------|-----------|------|-----------|------|-----------|------|-----------|------|-------------------|-------|-----------|
| BOOK PAGE S | SHEET ITEM NO. | CONTRACTITEM | UNIT | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | TOTAL | AS CONST. |
| | 201-00000 | CLEARING AND GRUBBING | LS | 1 | | | | | | | | | | | | 1 | |
| | 202-00010 | REMOVAL OF TREE | EACH | 66 | | | | | | | | | | | | 66 | |
| | 202-00019 | REMOVAL OF INLET | EACH | 1 | | | | | | | | | | | | 1 | |
| | 202-00020 | REMOVAL OF CONCRETE BOX CULVERT | EACH | 1 | | | | | | | | | | | | 1 | |
| | 202-00035 | REMOVAL OF PIPE | LF | 105 | | | | | | | | | | | | 105 | |
| | 202-00155 | REMOVAL OF WALL | LF | 80 | | | | | | | | | | | | 80 | |
| | 202-00201 | REMOVAL OF CURB | LF | 346 | | | | | | | | | | | | 346 | |
| | 202-00202 | REMOVAL OF GUTTER | LF | 18 | | | | | | | | | | | | 18 | |
| | 202-00207 | REMOVAL OF BRICK PAVERS | SY | 70 | | | | | | | | | | | | 70 | |
| | 202-00220 | REMOVAL OF ASPHALT MAT | SY | 1,051 | | | | | | | | | | | | 1,051 | |
| | 202-00821 | REMOVAL OF SIGN PANEL | EACH | 1 | | | | | | | | | | | | 1 | |
| | 202-01000 | REMOVAL OF FENCE | LF | 98 | | | | | | | | | | | | 98 | |
| | 202-01130 | REMOVAL OF GUARDRAIL TYPE 3 | LF | 212 | | | | | | | | | | | | 212 | |
| | 202-01300 | REMOVAL OF END ANCHORAGE | EA | 1 | | | | | | | | | | | | 1 | |
| | 202-04001 | PLUG CULVERT | EACH | 1 | | | | | | | | | | | | 1 | |
| | 203-00010 | UNCLASSIFIED EXCAVATION (COMPLETE IN PLACE) | CY | 5,530 | | | | | | | | | | | | 5,530 | |
| | 203-00100 | MUCK EXCAVATION | CY | 100 | | | | | | | | | | | | 100 | |
| | 203-00400 | ROCK EXCAVATION | CY | 2,620 | | | | | | | | | | | | 2,620 | |
| | 203-01100 | PROOFROLLING | HOUR | 20 | | | | | | | | | | | | 20 | |
| | 203-01510 | BACKHOE | HOUR | 60 | | | | | | | | | | | | 60 | |
| | 203-01594 | COMBINATION LOADER | HOUR | 60 | | | | | | | | | | | | 60 | |
| | 203-01597 | POTHOLING | HOUR | 40 | | | | | | | | | | | | 40 | |
| | 203-02330 | LABORER | HOUR | 60 | | | | | | | | | | | | 60 | |
| | 206-00000 | STRUCTURE EXCAVATION | CY | 2,905 | | | | | | | | | | | | 2,905 | |
| | 206-00065 | STRUCTURE BACKFILL (FLOW-FILL) | CY | 775 | | | | | | | | | | | | 775 | |
| | 206-00100 | STRUCTURE BACKFILL (CLASS 1) | CY | 1,255 | | | | | | | | | | | | 1,255 | |
| | 206-00360 | MECHANICAL REINFORCEMENT OF SOIL | CY | 140 | | | | | | | | | | | | 140 | |
| | 206-00510 | FILTER MATERIAL (CLASS A) | CY | 335 | | | | | | | | | | | | 335 | |
| | 206-01781 | SHORING (AREA 1) | LS | 1 | | | | | | | | | | | | 1 | |
| | 206-01782 | SHORING (AREA 2) | LS | 1 | | | | | | | | | | | | 1 | |
| | 206-01783 | SHORING (AREA 3) | LS | 1 | | | | | | | | | | | | 1 | |
| | 206-01784 | SHORING (AREA 4) | LS | 1 | | | | | | | | | | | | 1 | |
| | 206-01785 | SHORING (AREA 5) | LS | 1 | | | | | | | | | | | | 1 | |
| | 207-00205 | TOPSOIL | CY | 1,000 | | | | | | | | | | | | 1,000 | |
| | 207-00210 | STOCKPILE TOPSOIL | CY | 1,000 | | | | | | | | | | | | 1,000 | |
| | 208-00002 | EROSION LOG TYPE 1 (12 INCH) | LF | 3,360 | | | | | | | | | | | | 3,360 | |

| Print Date: 11/16/2016 | |
|-------------------------------------|-----------------------|
| Drawing File Name: 19888DES_SAQ.dgn | |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| MUL ENGINEERING | ` |

| | <u>Sheet Revisions</u> | |
|-------|------------------------|--|
| Date: | Init. | |
| | | |
| | | |
| | | |
| | | |





| As Constructed | tructed BOULDER CANYON TRAIL EXTENSION SUMMARY OF APPROXIMATE | | | | | | Code |
|----------------|--|-----|-----------------------|--------|--------------|------------|------|
| No Revisions: | SOMMA | | TITIES | YIMAIL | | STU C070-0 | 43 |
| Revised: | Designer: | | Structure | | | 19888 | |
| | Detailer: | CLJ | Numbers | | | | |
| Void: | Sheet Subset: | SAQ | Subset Sheets: 1 of 5 | | Sheet Number | 13 | |

| | NDEX | | | | | DWAY | | QUANTITI | | | | | | | | | | OJECT |
|----------|------------|----------------------|---|------|-------|-----------|------|-----------|------|-----------|------|-----------|------|-----------|------|-----------|-------|-----------|
| <u> </u> | PAGE SHEET | CONTRACT ITEM NO. | CONTRACT ITEM | UNIT | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | TOTAL | AS CONST. |
| BOOK | AGL SHEET | 208-00035 | AGGREGATE BAG | LF | 64 | AG CONST. | FLAN | AG CONST. | 64 | AG CONST. |
| | | | CONCRETE WASHOUT STRUCTURE | EACH | 4 | | | | | | | | | | | | 4 | |
| | | 208-00052 | STORM DRAIN INLET PROTECTION (TYPE II) | EACH | 1 | | | | | | | | | | | | 1 | |
| | | | STORM INLET DRAIN PROTECTION (TYPE III) | EACH | 2 | | | | | | | | | | | | 2 | |
| | | 208-00070 | VEHICLE TRACKING PAD | EACH | 4 | | | | | | | | | | | | 4 | |
| | | | REMOVAL AND DISPOSAL OF SEDIMENT (LABOR) | HOUR | 40 | | | | | | | | | | | | 40 | |
| | | 208-00105 | REMOVAL AND DISPOSAL OF SEDIMENT (EQUIPMENT) | HOUR | 40 | | | | | | | | | | | | 40 | |
| | | | SWEEPING (SEDIMENT REMOVAL) | HOUR | 40 | | | | | | | | | | | | 40 | |
| | | 208-00107 | REMOVAL OF TRASH | HOUR | 30 | | | | | | | | | | | | 30 | |
| | | 208-00207 | EROSION CONTROL MANAGEMENT | DAY | 180 | | | | | | | | | | | | 180 | |
| | | 210-00050 | RESET FIRE HYDRANT | EACH | 1 | | | | | | | | | | | | 1 | |
| | | | RESET GROUND SIGN | EACH | 1 | | | | | | | | | | | | 1 | |
| | | 210-02500 | RELAY SPRINKLER SYSTEM | LS | 1 | | | | | | | | | | | | 1 | |
| | | 210-04020 | MODIFY INLET | EACH | 2 | | | | | | | | | | | | 2 | |
| | | 211-01115 | ROCK REINFORCEMENT NUMBER 10 | LF | 375 | | | | | | | | | | | | 375 | |
| | | 212-00006 | SEEDING (NATIVE) | ACRE | 1.81 | | | | | | | | | | | | 1.81 | |
| | | 212-00009 | SEEDING (TEMPORARY) | ACRE | 0.53 | | | | | | | | | | | | 0.53 | |
| | | 213-00002 | MULCHING (WEED FREE HAY) | ACRE | 1.29 | | | | | | | | | | | | 1.29 | |
| | | 213-00061 | MULCH TACKIFIER | LB | 258 | | | | | | | | | | | | 258 | |
| | | 214-00000 | LANDSCAPE MAINTENANCE | LS | 1 | | | | | | | | | | | | 1 | |
| | | 216-00201 | SOIL RETENTION BLANKET (STRAW/COCONUT) (BIODEGRADABLE CLASS 1 | SY | 2,501 | | | | | | | | | | | | 2,501 | |
| | | 240-00000 | WILDLIFE BIOLOGIST | HOUR | 16 | | | | | | | | | | | | 16 | |
| | | 240-00010 | REMOVAL OF NESTS | HOUR | 8 | | | | | | | | | | | | 8 | |
| | | 240-00020 | NETTING | SY | 100 | | | | | | | | | | | | 100 | |
| | | 304-06000 | AGGREGATE BASE COURSE (CLASS 6) | TON | 1,369 | | | | | | | | | | | | 1,369 | |
| | | 304-09014 | AGGREGATE BASE COURSE (SPECIAL) | TON | 333 | | | | | | | | | | | | 333 | |
| | | 403-00720 | HOT MIX ASPHALT (PATCHING) (ASPHALT) | TON | 263 | | | | | | | | | | | | 263 | |
| | | 403-33721 | HOT MIX ASPHALT (GRADINGS) (75) (PG 58-28) | TON | 249 | | | | | | | | | | | | 249 | |
| | | 411-10255 | EMULSIFIED ASPHALT (SLOW-SETTING) | GAL | 42 | | | | | | | | | | | | 42 | |
| | | 420-00113 | GEOTEXTILE (DRAINAGE) (CLASS 2) | SY | 1,285 | | | | | | | | | | | | 1,285 | |
| | | 420-00114 | GEOTEXTILE (DRAINAGE) (CLASS 3) | SY | 35 | | | | | | | | | | | | 35 | |
| | | 502-00100 | DRILLING HOLE TO FACILITATE PILE DRIVING | LF | 30 | | | | | | | | | | | | 30 | |
| | | 502-00140 | BLAST HOLE TO FACILITATE PILE DRIVING | LF | 60 | | | | | | | | | | | | 60 | |
| | | 502-00460 | PILE TIP | EA | 6 | | | | | | | | | | | | 6 | |
| | | 502-11274 | STEEL PILING (HP 12X74) | LF | 136 | | | | | | | | | | | | 136 | |
| | | 504-04430 | REINFORCED CONCRETE FACING | SF | 495 | | | | | | | | | | | | 495 | |

Print Date: 11/16/2016

Drawing File Name: 19888DES_SAQ.dgn

Horiz. Scale: 1:1

Unit Information

Vert. Scale: As Noted

Unit Leader Initials

MULLER

ENGINEERING COMPANY

| | | Sheet Revisions | |
|---|-------|-----------------|-------|
| | Date: | Comments | Init. |
| 0 | | | |
| 0 | | | |
| 0 | | | |
| 0 | | | |





| As Constructed | BOULDER SUMMAR` | | | | - | Project No./ | Code |
|----------------|--------------------|-----|-----------------------|------------|--------------|--------------|------|
| No Revisions: | | | rITIES |)VIIAIVI F | - | STU C070-0 | 43 |
| Revised: | Designer: | | Structure | | | 19888 | |
| | Detailer: | CLJ | Numbers | | | | |
| Void: | Sheet Subset: | SAQ | Subset Sheets: 2 of 5 | | Sheet Number | 14 | |

| INI | DEX CONTRACT | CONTRACT ITEM | LIMIT | ROA | DWAY | | | | | | | | | | | | JECT TALS |
|---------|--------------------|--|-------|--------|-----------|------|-----------|------|-----------|------|-----------|------|-----------|------|-----------|--------|--------------|
| воок РА | AGE SHEET ITEM NO. | CONTRACTITEM | UNIT | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | TOTAL | AS CONST. |
| | 504-06100 | GROUND NAIL WALL | SF | 1,474 | | | | | | | | | | | | 1,474 | |
| | 506-00212 | RIPRAP (12 INCH) | CY | 54 | | | | | | | | | | | | 54 | |
| | 506-00424 | SOIL RIPRAP (24 INCH) | CY | 1,023 | | | | | | | | | | | | 1,023 | |
| | 514-00200 | PEDESTRIAN RAILING (STEEL) | LF | 601 | | | | | | | | | | | | 601 | |
| | 601-03000 | CONCRETE CLASS D | CY | 27 | | | | | | | | | | | | 27 | |
| | 601-03040 | CONCRETE CLASS D (BRIDGE) | CY | 44 | | | | | | | | | | | | 44 | |
| | 601-03050 | CONCRETE CLASS D (WALL) | CY | 386 | | | | | | | | | | | | 386 | |
| | 601-13001 | STRUCTURAL CONCRETE STAIN (SPECIAL) | SY | 5 | | | | | | | | | | | | 5 | |
| | 601-40005 | CUT STONE VENEER | SF | 4,666 | | | | | | | | | | | | 4,666 | |
| | 601-40400 | STRUCTURAL CONCRETE STAIN | SY | 72 | | | | | | | | | | | | 72 | |
| | 601-XXXXX | CONCRETE (CLASS G) | CY | 40 | | | | | | | | | | | | 40 | |
| | 602-00000 | REINFORCING STEEL | LB | 63,940 | | | | | | | | | | | | 63,940 | |
| | 603-01185 | 18 INCH REINFORCED CONCRETE PIPE (COMPLETE IN PLACE) | LF | 365 | | | | | | | | | | | | 365 | |
| | 603-01245 | 24 INCH REINFORCED CONCRETE PIPE (COMPLETE IN PLACE) | LF | 96 | | | | | | | | | | | | 96 | |
| | 603-01305 | 30 INCH REINFORCED CONCRETE PIPE (COMPLETE IN PLACE) | LF | 19 | | | | | | | | | | | | 19 | |
| | 603-01365 | 36 INCH REINFORCED CONCRETE PIPE (COMPLETE IN PLACE) | LF | 22 | | | | | | | | | | | | 22 | |
| | 603-01425 | 42 INCH REINFORCED CONCRETE PIPE (COMPLETE IN PLACE) | LF | 32 | | | | | | | | | | | | 32 | |
| | 603-01485 | 48 INCH REINFORCED CONCRETE PIPE (COMPLETE IN PLACE) | LF | 247 | | | | | | | | | | | | 247 | |
| | 603-05018 | 18 INCH REINFORCED CONCRETE END SECTION | EACH | 3 | | | | | | | | | | | | 3 | |
| | 603-05024 | 24 INCH REINFORCED CONCRETE END SECTION | EACH | 1 | | | | | | | | | | | | 1 | |
| | 603-05030 | 30 INCH REINFORCED CONCRETE END SECTION | EACH | 1 | | | | | | | | | | | | 1 | |
| | 603-05036 | 36 INCH REINFORCED CONCRETE END SECTION | EACH | 1 | | | | | | | | | | | | 1 | |
| | 603-05042 | 42 INCH REINFORCED CONCRETE END SECTION | EACH | 2 | | | | | | | | | | | | 2 | |
| | 603-05048 | 48 INCH REINFORCED CONCRETE END SECTION | EACH | 1 | | | | | | | | | | | | 1 | |
| | 603-50006 | 6 INCH PLASTIC PIPE | LF | 156 | | | | | | | | | | | | 156 | |
| | 603-71609 | 16X9 FOOT CONCRETE BOX CULVERT (PRECAST) | LF | 72 | | | | | | | | | | | | 72 | |
| | 603-71610 | 16x10 FOOT CONCRETE BOX CULVERT (PRECAST) | LF | 120 | | | | | | | | | | | | 120 | |
| | 604-00305 | INLET TYPE C (5 FOOT) | EACH | 7 | | | | | | | | | | | | 7 | |
| | 604-00310 | INLET TYPE C (10 FOOT) | EACH | 1 | | | | | | | | | | | | 1 | |
| | 604-00505 | INLET TYPE D (5 FOOT) | EACH | 1 | | | | | | | | | | | | 1 | |
| | 604-13005 | INLET TYPE 13 (5 FOOT) | EACH | 2 | | | | | | | | | | | | 2 | |
| | 604-16005 | INLET TYPE 16 (5 FOOT) | EACH | 1 | | | | | | | | | | | | 1 | |
| | 604-19000 | INLET (SPECIAL) | EACH | 1 | | | | | | | | | | | | 1 | |
| | 604-25005 | VANE GRATE INLET (5 FOOT) | EACH | 1 | | | | | | | | | | | | 1 | |
| | 604-25010 | VANE GRATE INLET (10 FOOT) | EACH | 1 | | | | | | | | | | | | 1 | |
| | 604-30010 | MANHOLE SLAB BASE (10 FOOT) | EACH | 2 | | | | | | | | | | | | 2 | |

| Print Date: 11/16/2016 | |
|-------------------------------------|-----------------------|
| Drawing File Name: 19888DES_SAQ.dgn | |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| MULI ENGINEERING | \ |

| | | <u>Sheet Revisions</u> | |
|-----------|-------|------------------------|--|
| | Date: | Init. | |
| \bigcap | | | |
| \bigcap | | | |
| \prod | | | |
| \prod | | | |





| As Constructed | BOULDER SUMMA | R CANYON | | | <u>-</u> | Project No./ | Code |
|----------------|------------------|----------|-------------------------|--------|--------------|--------------|------|
| No Revisions: | SOMMA | | TITIES | YIMYII | _ | STU C070-0 | 43 |
| Revised: | Designer: | | Structure | | | 19888 | |
| | Detailer: | CLJ | Numbers | | | | |
| Void: | Sheet Subset: | SAQ | Q Subset Sheets: 3 of 5 | | Sheet Number | 15 | |

| INDEX | CONTRACT | CONTRACT ITEM | UNIT | ROA | DWAY | | | | | | | | | | | PROJECT TOTALS | |
|----------------|------------|---|------|--------|-----------|------|-----------|------|-----------|------|-----------|------|-----------|------|-----------|-------------------|-----------|
| BOOK PAGE SHEE | T ITEM NO. | CONTRACTIEW | ONII | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | TOTAL | AS CONST. |
| | 604-30015 | MANHOLE SLAB BASE (15 FOOT) | EACH | 3 | | | | | | | | | | | | 3 | |
| | 605-00040 | 4 INCH PERFORATED PIPE UNDERDRAIN | LF | 69 | | | | | | | | | | | | 69 | |
| | 605-00060 | 6 INCH PERFORATED PIPE UNDERDRAIN | LF | 223 | | | | | | | | | | | | 223 | |
| | 605-83002 | GEOCOMPOSITE DRAIN WITH PIPE | SY | 445 | | | | | | | | | | | | 445 | |
| | 605-84000 | SUBSURFACE DRAIN OUTLET | LF | 99 | | | | | | | | | | | | 99 | |
| | 606-00301 | GUARDRAIL TYPE 3 (6-3 POST SPACING) | LF | 743.75 | | | | | | | | | | | | 743.75 | |
| | 606-00710 | GUARDRAIL TYPE 7 (STYLE CA) | LF | 269 | | | | | | | | | | | | 269 | |
| | 606-00740 | GUARDRAIL TYPE 7 (STYLE CE) | LF | 236 | | | | | | | | | | | | 236 | |
| | 606-00741 | GUARDRAIL TYPE 7 (STYLE CE) (SPECIAL) | LF | 490 | | | | | | | | | | | | 490 | |
| | 606-01370 | TRANSITION TYPE 3G | EACH | 1 | | | | | | | | | | | | 1 | |
| | 606-01385 | TRANSITION TYPE 3J | EACH | 1 | | | | | | | | | | | | 1 | |
| | 606-02003 | END ANCHORAGE (NONFLARED) | EACH | 1 | | | | | | | | | | | | 1 | |
| | 606-02005 | END ANCHORAGE (FLARED) | EACH | 4 | | | | | | | | | | | | 4 | |
| | 607-01000 | FENCE BARBED WIRE WITH METAL POSTS | LF | 74 | | | | | | | | | | | | 74 | |
| | 607-11460 | FENCE WOOD RAIL | LF | 285 | | | | | | | | | | | | 285 | |
| | 607-11525 | FENCE (PLASTIC) | LF | 2,000 | | | | | | | | | | | | 2,000 | |
| | 608-00026 | CONCRETE BIKEWAY (6 INCH) | SY | 2,884 | | | | | | | | | | | | 2,884 | |
| | 609-21020 | CURB AND GUTTER TYPE 2 (SECTION II-B) | LF | 305 | | | | | | | | | | | | 305 | |
| | 609-24002 | GUTTER TYPE 2 (2 FOOT) | LF | 129 | | | | | | | | | | | | 129 | |
| | 609-24100 | GUTTER TYPE 2 (VARIABLE) | LF | 41 | | | | | | | | | | | | 41 | |
| | 614-00011 | SIGN PANEL (CLASS I) | SF | 54 | | | | | | | | | | | | 54 | |
| | 614-00216 | STEEL SIGN POST (2X2 INCH TUBING) | LF | 180 | | | | | | | | | | | | 180 | |
| | 614-00218 | STEEL SIGN POST (2.25X2.25 INCH TUBING) | LF | 54 | | | | | | | | | | | | 54 | |
| | 614-01512 | STEEL SIGN SUPPORT (2-INCH ROUND) (POST) | LF | 10 | | | | | | | | | | | | 10 | |
| | 614-01522 | STEEL SIGN SUPPORT (2-INCH ROUND) (SOCKET) | EACH | 1 | | | | | | | | | | | | 1 | |
| | 614-85001 | IMPACT ATTENUATOR | EACH | 1 | | | | | | | | | | | | 1 | |
| | 619-30320 | 4 INCH GALVANIZED PIPE | LF | 14 | | | | | | | | | | | | 14 | |
| | 620-00002 | FIELD OFFICE (CLASS 2) | EACH | 1 | | | | | | | | | | | | 1 | |
| | 620-00012 | FIELD LABORATORY (CLASS 2) | EACH | 1 | | | | | | | | | | | | 1 | |
| | 620-00020 | SANITARY FACILITY | EACH | 1 | | | | | | | | | | | | 1 | |
| | 621-00425 | DETOUR (CBC 1) | LS | 1 | | | | | | | | | | | | 1 | |
| | 621-00425 | DETOUR (CBC 2) | LS | 1 | | | | | | | | | | | | 1 | |
| | 625-00000 | CONSTRUCTION SURVEYING | LS | 1 | | | | | | | | | | | | 1 | |
| | 626-00000 | MOBILIZATION | LS | 1 | | | | | | | | | | | | 1 | |
| | 627-00008 | MODIFIED EPOXY PAVEMENT MARKING | GAL | 4.41 | | | | | | | | | | | | 4.41 | |
| | 627-00011 | PAVEMENT MARKING PAINT (WATERBORNE) (TEMPORARY) | GAL | 15 | | | | | | | | | | | | 15 | |

| Print Date: 11/16/2016 | |
|-------------------------------------|-----------------------|
| Drawing File Name: 19888DES_SAQ.dgn | 1 |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| MUL ENGINEERING | |

| | | <u>Sheet Revisions</u> | |
|---|-------|------------------------|-------|
| | Date: | Comments | Init. |
| 0 | | | |
| 0 | | | |
| 0 | | | |
| 0 | | | |





| As Constructed | BOULDER SUMMAR | | | | = | Project No./ | Code |
|----------------|----------------|-----|-------------|------------|--------|--------------|------|
| No Revisions: | | | rITIES |)VIIAIVI F | - | STU C070-043 | |
| Revised: | Designer: | | Structure | | | 19888 | |
| | Detailer: | CLJ | Numbers | | | | |
| Void: | Sheet Subset: | SAQ | Subset Shee | ets: | 4 of 5 | Sheet Number | 16 |

| INDEX | CONTRACT | | ROADWAY | | | | | | | | | | JECT TALS | | | | |
|-----------------|-----------|---|---------|--------|-----------|------|-----------|------|-----------|------|-----------|------|--------------|------|-----------|--------|-----------|
| BOOK PAGE SHEET | ITEM NO. | CONTRACTITEM | UNIT | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | PLAN | AS CONST. | TOTAL | AS CONST. |
| | 627-01010 | PREFORMED PLASTIC PAVEMENT MARKING (TYPE I)(INLAID) | SF | 160.13 | | | | | | | | | | | | 160.13 | |
| | 628-00070 | BRIDGE GIRDER AND DECK UNIT (70 FEET TO 75 FEET) | EACH | 1 | | | | | | | | | | | | 1 | |
| | 630-00000 | FLAGGING | HOUR | 500 | | | | | | | | | | | | 500 | |
| | 630-00003 | UNIFORMED TRAFFIC CONTROL | HOUR | 16 | | | | | | | | | | | | 16 | |
| | 630-00007 | TRAFFIC CONTROL INSPECTION | DAY | 51 | | | | | | | | | | | | 51 | |
| | 630-00012 | TRAFFIC CONTROL MANAGEMENT | DAY | 129 | | | | | | | | | | | | 129 | |
| | 630-80341 | CONSTRUCTION TRAFFIC SIGN (PANEL SIZE A) | EACH | 40 | | | | | | | | | | | | 40 | |
| | 630-80342 | CONSTRUCTION TRAFFIC SIGN (PANEL SIZE B) | EACH | 12 | | | | | | | | | | | | 12 | |
| | 630-80350 | VERTICAL PANEL | EACH | 150 | | | | | | | | | | | | 150 | |
| | 630-80355 | PORTABLE MESSAGE SIGN PANEL | EACH | 2 | | | | | | | | | | | | 2 | |
| | 630-80360 | DRUM CHANNELIZING DEVICE | EACH | 100 | | | | | | | | | | | | 100 | |
| | 630-80364 | DRUM CHANNELIZING DEVICE (WITH LIGHT) (STEADY BURN) | EACH | 20 | | | | | | | | | | | | 20 | |
| | 630-80370 | CONCRETE BARRIER (TEMPORARY) | LF | 2,000 | | | | | | | | | | | | 2,000 | |
| | 630-85010 | IMPACT ATTENUATOR (TEMPORARY) | EACH | 6 | | | | | | | | | | | | 6 | |
| | 630-86810 | TRAFFIC SIGNAL (TEMPORARY) | EACH | 2 | | | | | | | | | | | | 2 | |
| | 641-10000 | SHOTCRETE | SY | 164 | | | | | | | | | | | | 164 | |
| | 700-70010 | F/A MINOR CONTRACT REVISIONS | FA | 1 | | | | | | | | | | | | 1 | |
| | 700-70011 | F/A PARTNERING | FA | 1 | | | | | | | | | | | | 1 | |
| | 700-70016 | F/A FUEL COST ADJUSTMENT | FA | 1 | | | | | | | | | | | | 1 | |
| | 700-70021 | F/A ON-THE-JOB TRAINEE | HOUR | 600 | | | | | | | | | | | | 600 | |
| | 700-70100 | F/A RELOCATE UTILITIES | FA | 1 | | | | | | | | | | | | 1 | |
| | 700-70380 | F/A EROSION CONTROL | FA | 1 | | | | | | | | | | | | 1 | |
| | | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | | |

Print Date: 11/16/2016

Drawing File Name:19888DES_SAQ.dgn

Horiz. Scale: 1:1

Unit Information

Vert. Scale: As Noted

Unit Leader Initials

MULLER

ENGINEERING COMPANY

Sheet Revisions

Date: Comments Init.





| As Constructed | | ON TRAIL EXTENSION OF APPROXIMATE | Project No./Code | |
|----------------|-----------------|------------------------------------|------------------|--|
| No Revisions: | | ANTITIES | STU C070-043 | |
| Revised: | Designer: S | DB Structure | 19888 | |
| | Detailer: (| CLJ Numbers | 1 | |
| Void: | Sheet Subset: S | AQ Subset Sheets: 5 of 5 | Sheet Number 17 | |

SUMMARY OF EARTHWORK QUANTITIES

| | CUBIC YARDS |
|--|-------------|
| UNCLASSIFIED EXCAVATION (COMPLETE IN PLACE) | |
| BOULDER CANYON TRAIL EXTENSION (FROM CROSS-SECTIONS) | 5,530 |
| TOTAL FOR PAY QUANTITY | 5,530 |
| STRUCTURE BACKFILL (FLOW-FILL) (FROM STRUCTURES TAB) | 775 |
| STRUCTURE BACKFILL (CLASS 1) (FROM STRUCTURES TAB) | 1,255 |
| STRUCTURE EXCAVATION (FROM STRUCTURES TAB) | 2,905 |
| ROCK EXCAVATION (FROM CROSS SECTIONS) | 2,620 |
| MUCK EXCAVATION (AS NEEDED) | 100 |
| FOR INFORMATION ONLY | |
| | CUBIC YARDS |
| EMBANKMENT MATERIAL (COMPLETE IN PLACE) | |
| BOULDER CANYON TRAIL EXTENSION (FROM CROSS-SECTIONS) | 3,230 |
| TOTAL | 3,230 |
| STRUCTURE BACKFILL (CLASS 1) (FROM DRAINAGE TAB) | 1,558 |
| STRUCTURE EXCAVATION | |
| FROM STRUCTURES TAB | 2,905 |
| FROM DRAINAGE TAB | 2,904 |
| TOTAL | 5,809 |
| | |
| EARTHWORK QUANTITIES BALANCE: | CUBIC YARDS |
| | |
| EMBANKMENT MATERIAL (COMPACTION FACTOR = 1.15) | 3,715 |
| UNCLASSIFIED EXCAVATION + STRUCTURE EXCAVATION + ROCK EXCAVATION | 13,959 |
| EXCESS MATERIAL | 10,244 |

NOTES:

- 1. UNCLASSIFIED EXCAVATION VOLUMES INCLUDE THE EXISTING PAVEMENT.
- 2. ROADWAY QUANTITIES BALANCE DOES NOT REFLECT THE EARTHWORK REQUIRED IN EACH CONSTRUCTION PHASE. THE PROJECT MAY REQUIRE ADDITIONAL EMBANKMENT OR EXCAVATION PER PHASE. THE COST OF ADDITIONAL EMBANKMENT, EXCAVATION, HAULING, AND HANDLING WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE ORIGINAL PLAN QUANTITIES.
- 3. THE BID COST OF MUCK EXCAVACTION PER CUBIC YARD SHALL INCLUDE REMOVAL OF MUCK AND BACKFILL WITH SUITABLE EMBANKMENT MATERIAL.



| MU ENGINEE | LLER RING COMPANY |
|--------------------------------|-----------------------|
| Unit Information | Unit Leader Initials |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Drawing File Name:19888DES_Tab | o_Earthwork.dgn |
| Print Date: 11/16/2016 | |

| | Sheet Revisions | |
|-------|-----------------|-------|
| Date: | Comments | Init. |
| | | |
| | | |
| | | |
| | | |





| | | | | | | Call before you | u dig. |
|----------------|---------------------------|------------------|------------|--------|--------|-----------------|--------|
| As Constructed | BOULDER CA | Project No./Code | | | | | |
| No Revisions: | TABULATIC |)N C | F EAR | THWORK | | STU C070-04 | 43 |
| Revised: | . Designer: SDB Structure | | | 19888 | | | |
| | Detailer: | SDB | Numbers | | | | |
| Void: | Sheet Subset: | TAB | Subset She | ets: | 1 of 1 | Sheet Number | 18 |

| STATION | SIDE | REMOVAL OF TREE | REMOVAL OF CONCRETE BOX CULVERT | REMOVAL OF WALL | REMOVAL OF BRICK PAVERS | RESET FIRE HYDRANT | RELAY SPRINKLER SYSTEM | MODIFY INLET | COMMENTS |
|------------------|-----------|--------------------|---------------------------------|--------------------|-------------------------------|-----------------------|------------------------------|-----------------|------------------------------------|
| | | EA | EA | LF | SY | EA | LS | EA | |
| 103+00 TO 103+50 | LT | 3 | | | | | | | |
| 104+75 TO 105+75 | LT | 7 | | | | | | | |
| 108+25 | RT | | | 40 | | | | | REMOVAL OF WING WALLS FROM OLD CBC |
| 108+25 | LT | | 1 | | | | | | REMOVAL OF OLD CBC |
| 109+75 TO 110+25 | RT | 3 | | | | | | | |
| 111+00 | LT | 1 | | | | | | | |
| 112+00 TO 116+00 | вотн | 20 | | | | | | | |
| 114+20 | MIDDLE | | | | | 1 | | | |
| 116+00 TO 117+00 | RT | 2 | | | | | | | |
| 120+47 TO 120+87 | LT | | | 40 | | | | | EXISTING WALL BY ALPS INN |
| 120+48 TO 125+33 | LT | | | | | | 1 | | IN FRONT OF ALPS INN WALL |
| 124+30 | LT | 1 | | | | | | | |
| 125+33 TO 125+81 | LT | | | | 70 | | | | REMOVAL OF PAVERS IN FRONT OF ALPS |
| 128+40 | LT | | | | | | | 1 | |
| 128+80 | LT | | | | | | | 1 | |
| 133+00 TO 133+50 | ВОТН | 3 | | | | | | | |
| 135+50 TO 137+00 | MIDDLE | 22 | | | | | | | |
| 138+00 TO 139+00 | LT | 3 | | | | | | | |
| 139+20 | RT | 1 | | | | | | | |
| PROJE | CT TOTALS | 66 | 1 | 80 | 70 | 1 | 1 | 2 | |



| Print Date: 11/16/2016 | |
|-----------------------------------|-----------------------|
| Drawing File Name:19888DES_Tab_Re | movals.dgn |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| MUL ENGINEERING | |

| | | Sheet Revisions | |
|---|-------|-----------------|-------|
| | Date: | Comments | Init. |
| | | | |
| 0 | | | |
| 0 | | | |
| | | | |





| | | | | | | Call before yo | u alg. |
|----------------|----------------|-----|-----------------------|--|--|----------------|--------|
| As Constructed | BOULDER TABULA | | TRAIL EX | | | Project No./ | 'Code |
| No Revisions: | RESETS | | | | | STU C070-0 | 43 |
| Revised: | Designer: | CZC | Structure | | | 19888 | |
| | Detailer: | CZC | Numbers | | | | |
| Void: | Sheet Subset: | TAB | Subset Sheets: 1 of 1 | | | Sheet Number | 19 |

| | | HOT MIV | HOT MIX | ASPHALT | | | | | |
|-----------------------|--------------------|----------------------------|---------------|-----------------|--------------------------|---------------------|-----------------------------|-----------------------------|--|
| OTATION | REMOVAL OF ASPHALT | HOT MIX ASPHALT (PATCHING) | (GRADING S) (| (75) (PG 58-28) | EMULSIFIED ASPHALT (SLOW | CONCRETE BIKEWAY | AGGREGATE BASE COURSE | AGGREGATE BASE COURSE | OOMMENTO |
| STATION | MAT | (ASPHALT) ¹ | воттом | ТОР | SETTING) | (6 INCH) | (CLASS 6) | (SPECIAL) | COMMENTS |
| | | , | 3.5" | 2.0" | ĺ | | | , , | |
| | SY | TON | TON | TON | GAL | SY | TON | TON | |
| SH 119 EB | | 21 | | | | | | | EASTBOUND GUARDRAIL AT CBC 1 |
| SH 119 WB | | 30 | | | | | | | WESTBOUND GUARDRAIL AT CBC 1 |
| SH 119 EB | | 17 | | | | | | | EASTBOUND GUARDRAIL AT CBC 2 |
| SH 119 WB | 68 | 80 | | | | | 79 | | WB GUARDRAIL (Type 7) AT ROCK CUT TO CBC 2 |
| SH 119 CBC 1 | 286 | | 55 | 32 | 15 | | 86 | | SH 119 SURFACING FOR CBC 1 CONSTRUCTION |
| SH 119 CBC 2 | 492 | | 95 | 55 | 25 | | 148 | | SH 119 SURFACING FOR CBC 2 CONSTRUCTION |
| 102+50 TO 110+10 | | | | | | 713 | 214 | | |
| 110+10 TO 116+35 | | | | | | | | 209 | |
| 116+35 TO 124+95 | | | | | | 854 | 256 | | |
| 120+83 TO 125+33 | 114 | 102 | | | | | 101 | | TYPE 7 GUARDRAIL AT ALPS |
| 125+33 TO 128+37 | 91 | | | | | | 26 | | STONE CURB REMOVAL & TYPE IIB C&G INSTALL |
| 125+33 TO 136+90 | | | | | | 1,317 | 394 | | |
| 136+90 TO 139+52 | | | | | | | | 108 | |
| | | | | | | | | | |
| SUBTOTAL | 1,051 | 250 | 150 | 87 | 40 | 2,884 | 1,304 | 317 | |
| 5% FOR IRREGULARITIES | S | 13 | 8 | 4 | 2 | | 65 | 16 | |
| SUB TOTALS | 1,051 | 263 | 158 | 91 | 42 | 2,884 | 1,369 | 333 | |
| PROJECT TOTALS | 1,051 | 263 | 158 | 91 | 42 | 2,884 | 1,369 | 333 | |

NOTES:

1. SEE PLAN SHEETS FOR H.M.A. (PATCHING) AREAS. H.M.A. (PATCHING) FOR TYPE 3 GUARDRAIL AREAS SHALL BE A MINIMUM OF 2 INCHES H.M.A. (GRADING S) (75) (PG 58-28). H.M.A. (PATCHING) FOR TYPE 7 GUARDRAIL AREAS SHALL MATCH THE FULL DEPTH PAVEMENT SECTION SHOWN ON THE TYPICAL SECTIONS.



| Unit Information | Unit Leader Initials | | | | | | |
|--|-----------------------|--|--|--|--|--|--|
| Horiz. Scale: 1:1 | Vert. Scale: As Noted | | | | | | |
| Drawing File Name:19888DES_Tab_Surface.dgn | | | | | | | |
| Print Date: 11/16/2016 | | | | | | | |

| | | Sheet Revisions | | |
|---|-------|-----------------|-------|--|
| | Date: | Comments | Init. | |
| 0 | | | | |
| 0 | | | | |
| 0 | | | | |
| | | | | |





| | | | Can before you | a aigi | |
|----------------|------------------|---------------------------------|------------------|--------|--|
| As Constructed | | N TRAIL EXTENSION OF SURFACING | Project No./Code | | |
| No Revisions: | | ITITIES | STU C070-043 | | |
| Revised: | | C Structure | 19888 | | |
| | Detailer: CZ | C Numbers | | | |
| Void: | Sheet Subset: TA | B Subset Sheets: 1 of 1 | Sheet Number | 20 | |

| STATION | SIDE | REMOVAL OF CURB | REMOVAL OF GUTTER | STRUCTURAL CONCRETE STAIN (SPECIAL) | CURB AND GUTTER TYPE 2 (SECTION II-B) | GUTTER TYPE 2 (VARIABLE) | GUTTER TYPE 2 (2 FT.) | COMMENTS |
|------------------|-----------|--------------------|----------------------|--|---|--------------------------------|-----------------------------|---------------------------------|
| | | LF | LF | SF | LF | LF | LF | |
| 103+95 TO 104+59 | LT | | | | | 41 | | ON TOP OF WALL 3 |
| 104+59 TO 105+69 | LT | | | | | | 111 | ON TOP OF WALL 5 |
| 124+51 TO 124+91 | RT | 41 | | | | | | |
| 125+32 | LT | | 18 | | | | 18 | |
| 125+33 TO 128+37 | RT | 305 | | | | | | |
| 125+33 TO 128+37 | RT | | | | 305 | | | |
| 120+87 | LT | | | 5 | | | | STAINING EDGE OF SHORTENED WALL |
| PROJE | CT TOTALS | 346 | 18 | 5 | 305 | 41 | 129 | |

now what's below Call before you di

Print Date: 11/16/2016

Drawing File Name: 19888DES_Tab_Concrete.dgn

Horiz. Scale: 1:1 Vert. Scale: As Noted

Unit Information Unit Leader Initials

MULLER

ENGINEERING COMPANY

Sheet Revisions

Date: Comments Init.





| | | | | | | | Call before yo | u aig. |
|-------|----------------|---------------|------------------|-------------|----------|------|----------------|--------|
| | As Constructed | BOULDER C | Project No./Code | | | | | |
| | No Revisions: | TABULATION | OF | CONCR | ETE ITEM | IS | STU C070-0 | 43 |
| | Revised: | Designer: | | Structure | | | 19888 | |
| | | Detailer: | CZC | Numbers | | | | |
| Void: | Void: | Sheet Subset: | TAB | Subset Shee | ets: 1 | of 1 | Sheet Number | 21 |

| STATION | SIDE | REMOVAL OF GUARDRAIL TYPE 3 | REMOVAL OF END ANCHORAGE | | GUARDRAIL TYPE 7 (STYLE T CE) (SPECIAL) | | GUARDRAIL TYPE 7 (STYLE CA) | TRANSITION TYPE 3G | TYPE 3J | END ANCHORAGE (NONFLARED) | END ANCHORAGE (FLARED) | IMPACT ATTENUATOR | COMMENTS | |
|------------------|-----------|-----------------------------------|--------------------------------|--------|---|-----|-----------------------------------|-----------------------|---------|---------------------------------|------------------------------|----------------------|---|--|
| | | LF | EA | LF | LF | LF | LF | EA | EA | EA | EA | EA | | |
| SH 119 | EB | | | 206.25 | | | | | 1 | | 1 | | Eastbound SH 119 at Chapman Drive | |
| SH 119 | WB | | | 243.75 | | | | | | | 2 | | Westbound SH 119 at Chapman Drive | |
| 120+48 125+33 | RT | | | | 490 | | | | | | | | Use Colored Concrete as directed | |
| 120+40 125+55 | 111 | | | | 490 | | | | | | | | See special detail with Stone Veneer | |
| 129+38 | RT | | | | | | | | | | | 1 | | |
| 129+38 TO 131+74 | RT | | | | | 236 | | | | | | | Use Colored Concrete as directed | |
| 131+74 TO 134+68 | RT | | | | | | 269 | | | | | | Use Colored Concrete as directed | |
| 132+48 | RT | | 1 | | | | | | | | | | Westbound SH 119 at CBC 2 | |
| 132+48 TO 134+83 | RT | 212 | | | | | | | | | | | | |
| 133+36 TO 136+33 | RT TO LT | | | 293.75 | | | | | | 1 | 1 | | Eastbound SH 119 at CBC 2 | |
| 134+68 | RT | | | | | | | 1 | | | | | Westbound SH 119 Tie Type 7 to Existing | |
| 135+49 TO 136+85 | RT | | | | | | | | | | | | , | |
| PROJE | CT TOTALS | 212 | 1 | 743.75 | 490 | 236 | 269 | 1 | 1 | 1 | 4 | 1 | | |

TABULATION OF GUARDRAIL


- 1. ALL GUARDRAIL TYPE 3 SHALL BE GALVANIZED. REFLECTOR TABS SHALL BE PROVIDED AND PLACED.
- 2. USE STEEL POSTS FOR ALL NEW GUARDRAIL, EXCEPT AS REQUIRED FOR END ANCHORAGES. GUARDRAIL POSTS SHALL BE GALVANIZED.

TABULATION OF FENCING

| STATION | SIDE | REMOVAL OF FENCE | FENCE BARBED WIRE WITH METAL POSTS | FENCE WOOD RAIL | |
|------------------|-----------|---------------------|--|--------------------|--|
| | | LF | LF | LF | |
| 117+27 TO 118+44 | BOTH | 98 | | | |
| 117+27 TO 118+44 | BOTH | | 74 | | |
| 136+31 TO 139+00 | LT | | | 285 | |
| | | | | | |
| PROJE | CT TOTALS | 98 | 74 | 285 | |

NOTES:

- 1. IT IS ESTIMATED THAT 6 END POSTS AND 2 CORNER AND LINE BRACE POSTS WILL BE REQUIRED.
- 2. SEE STANDARD PLAN M-607-01 FOR ADDITIONAL DETAILS.
- 3. METAL LINE POSTS AND METAL CORNER AND LINE BRACE POSTS WILL BE REQUIRED ON THIS PROJECT.
- 4. WIRE TIES WILL BE REQUIRED ON EACH WIRE AT EACH METAL POST.




TAB Subset Sheets:

Sheet Subset:

Sheet Number

Print Date: 11/16/2016 Drawing File Name: 19888DES_Tab_Guardrails.dgn Horiz. Scale: 1:1 Vert. Scale: As Noted Unit Information Unit Leader Initials








Revised:

| taig CULIT-reniable.tbi | TO ESTABLISH GEOMETRIC CONTROL FOR THE CONSTRUCTION OF THIS PROJECT. THE DEPARTMENT HAS PROVIDED THE FOLLOWING INFORMATION: Format | Structure Excavation limits (Section Concrete Box Culverts (Section Piling locations and cut off ele Coisson locations and elevation: Footing locations, alignment, an Abutment/Pier locations, alignment Wingwall skew angles/offsets Structural concrete form locations Substructure As-constructed surequired for Bridges (Sut Period of Bridge expansion joint(s) alignment Deck grades at Girder 10th or Slope and Ditch Poving (Section Other: Retaining Walls, Pedestrem Other: Retaining Walls, Pedestrem Delineators (Section 607) Fencing (Section 607) Fermanent Sound Barrier Other: Delineators (Section 612) Fermanent Lighting (Section 613) and Traffic Contro Signal pole locations and elevations Sign locations Field verify sign post locations. | venating Agent in 409) Tangent Curve Special Interval Interval Offset Left Center Interval Interval Interval Left Interval Interval Interval was as assigned a structure number cition 206) gwalls (Section 601) dwalls and Wingwalls ion 614), Concrete Box Culverts, Bridges - es assigned a structure number cition 206) ion 603) w/ Headwalls and Wingwalls (Section 601) vations (Section 502) is (Section 503) id elevations ent, and elevations ions invey inth point locations and elevations ion Bridge I Devices (Permanent) (Section 614) tions | Povement Marking (Section 627) Supping (Ferm) |
|---------------------------|---|--|--|---|
| ultPrinter_v8i.pitcig CDL | — □ Untreated Subgrade | □ Light pole locations and elevati □ Sign locations | ons | ■ Horizontal Alignment ■ Grading |
| JI-Derau | Print Date: 11/16/2016 Drawing File Name: 19888SURV_Tab.dgn Sheet Revisions Date: Comments | Init. | As Cons | tructed BOULDER CANYON TRAIL EXTENSION Project No./Code |
| CDI | Horiz. Scale: 1:1 Vert. Scale: As Noted | Init. | No Revisions: | 5.0 50.0 |
| 2016 | Unit Information Unit Leader Initials | co 📡 | County Revised: | Designer: SDB Structure 19888 Detailer: REW Numbers |
| 1/110/ | MULLER ENGINEERING COMPANY | Region 4 | Void: | Sheet Subset: SURVEY Subset Sheets: 1 of 1 Sheet Number 23 |
| - I | ENGINEERING CONTAIN | | | |



GEOMETRY PLAN

ZDA

Sheet Subset: GEDMETRY Subset Sheets:

Structure

Numbers

Designer:

Detailer:

STU C070-043

19888

Sheet Number

24

No Revisions:

Revised:

Void:

Drawing File Name: 19888DES_Geometry01.dgn

Vert. Scale: As Noted

Unit Leader Initials

Horiz. Scale: 1:100


Unit Information

Date:

Comments

Init.

Region 4



SDB Structure

ZDA

Sheet Subset: GEDMETRY Subset Sheets:

Numbers

19888

Sheet Number

25

Designer:

Detailer:


Revised:

Void:

zadkison 3:22:20 PM Q:\2015 Projects\15-02

Unit Information

Unit Leader Initials



Void:


Sheet Subset:


PLAN Subset Sheets:


Sheet Number


1 of 7


26


















Unit Information Unit Leader Initials





| | As Constructed | | R CANYON | | | | Project No./Code | | |
|---|----------------|---------------|----------|-------------|------|--------|------------------|----|--|
| | No Revisions: | STA. 10: | | | _ | | STU C070-043 | | |
| I | Revised: | Designer: | | Structure | | | 19888 | | |
| Ì | | Detailer: | REW | Numbers | | | | | |
| | Void: | Sheet Subset: | PROFILE | Subset Shee | ets: | 1 of 8 | Sheet Number | 33 | |



Detailer:


Sheet Subset:

PROFILE Subset Sheets:

Sheet Number

34

Void:



Designer:

Detailer:

Sheet Subset:

Revised:

Void:

SDB Structure


REW Numbers

PROFILE Subset Sheets:

19888

Sheet Number

35



REW Numbers

PROFILE Subset Sheets:

Sheet Number


36

Detailer:

Sheet Subset:

Void:

zadkison 3:23:51 PM 0:\2015 Projects\15-025.01 Boulder Canyon TrailExtensio



Revised:

Void:

19888

Sheet Number


37

REW Numbers

PROFILE Subset Sheets:

Detailer:

Sheet Subset:



Designer:

Detailer:

Sheet Subset:

Revised:

Void:

SDB Structure

PROFILE Subset Sheets:


Numbers

CZC

19888

Sheet Number

38



Revised:

Void:

19888

39

Sheet Number


CZC

Detailer:

Sheet Subset:

Numbers

PROFILE Subset Sheets:



REW Numbers

PROFILE Subset Sheets:


Sheet Number


40


Detailer:

Sheet Subset:

Void:








GUARDRAIL TYPE 7 TRANSITION

NOTES:

- 1. TRANSITION SHALL BE PAID FOR AS LF OF GUARDRAIL TYPE 7 (STYLE CE) (SPECIAL)
- 2. COLORED CONCRETE SHALL BE USED FOR THE TRANSITION AND SHALL MATCH THE COLORING USED ON THE REMAINDER OF THE TYPE 7 SECTION. NO STONE VENEER SHALL BE PLACED ON THE TRANSITION.

| Print Date: 11/17/2016 | | Sheet Revisions | | | | |
|------------------------------|----------------------------------|-----------------|----------|-------|--|--|
| Drawing File Name: 19888DES. | _Guardrail Transition Detail.dgn | Date: | Comments | Init. | | |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted | | | | | |
| Unit Information | Unit Leader Initials | | | | | |
| /// M | ULLER | | | | | |
| 1 | VIEEDING COMPANY | | | | | |





| As Constructed | | R CANYON | Project No./Code | | | |
|----------------|----------------------------|----------|----------------------|--------|--------------|----|
| No Revisions: | | DET | STU C070-043 | | | |
| Revised: | Designer: | | Structure Numbers | | 19888 | |
| Void: | Detailer: Sheet Subset: | | Subset Sheets: | 1 of 1 | Sheet Number | 43 |

| Pothole Date | Test Hole Number | Utility Type / Description | Alignment | Station | Offset (Ft.) | Surface Elevation | Depth to Top Feet (Inches) | Outside Diameter Feet (Inches) | Depth to Bottom Feet (Inches) | Utility Top Elevation | Utility Bottom Elevation | X Coordinate (EASTING) | Y Coordinate (NORTHING) | Comments / Remarks |
|-----------------|---------------------|-------------------------------|-------------------------|--------------------|----------------------------|----------------------|-------------------------------|-----------------------------------|----------------------------------|--------------------------|-----------------------------|---------------------------|----------------------------|---|
| 08/04/16 | PH-1 | Water | Boulder Canyon Trail | 106+01.34 | 40.97' RT. | 5808.15 | 1.00 (12) | 2.00 (24) | 3.00 (36) | 5807.15 | 5805.15 | 95935.82 | 97679.44 | |
| 07/30/16 | PH-4B | Water | Boulder Canyon Trail | 109+23.09 | 11.82 RT. | 5800.28 | 5.50 (66) | 1.33 (16) | 6.83 (82) | 5794.78 | 5793.45 | 95917.85 | 97941.75 | |
| 07/30/16 | PH-5 | Water | Boulder Canyon Trail | 114+21.5 | 19.31 LT. | 5794.35 | 2.00 (24) | 1.33 (16) | 3.33 (40) | 5792.35 | 5791.02 | 95785.60 | 98413.77 | |
| 07/30/16 | PH-6 | Water | Boulder Canyon Trail | 116+11.75 | 6.87 LT. | 5792.73 | 4.50 (54) | 1.33 (16) | 5.83 (70) | 5788.23 | 5786.90 | 95752.20 | 98595.93 | |
| 07/30/16 | PH-7 | Water | Boulder Canyon Trail | 119+47.5 | 30.23 LT. | 5781.60 | 1.92 (23) | 1.33 (16) | 3.25 (39) | 5779.68 | 5778.35 | 95974.38 | 98824.38 | |
| 07/30/16 | PH-8 | Water | Boulder Canyon Trail | 119+87.93 | 26.91 LT. | 5780.36 | 1.50 (18) | 1.33 (16) | 2.83 (34) | 5778.86 | 5777.53 | 96010.38 | 98843.09 | |
| 07/30/16 | PH-9 | Unknown | Boulder Canyon Trail | Approx. 136+25. | Approx. 0.00 On Alg. | N/A | Unknown | Unknown | Unknown | Unknown | Unknown | N/A | N/A | Unknown utility not found. Unable to confirm any utility crossings in that area |
| 07/30/16 | PH-10 | Unknown | Boulder Canyon Trail | Approx. 138+00. | Approx. 0.00 On Alg. | N/A | Unknown | Unknown | Unknown | Unknown | Unknown | N/A | N/A | Unknown utility not found. Unable to confirm any utility crossings in that area |
| 07/30/16 | PH-11 | Electric | Boulder Canyon Trail | 138+70.92 | 45.34 LT. | 5751.60 | 2.83 (34) | 0.08 (1) | 2.92 (35) | 5748.77 | 5748.68 | 96009.74 | 100084.11 | |
| 07/30/16 | PH-12 | Electric | Boulder Canyon Trail | 139+08.84 | 8.29 LT. | 5739.18 | 2.75 (33) | 0.08 (1) | 2.83 (34) | 5736.43 | 5736.35 | 96055.13 | 100056.71 | |
| 08/04/16 | PH-13 | Water | 4-Mile Canyon | | | 5748.30 | Unknown | Unknown | Unknown | Unknown | Unknown | 96191.81 | 100230.68 | Water Line not Found |
| 08/08/16 | PH-13.1 | Water | 4-Mile Canyon | | | 5733.37 | 3.33 (40) | 0.08 (1) | 3.42 (41) | 5730.04 | 5729.95 | 96240.08 | 100248.73 | |
| 08/08/16 | PH-13.2 | Water | 4-Mile Canyon | | | 5733.73 | 3.83 (46) | 0.08 | 3.92 (47) | 5729.90 | 5729.81 | 96242.38 | 100251.38 | |
| 08/04/16 | PH-16 | Water | Boulder Canyon Trail | 106+04.96 | 130.95 RT. | 5810.87 | 1.92 | 2.00 | 3.92 (47) | 5808.95 | 5806.95 | 95887.32 | 97601.68 | |
| 08/04/16 | PH-17 | Water | Boulder Canyon Trail | 106+05.67 RT. | 91.4 66' | 5802.11 | 2.00 | 2.00 | 4.00 (48) | 5800.11 | 5798.11 | 95915.27 | 97630.05 | |

| Print Date: 11/16/2016 | |
|--------------------------------------|-----------------------|
| Drawing File Name: 19888UTIL_Pothole | Log.dgn |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| 7//4 N AL II I | |

MULLER
ENGINEERING COMPANY

| | Sheet Revisions | | | | | | | |
|-------|-----------------|-------|--|--|--|--|--|--|
| Date: | Comments | Init. | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |





| As Constructed | | BOULD | ER CANYON | Project No./Code | | | |
|----------------|---------------|---------------|-----------|-----------------------|--|--------------|-----|
| | No Revisions: | (FOR | INFORM | | | STU C070-0 | 143 |
| | Revised: | Designer: | CZC | Structure | | 19888 | |
| | | Detailer: | CZC | Numbers | | | |
| | Void: | Sheet Subset: | UTIL TAB | Subset Sheets: 1 of 1 | | Sheet Number | 44 |

- 1. ALL WORK SHALL BE DONE IN ACCORDANCE WITH THE "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION", COLORADO DEPARTMENT OF TRANSPORATION, 2011 EDITION, AS MODIFIED BY THE PROJECT SPECIAL PROVISIONS AND THESE PLANS.
- 2. REFER TO REVISION OF SECTION 628 "PREFABRICATED STEEL BRIDGE" FOR SPECIFICATIONS AND REQUIREMENTS FOR THE PREFABRICATED STEEL BRIDGE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING WITH PREFABRICATED BRIDGE MANUFACTURER AND VERIFYING ALL DIMENSIONS SHOWN ON THE PLAN INCLUDING ABUTMENT SEATS AND LOCATION AND DIMENSIONS OF ANCHOR BOLTS PRIOR TO THE CONSTRUCTION OF THE BRIDGE ABUTMENTS.
- 3. EXCEPT AS SHOWN IN THE PLANS, STRUCTURE EXCAVATION SHALL BE IN ACCORDANCE WITH M-206-1 FOR CAST-IN-PLACE RETAINING WALLS. STRUCTURE BACKFILL SHALL MEET THE REQUIREMENTS FOR STRUCTURE BACKFILL (CLASS 1) UNLESS NOTED OTHERWISE.
- 4. STRUCTURE BACKFILL FOR THE ABUTMENT AND WINGS SHALL BE MECHANICALLY STABILIZED SOIL IN ACCORDANCE WITH THE EXCAVATION AND BACKFILL DETAILS.
- 5. THE SDILS AND FOUNDATION INVESTIGATION FOR THIS PROJECT WAS PERFORMED BY YEH AND ASSOCIATES, INC. THE SUBSURFACE CONDITIONS AND RECOMMENDATIONS FOR THE STRUCTURE PROJECT ARE CONTAINED IN A REPORT DATED AUGUST 22, 2016, JDB NUMBER 215-177.
- 6. A REPRESENTATIVE OF THE GEOTECHNICAL ENGINEER SHALL BE PRESENT TO OBSERVE THE FOUNDATION EXCAVATION PRIOR TO PLACEMENT OF SUBGRADE STABILIZATION.
- 7. EXPANSION JOINT MATERIAL SHALL MEET AASHTO SPECIFICATION M213.
- 8. COVERAGE FROM THE FACE OF CONCRETE TO THE FACE OF REINFORCEMENT SHALL BE 2 INCHES, UNLESS NOTED OTHERWISE.
- 9. ALL REINFORCING STEEL SHALL BE BLACK REINFORCING UNLESS OTHERWISE NOTED.
- 10. (E) DENDTES EPOXY CDATED REINFORCING STEEL.
- 1. THE FOLLOWING TABLE GIVES THE MINIMUM CLASS C LAP SPLICE LENGTH FOR EPOXY COATED REINFORCING BARS PLACED IN ACCORDANCE WITH SUBSECTION 602.06. THESE SPLICE LENGTHS SHALL BE INCREASED BY 25% FOR BARS SPACED AT LESS THAN 6" ON CENTER.

BAR SIZE #4 #5 #6 #7 #8 #9 #10 #11

SPLICE LENGTH FOR
CLASS D CONCRETE 1'-7" 2'-0" 2'-4" 2'-10" 3'-8" 4'-8" 5'-11" 7'-.

- 12. WHEN THE CONTRACTOR ELECTS TO SUBSTITUTE EPOXY COATED REINFORCEMENT FOR BLACK REINFORCING BARS, THE MINIMUM LAP SPLICE SHALL BE AS DESCRIBED ABOVE.
- 3. THE FOLLOWING TABLE GIVES THE MINIMUM CLASS C LAP SPLICE LENGTH FOR BLACK REINFORCING BARS PLACED IN ACCORDANCE WITH SUBSECTION 602.06. THESE SPLICE LENGTHS SHALL BE INCREASED BY 25% FOR BARS SPACED AT LESS THAN 6" ON CENTER.

BAR SIZE #4 #5 #6 #7 #8 #9 #10 #11

SPLICE LENGTH FOR
CLASS D CONCRETE 1'-5" 1'-9" 2'-1" 2'-6" 3'-3" 4'-1" 5'-2" 6'-4"

- 14. ALL CONCRETE SHALL BE CLASS D, f'c = 4,500 psi.
- 15. STRUCTURAL CONCRETE SHALL CONFORM TO CEMENTITIOUS MATERIALS REQUIREMENT CLASS O, CORRESPONDING TO SULFATE RESISTANCE CLASS O.
- 16. EXPOSED OUTSIDE CORNERS SHALL RECIEVE A 3/4" CHAMFER, UNLESS NOTED OTHERWISE.
- 17. BACKFILL OF STRUCTURES SHALL BE IN ACCORDANCE WITH "PHASING NOTES" LOCATED ON THE EXCAVATION AND BACKFILL DETAILS SHEET. IN NO CASE SHALL STRUCTURES BE BACKFILLED UNTIL ALL MEMBERS HAVE REACHED 80-PERCENT OF DESIGN STRENGTH.
- 18. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE STABILITY OF THE STRUCTURE DURING CONSTRUCTION.

Vert. Scale: As Noted

STRUCTURAL NOTES CONT.:

- 19. PERMANENT STEEL DECK FORMS ARE ALLOWED.
- 20. THE INFORMATION SHOWN ON THESE PLANS CONCERNING THE TYPE AND LOCATION OF UNDERGROUND UTILITIES IS NOT GUARANTEED TO BE ACCURATE OR ALL INCLUSIVE. THE CONTRACTOR IS RESPONSIBLE FOR MAKING HIS OWN DETERMINATION AS TO THE TYPE AND LOCATION OF UNDERGROUND UTILITIES AS MAY BE NECESSARY TO AVOID DAMAGE THERETO. THE CONTRACTOR SHALL CONTACT THE UTILITY NOTIFICATION CENTER OF COLORADO AT 1-800-922-1987 AT LEAST 2 DAYS (NOT INCLUDING THE DAY OF NOTIFICATION) PRIOR TO ANY EXCAVATION OR OTHER EARTHWORK.

DESIGN DATA:

AASHTO LRFD GUIDE SPECIFICATIONS FOR THE DESIGN OF PEDESTRIAN BRIDGES, 2° EDITION (2016 INTERIM)

AASHTO LRFD BRIDGE SPECIFICATIONS, 7™ EDITION (2016 INTERIM)

DESIGN METHOD: LOAD AND RESISTANCE FACTOR DESIGN

LIVE LOAD: VEHICLE LOAD: 10,000 LBS (H-5) OR PEDESTRIAN LOAD: 90 PSF

DEAD LOAD: SELF-WT AND WEIGHT OF SOIL OVERBURDEN

(WHERE APPLICABLE)

SOIL PARAMETERS:

UNIT WEIGHT: 135 PCF

EQUIV. FLUID PRESSURES: 38 PCF (ACTIVE)

60 PCF (AT-REST)

ALLOWABLE BEARING PRESSURE: 2500 x B'x (1-tan(W))2

REINFORCED CONCRETE:

CDDT CLASS D: $f_C' = 4,500 \text{ PSI}$

REINFORCING STEEL: $f_y = 60,000 \text{ PSI}$

STEEL PILING:

AASHTO M270 (ASTM A572) GRADE 50 ($F_V = 50,000 \text{ PSI}$)

REACTIONS AT BEARINGS (USED IN SUBSTRUCTURE DESIGN)

DEAD LOAD:

12.9 KIPS/BEARING x 4

LIVE LOAD:

15.7 KIPS/BEARING x 4

ABBREVIATIONS

EF = EACH FACE TO = TOP OF

TOW = TOP OF WALL BF = BACK FACE

BO = BOTTOM OF

BRG = BEARING

FF = FRONT FACE

OC = ON CENTER

Section or Detail Identification



Cross Reference Drawing Number (if blank or dash, reference is to same sheet)

SHEET LIST:

B1 STRUCTURE GENERAL NOTES

B2 SUMMARY OF APPROXIMATE QUANTITIES

B3 PEDESTRIAN BRIDGE GENERAL LAYOUT

B4 BRIDGE HYDRAULICS

B5 ABUTMENT 1 DETAILS

B6 ABUTMENT 2 DETAILS

B7-B8 ABUTMENT TYPICAL DETAILS

B9 EXCAVATION AND BACKFILL DETAILS

B10-B11 ARCHITECHTURAL TREATMENTS

STEEL PILING NOTES:

- 1. ALL PILES ARE HP12x74.
- REINFORCING PILE TIP (SEE DETAIL) REQUIRED FOR ALL PILES.
- PILES ARE ALL END BEARING AND SHALL BE DRIVEN TO REFUSAL.
- 4. IT IS ANTICIPATED THAT PRE-DRILLING AND BLASTING WILL BE REQUIRED TO FACILITATE PILE DRIVING, SEE DETAIL SHT. B7.
- 5. WAVE EQUATION ANALYSIS IS REQUIRED FOR THIS PROJECT TO VERIFY THE SUITABILITY OF THE DRIVING HAMMER. THE CONTRACTOR SHALL PERFORM THE ANALYSIS PRIOR TO THE START OF CONSTRUCTION. THE RESULTS OF THE ANALYSIS SHALL BE SUBMITTED TO THE ENGINEER FOR REVIEW.
- 6. THE CONTRACTOR SHALL CONDUCT A PILE DRIVING ANALYSIS (PDA) ON A MINIMUM OF ONE PILE AT EACH ABUTMENT.
- A REPRESENTATIVE OF THE GEOTECHNICAL ENGINEER SHALL BE PRESESENT DURING THE START OF EACH PILE DRIVING.
- 3. IN ACCORDANCE WITH SECTION 502, THE GEOTECHNICAL ENGINEER SHALL DEVELOP VIRTUAL REFUSAL CRITIERA DURING CONSTRUCTION USING THE RESULTS OF THE PDA.

ARCHITECTURAL TREATMENT

- 1. THE SELECTION OF STONE VENEER TYPE AND MANUFACTURER SHALL BE BY THE OWNER. THE CONTRACTOR SHALL PROVIDE VENEER SAMPLES AND MOCKUPS AS REQUIRED BY THE PROJECT SPECIAL PROVISIONS. THE MAXIMUM THICKNESS OF VENEER SHALL BE 1½". VENEER SHALL BE ATTACHED BY MEANS OF ADHESIVE MORTAR IN ACCORDANCE WITH THE PROJECT SPECIAL PROVISIONS. PAYMENT FOR ALL WORK SHALL BE MADE UNDER (601) CUT STONE VENEER.
- 2. EXPOSED CONCRETE NOT RECEIVING VENEER SHALL BE GIVEN A CLASS 2 RUBBED FINISH (INCLUDED IN THE COST OF THE CONCRETE (CLASS D.)

Know what's below Call before you dig.

Unit Information Unit Leader Initials

MULLER

ENGINEERING COMPANY

Print Date: 11/16/2016

Horiz Scale: 1:1

Drawing File Name: 19888BRG_General Notes.dqn

Sheet Revisions


Date: Comments Init.








| | | | | | | <u> </u> | |
|----------------|---------------|-------------------------|--------------------------|------------------|--------------|----------|--|
| As Constructed | | R CANYON DESTRI | N | Project No./Code | | | |
| No Revisions: | | GENERA | STU C070-043 | | | | |
| Revised: | Designer: | Designer: ASP Structure | | | 19888 | | |
| | Detailer: | LJLJ | Numbers | | | | |
| Void: | Sheet Subset: | BRIDGE | Subset Sheets: B1 of B25 | | Sheet Number | 45 | |


| | | | | - | Summ | nary of Quantities | | | | | |
|----------|---|---------------------------------|-------------|--|---------|-----------------------|-------------------|-------------------|---|-----------------|--|
| А | | | | | BOULDER | CANYON TRAIL EXTENSIO | N | | | | |
| | | IT | TEM NO. D | ESCRIPTION | UNIT | PED BRIDGE | CBC 1 | CBC 2 | TOTAL | | |
| + | | 20 | 06-00000 S | tructure Excavation | CY | 85 | 1005 | 1815 | 2905 | | |
| | | 20 | 06-00065 S | tructure Backfill (Flow-Fill) | CY | | 360 | 415 | 775 | | |
| В | | 20 | 06-00100 S | tructure Backfill (Class 1) | CY | 140 | 685 | 430 | 1255 | | |
| | | 20 | 06-00360 M | dechanical Reinforcement of Soil | CY | 140 | | | 140 | | |
| + | | 20 | 06-00510 Fi | ilter Material (Class A) | CY | | 75 | 125 | 200 | | |
| | | 20 | 06-01781 S | horing (Area 1) | LS | | 1 | | 1 | | |
| С | | 20 | 06-01782 S | horing (Area 2) | LS | | 1 | | 1 | | |
| | | | | choring (Area 3) | LS | | | 1 | 1 | | |
| ┨ | | | | horing (Area 4) | LS | | | 1 | 1 | | |
| | | | | rhoring (Area 5) | LS | | | 1 | 1 | | |
| D | | | | Seotextile (Drainage) (Class 2) | SY | | 485 | 755 | 1240 | | |
| | | | | Seotextile (Drainage) (Class 3) | SY | | 403 | 35 | 35 | | |
| 4 | | | | rilling Hole to Facilitate Pile Driving | LF | 30 | | 30 | 30 | | |
| l | | | | | | | | | | | |
| Е | | | | last Hole to Facilitate Pile Driving | LF | 60 | | | 60 | | |
| | | | 02-00460 P | | EACH | 6 | | | 6 | | |
| 4 | | | | teel Piling (HP 12x74) | LF | 136 | | | 136 | | |
| l | | _ | | teinforced Concrete Facing | SF | | | 495 | 495 | | |
| l | | 51 | 14-00200 P | edestrian Railing (Steel) | LF | 60 | 207 | 334 | 601 | | |
| l | | 60 | 01-03000 C | concrete Class D | CY | | | 21 | 21 | | |
| l | | | 01-03040 C | concrete Class D (Bridge) | CY | 44 | | | 44 | | |
| l | | 60 | 01-03050 C | concrete Class D (Wall) | CY | 24 | 197 | 165 | 386 | | |
| l | | 60 | 01-40005 C | tut Stone Veneer | SF | 574 | 1122 | 1496 | 3192 | | |
| l | | 60 | 01-40400 S | tructural Concrete Stain | SY | | 36 | 36 | 72 | | |
| ı | | 60 | 01-XXXX C | concrete (Class G) | CY | | 15 | 25 | 40 | | |
| l | | ▲ 60 | 02-00000 R | leinforcing Steel | LB | 8135 | 29970 | 24700 | 62805 | | |
| ı | | 60 | 03-50006 6 | Inch Plastic Pipe | LF | | 138 | | 138 | | |
| l | | 60 | 03-71609 16 | 6x9 Foot Concrete Box Culvert (Precast) | LF | | 72 | | 72 | | |
| ı | | 60 | 03-71610 | 6x10 Foot Concrete Box Culvert (Precast) | LF | | | 120 | 120 | | |
| l | | 60 | 04-19000 In | nlet Special | EACH | | 1 | | 1 | | |
| | NOTES: | 60 | 05-00040 4 | Inch Perforated Pipe Underdrain | LF | | | 69 | 69 | | |
| ı | ■ INCLUDES 12 CY TRAIL APPROACH | 60 | 05-83002 G | Seocomposite Drain with Pipe | SY | | 183 | 262 | 445 | | |
| | SLAB | 60 | 05-84000 S | subsurface Drain Outlet | LF | | 55 | 44 | 99 | | |
| | ▲ INCLUDES 2790 lbs OF TRAIL REINFORCEMENT | | | Inch Galvanized Pipe | LF | | | 14 | 14 | | 811 |
| | INCLUDES 136 LF BIKEWAY MOUNTED | | | uridge Girder and Deck Unit (70 Feet to 75 Feet) | EACH | 1 | | | 1 | | |
| | PEDESTRIAN RAILING | | · - | | , | | 1 | 1 | 1 | | Know what's belo y Call before yo |
| \vdash | Print Date: 11/16/2016 | Т | | Sheet Revisions | | | <u> </u> | A - O - 1 - 1 - 1 | BOULDER CANYON TR | AIL EXTENSION | |
| _ | Drawing File Name: 19888BRG_Summary of Quantities.dgn | | Date: | Comments Init. | | Á | () | As Constructed | SUMMARY OF G | | Project No./ |
| - | Horiz. Scale: 1:1 Vert. Scale: As Noted | \supseteq | | | | | | lo Revisions: | | | STU C070-0 |
| \vdash | Unit Information Unit Leader Initials | \Longrightarrow ${\mathbb F}$ | | co | | | Boulder County | evised: | Designer: ASP Str Detailer: LJLJ Nur | ucture mbers | 19888 |
| 1 | MULLER ENGINEERING COMPANY | $\exists \vdash$ | | Region | 4 | | | 'oid: | Detailer: LJLJ Nur Sheet Subset: BRIDGE Su | | 25 Sheet Number |























- 1. ALL WORK SHALL BE DONE IN ACCORDANCE WITH THE "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION", COLORADO DEPARTMENT OF TRANSPORATION, 2011 EDITION, AS MODIFIED BY THE PROJECT SPECIAL PROVISIONS AND THESE PLANS.
- 2. EXCEPT AS SHOWN IN THE PLANS, STRUCTURE EXCAVATION SHALL BE IN ACCORDANCE WITH M-206-1 FOR RETAINING WALLS AND BOX CULVERTS. STRUCTURE BACKFILL SHALL MEET THE REQUIREMENTS FOR STRUCTURE BACKFILL (CLASS 1) UNLESS NOTED OTHERWISE.
- 3. THE SDILS AND FOUNDATION INVESTIGATION FOR THIS PROJECT WAS PERFORMED BY YEH AND ASSOCIATES, INC. THE SUBSURFACE CONDITIONS AND RECOMMENDATIONS FOR THE STRUCTURE PROJECT ARE CONTAINED IN A REPORT DATED AUGUST 22, 2016, JOB NUMBER 215-177.
- 4. A REPRESENTATIVE OF THE GEOTECHNICAL ENGINEER SHALL BE PRESENT TO OBSERVE THE FOUNDATION EXCAVATION PRIOR TO PLACEMENT OF SUBGRADE STABILIZATION.
- 5. EXPANSION JOINT MATERIAL SHALL MEET AASHTO SPECIFICATION M213.
- 6. COVERAGE FROM THE FACE OF CONCRETE TO THE FACE OF REINFORCEMENT SHALL BE 2 INCHES, UNLESS NOTED OTHERWISE.
- 7. ALL REINFORCING STEEL IN HEADWALL, RETAINING WALLS, AND CONCRETE FOOTING SHALL BE BLACK REINFORCING UNLESS OTHERWISE NOTED.
- 8. (E) DENOTES EPOXY COATED REINFORCING STEEL.
- . THE FOLLOWING TABLE GIVES THE MINIMUM CLASS C LAP SPLICE LENGTH FOR EPOXY COATED REINFORCING BARS PLACED IN ACCORDANCE WITH SUBSECTION 602.06. THESE SPLICE LENGTHS SHALL BE INCREASED BY 25% FOR BARS SPACED AT LESS THAN 6" ON CENTER.

| BAR SIZE | #4 | #5 | #6 | #7 | #8 | #9 | #10 | #11 |
|---------------------------------------|--------|--------|--------|---------|--------|--------|---------|--------|
| SPLICE LENGTH FOR CLASS D CONCRETE | 1'-7'' | 2'-0'' | 2'-4'' | 2'-10'' | 3'-8'' | 4'-8'' | 5'-11'' | 7'-3'' |

- 10. WHEN THE CONTRACTOR ELECTS TO SUBSTITUTE EPOXY COATED REINFORCEMENT FOR BLACK REINFORCING BARS, THE MINIMUM LAP SPLICE SHALL BE AS DESCRIBED ABOVE.
- 1. THE FOLLOWING TABLE GIVES THE MINIMUM CLASS C LAP SPLICE LENGTH FOR BLACK REINFORCING BARS PLACED IN ACCORDANCE WITH SUBSECTION 602.06. THESE SPLICE LENGTHS SHALL BE INCREASED BY 25% FOR BARS SPACED AT LESS THAN 6" ON CENTER.

| BAR SIZE | #4 | #5 | #6 | #7 | #8 | #9 | #10 | #11 |
|---------------------------------------|-------|--------|-------|--------|--------|--------|--------|------|
| SPLICE LENGTH FOR CLASS D CONCRETE | 1'-5" | 1'-9'' | 2'-1" | 2'-6'' | 3'-3'' | 4'-1'' | 5'-2'' | 6'-4 |

- 12. ALL CONCRETE IN HEADWALLS, RETAINING WALLS, AND CONCRETE PHASING SHALL BE CLASS D, $\rm f^{\prime}_{C}=4,\!500~psi.$
- 13. 4" CONCRETE OVERLAY IN BOX CULVERTS SHALL BE CLASS G, f' = 4,500 psi.
- 14. STRUCTURAL CONCRETE SHALL CONFORM TO CEMENTITIOUS MATERIALS REQUIREMENT CLASS O, CORRESPONDING TO SULFATE RESISTANCE CLASS O.
- 15. THE HEADWALL AND WINGWALL FOOTINGS SHALL BE PLACED MONOLITHICALLY.
- 5. EXPOSED OUTSIDE CORNERS SHALL RECIEVE A $rac{3}{4}$ " CHAMFER,UNLESS NOTED OTHERWISE.
- 17. THE CONTRACTOR SHALL NOT BACKFILL STRUCTURES UNTIL TOP SLAB AND WALLS HAVE REACHED 80 PERCENT OF DESIGN STRENGTH.
- 18. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE STABILITY OF THE STRUCTURE DURING CONSTRUCTION.
- .9. THE INFORMATION SHOWN ON THESE PLANS CONCERNING THE TYPE AND LOCATION OF UNDERGROUND UTILITIES IS NOT GUARANTEED TO BE ACCURATE OR ALL INCLUSIVE. THE CONTRACTOR IS RESPONSIBLE FOR MAKING HIS OWN DETERMINATION AS TO THE TYPE AND LOCATION OF UNDERGROUND UTILITIES AS MAY BE NECESSARY TO AVOID DAMAGE THERETO. THE CONTRACTOR SHALL CONTACT THE UTILITY NOTIFICATION CENTER OF COLORADO AT 1-800-922-1987 AT LEAST 2 DAYS (NOT INCLUDING THE DAY OF NOTIFICATION) PRIOR TO ANY EXCAVATION OR OTHER EARTHWORK.

DESIGN DATA:

AASHTO LRFD BRIDGE SPECIFICATIONS, 7TH EDITION (2016 INTERIM)

DESIGN METHOD: LOAD AND RESISTANCE FACTOR DESIGN

LIVE LOAD: VEHICLE LOAD: AASHTO HL93

LIVE LDAD SURCHARGE: 2'-0" OF EARTH

(WHERE APPLICABLE)

DEAD LOAD: SELF-WT AND WEIGHT OF SOIL OVERBURDEN

(WHERE APPLICABLE)

SOIL PARAMETERS:

UNIT WEIGHT: 135 PCF

EQUIV. FLUID PRESSURES: 38 PCF (ACTIVE)

60 PCF (AT-REST)

WALL NOMINAL BEARING RESISTANCE: 2500 x B' x (1-tan(W))²

BDX NDMINAL BEARING RESISTANCE: $70,000 \times (1-tan(W))^2$

REINFORCED CONCRETE:

CDOT CLASS D: $f'_C = 4,500 \text{ PSI}$ REINFORCING STEEL: $f_V = 60,000 \text{ PSI}$

 $\Pi C = \Pi N CENTER$

ABBREVIATIONS

FF = FRONT FACE

EF = EACH FACE TO = TOP OF

TOW = TOP OF WALL BF = BACK FACE

BO = BOTTOM OF BRG = BEARING

POB = POINT OF BEGINNING FG = FINISHED GRADE

POE = POINT OF ENDING

Section or Detail Identification



<u>Cross Reference Drawing Number</u> (if blank or dash, reference is to same sheet)

SHEET LIST:

| B12 | UNDERCROSSING STRUCTURE GENERAL NOTES |
|---------|---------------------------------------|
| B13-B14 | BOX CULVERT GENERAL LAYOUT |
| B15 | TYPICAL UNDERCROSSING SECTION |
| B16-B17 | WALLS 3, 5, 6, AND 7 GENERAL LAYDUT |
| B18-B19 | WALLS 9 AND 10 GENERAL LAYOUT |
| B20-B21 | HEADWALL DETAILS |
| B22 | RETAINING WALL DETAILS |
| B23 | ARCHITECTURAL TREATMENTS |
| B24-B25 | PEDESTRIAN BRIDGE RAILING DETAILS |


ARCHITECTURAL TREATMENT


- 1. THE SELECTION OF STONE VENEER TYPE AND MANUFACTURER SHALL BE BY THE OWNER. THE CONTRACTOR SHALL PROVIDE VENEER SAMPLES AND MOCKUPS AS REQUIRED BY THE PROJECT SPECIAL PROVISIONS. THE MAXIMUM THICKNESS OF VENEER SHALL BE 1½. VENEER SHALL BE ATTACHED BY MEANS OF ADHESIVE MORTAR IN ACCORDANCE WITH THE PROJECT SPECIAL PROVISIONS. PAYMENT FOR ALL WORK SHALL BE MADE UNDER (601) CUT STONE VENEER.
- 2. EXPOSED CONCRETE NOT RECEIVING VENEER SHALL BE GIVEN A CLASS 2 RUBBED FINISH (INCLUDED IN THE COST OF THE CONCRETE (CLASS D.)





Print Date: 11/16/2016 BOULDER CANYON TRAIL EXTENSION Sheet Revisions Project No./Code As Constructed UNDERCROSSING STRUCTURE Drawing File Name: 19888BRG_Undercrossing General Notes.dgn Date: Comments Init. No Revisions: GENERAL NOTES STU C070-043 Horiz. Scale: 1:1 Vert. Scale: As Noted Unit Information Unit Leader Initials ASP Structure Revised: 19888 CO Numbers Detailer: \perp JL J Void: Sheet Number 56 Region **BRIDGE** Subset Sheets: B12 of B25 Sheet Subset:


| MITIAL DATE | DATE |





























FOOTING STEP DETAIL 2
SEE RETAINING WALL ELEVATION
FOR LOCATION




EXPANSION JOINT




WEAKENED PLANE
SEE RETAINING WALL
ELEVATION FOR SPACING





| | DESIG | GN DATA-REINI | ORCING STEEL | DIMENSIONS | | |
|----------|------------|----------------|---------------|-----------------|------------|------------|
| Н | 3' | 6' | 9' | 12' | 15' | 17' |
| TW | 1'-0" | 1'-0" | 1'-2" | 1'-2" | 1'-4" | 1'-4" |
| W | 5'-6" | 7'-0" | 9'-0" | 11'-4" | 13'-0" | 13'-6" |
| С | 1'-3" | 1'-6" | 1'-9" | 2'-0" | 2'-3" | 2'-6" |
| В | 4'-3" | 5'-6" | 7'-3" | 9'-4" | 10'-9" | 11'-0" |
| TF | 1'-0" | 1'-0" | 1'-2" | 1'-2" | 1'-4" | 1'-4" |
| b BARS | #5 @ 1'-0" | #5 @ 1'-0" | #5 @ 6" | #5 @ 6" | #7 @ 6" | #8 @ 6" |
| c BARS | #5 @ 1'-0" | #5 @ 1'-0" | #5 @ 6" | #5 @ 6" | #7 @ 6" | #8 @ 6" |
| d BARS | #5 @ 1'-0" | #5 @ 1'-0" | #5 @ 1'-0" | #5 @ 1'-0" | #6 @ 1'-0" | #6 @ 1'-0" |
| | | | | | | |
| B Splice | 1'-9" | 1'-9" | 4'-6" | 5'-8" | 8'-5" | 11'-8" |
| | Design D | ata applies to | the specified | height (H) or I | ess. | |



RETAINING WALL TYPICAL SECTION

SCALE: 1/4" = 1'-0"

| DESIGN DATA-REINFORCING STEEL-DIMENSIONS | | | | | | |
|--|------------|------------|------------|------------|---------|--|
| Н | 3' | 6' | 9' | 12' | 15' | |
| TW | 1'-0" | 1'-2" | 1'-2" | 1'-4" | 1'-4" | |
| W | 6'-6" | 8'-8" | 10'-8" | 12'-10" | 14'-10" | |
| С | 4'-0" | 6'-0" | 8'-0" | 10'-0" | 12'-0" | |
| В | 2'-6" | 2'-8" | 2'-8" | 2'-10" | 2'-10" | |
| TF | 1'-0" | 1'-2" | 1'-2" | 1'-4" | 1'-8" | |
| b BARS | #5 @ 1'-0" | #5 @ 1'-0" | #5 @ 1'-0" | #6 @ 1'-0" | #6 @ 6" | |
| d BARS | #5 @ 1'-0" | #5 @ 6" | #6 @ 6" | #7 @ 6" | #8 @ 6" | |
| | | | | | | |
| B Splice | 1'-9" | 1'-9" | 1'-9" | 5'-8" | 6'-7" | |
| Design Data applies to the specified height (H) or less. | | | | | | |

RETAINING WALL NOTES:

1. ALL ITEMS REQUIRED TO INSTALL EXPANSION JOINT AND WEAKENED PLANE PER THIS DETAIL WILL NOT BE MEASURED DIRECTLY BUT SHALL BE INCLUDED IN THE COST OF CONCRETE CLASS D.

2. HORIZONTAL REINFORCEMENT IN THE FOOTING AND STEM SHALL BE MADE CONTINUOUS AT WALL CORNERS, UNLESS NOTED OTHERWISE.


| 811. | | | | |
|---|--|--|--|--|
| Know what's below Call before you dig. | | | | |


| Print Date: 11/16/2016 | |
|--------------------------------------|-----------------------|
| Drawing File Name: 19888BRG_Retainin | g Wall Details.dgn |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| MUL ENGINEERING | \ |

| | Date: | Comments | Init. | |
|---|-------|----------|-------|--------|
| | | | | |
| | | | | CO. |
| 0 | | | | |
| | | | | Region |

| CDOI | Boul |
|------|------|
| on 4 | |

| As Constructed | BOULDER CANYON TRAIL EXTENSION RETAINING WALL DETAILS | | | Project No./Code | | | \vdash | | |
|----------------|---|--------|---------------------------|------------------|-----------------|----|----------|----|---|
| No Revisions: | | | | STU C070-043 | | | | | |
| Revised: | Designer: | | Structure | | | | 19888 | | ĸ |
| | Detailer: | LJLJ | Numbers | | | | | ł | |
| /oid: | Sheet Subset: | BRIDGE | Subset Sheets: B22 of B25 | | Sheet Number 66 | | | | |
| 11 | 12 | 13 | | 14 | | 15 | | 16 | • |





Revised:

Void:

19888

68

Sheet Number

Numbers

Subset Sheets: B24 of B25

LJLJ


BRIDGE

Detailer:

Sheet Subset:

CO

Region



Designer:

Detailer:

Sheet Subset:

Revised:

Void:

SEH Structure

MJW

Numbers

Subset Sheets:

19888

Sheet Number

70

Unit Information

Unit Leader Initials

Yeh and Associates, Inc.

Consulting Engineers & Scientists

Void:

Sheet Subset:

Subset Sheets:

Region 4

71

Sheet Number

Consulting Engineers & Scientists

| Print Date: 11/16/2016 | |
|-------------------------------|-----------------------|
| Drawing File Name: 19888MAT_C | ED_TAB.dgn |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| | |
| | |


| | Sheet Revisions | | | | |
|-----------|----------------------|--|--|--|--|
| | Date: Comments Init. | | | | |
| \bigcap | | | | | |



| 117 A. M. |
|-------------------|
| Boulder County |
| |

| As Constructed | BOULDER CANYON TABULATION OF G | TRAIL EXTENSION | Project No./Code | |
|----------------|--------------------------------|-----------------|------------------|--|
| No Revisions: | | K BOLTING | STU C070-043 | |
| Revised: | Designer: SEH | Structure | 19888 | |
| | Detailer: | Numbers | | |
| Void: | Sheet Subset: | Subset Sheets: | Sheet Number 72 | |

fourthrine-Use Might of CDIT-Pentable. Ibl



Void:

Sheet Subset:

Subset Sheets:

73

Sheet Number

Consulting Engineers & Scientists

- 1.1 GROUND NAILS GRADE 75 THREAD BAR OR EQUIVALENT IN ACCORDANCE WITH ASTM A615 AND EPOXY COATED IN ACCORDANCE WITH ASTM A775 AS SHOWN ON THE DRAWINGS.

 FY=75,000 PSI
- 1.2 GROUT GROUT MAY BE NEAT-CEMENT OR WITH SAND, WITH TYPE II CEMENT IN ACCORDANCE WITH ASTM C150. WATER-CEMENT RATIO SHOULD BE BETWEEN 0.4 AND 0.6 AND GROUT SHOULD DEVELOP THE FOLLOWING STRENGTHS AT THE SPECIFIED CURE F'C=3,000 PSI MINIMUM 7 DAY
- 1.3 END HARDWARE NUTS AND WASHERS SHALL BE IN ACCORDANCE WITH GROUND NAIL MANUFACTURER'S RECOMMENDATIONS. BEARING PLATE SHALL BE IN ACCORDANCE WITH ASTM A36, GRADE 36.
- SHOTCRETE SHOTCRETE MIX SHALL CONSIST OF TYPE II CEMENT IN ACCORDANCE WITH ASTM C150, POTABLE WATER AND NORMAL WEIGHT AGGREGATE IN ACCORDANCE WITH ASTM C33. ADMIXTURES, IF USED, SHOULD BE NON-CORROSIVE TO STEEL. F'C=4,500 PSI (28-DAY STRENGTH)
- 1.5 UNLESS OTHERWISE NOTED ON THE PLANS, MINIMUM COVER OF SHOTCRETE REINFORCEMENT AND NAIL END HARDWARE SHOULD BE AS FOLLOWS:
 FACE EXPOSED TO WEATHER 2"
 FACE EXPOSED TO SOIL 3"
- 1.6 WELDED WIRE MESH SHALL BE IN ACCORDANCE WITH ASTM A185. FY=60,000 PSI
- WALERS AND VERTICAL BEARING BARS SHALL BE IN ACCORDANCE WITH ASTM A615. FY=60,000 PSI
- STRIP DRAINS CONSIST OF 12" WIDE DIMPLED CORES WRAPPED IN GEOTEXTILE.IN CONFORMANCE WITH CDOT REVISED SECTION 504.
- CENTRALIZERS SHOULD BE PLASTIC AND ATTACHED TO THE NAILS IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.

2.0 GROUND NAIL WALL CONSTRUCTION SEQUENCE

- EXCAVATE ONE LIFT TO A MAXIMUM DEPTH OF FIVE (5) FEET. BOULDERS, COBBLES, AND/OR BEDROCK MAY BE ENCOUNTERED AT ANY DEPTH OF THE EXCAVATION OR DRILLING. WHERE EXCAVATION HAS ALREADY TAKEN PLACE FOR CBC OR ADJACENT CIP WALL CONSTRUCTION, BACKFILL THE VOID WITH CLASS 1 STRUCTURE BACKFILL OR STRUCTURE BACKFILL (FLOW-FILL), ACCORDING TO THE SPECIFICATIONS OF CDOT SECTION 206.03. IF SLOUGHING GROUND CONDITIONS ARE ENCOUNTERED, GROUND NAILS MAY BE DRILLED AND INSTALLED THROUGH A TEMPORARY STABILIZING BERM AND/OR PLACEMENT OF A SACRIFICIAL REINFORCED SHOTCRETE FLASH COAT MAY BE USED TO TEMPORARILY STABILIZE THE EXCAVATION PRIOR TO DRILLING GROUND NAILS. CARE SHOULD BE TAKEN DURING EXCAVATION THAT NO GROUND IS LOST FROM BEHIND THE SHOTCRETE OF THE PRIOR LIFT.
- 2.2 INSTALL GROUND NAILS AT THE SPACINGS AND TO THE LENGTHS SHOWN ON THE PLANS. THE TOP ROW OF GROUND NAILS SHALL BE WITHIN 2.5 FEET OF THE TOP OF THE WALL. THE BOTTOM ROW OF NAILS SHALL BE WITHIN 3 FEET OF THE BOTTOM OF THE WALL. THE TOLERANCE FOR GROUND NAIL LOCATIONS SHALL BE 6 INCHES. TREMIE THE GROUT FROM THE BOTTOM OF THE HOLE UP.
- INSTALL STRIP DRAINS, WELDED WIRE MESH, WALERS AND VERTICAL BEARING BARS AS SHOWN ON THE DRAWINGS. USE PLASTIC CHAIRS TO HOLD THE WELDED WIRE MESH AWAY FROM THE SOIL AS
- INSTALL SHOTCRETE TO THE MINIMUM THICKNESS SHOWN ON THE DRAWINGS AND TO ATTAIN THE MINIMUM COVERAGE'S SPECIFIED HEREIN.GIVE SPECIAL ATTENTION TO FILLING THE VOID IN THE BORE HOLE ABOVE THE GROUT LINE.COLD WEATHER PROTECTION MEASURES MAY BE NECESSARY. 2.4
- INSTALL THE GROUND NAIL END HARDWARE AFTER THE SHOTCRETE HAS BEEN INSTALLED. WHILE THE SHOTCRETE IS STILL WET, EMBED THE PLATE INTO THE SHOTCRETE SURFACE UNTIL THERE IS NO VOID BEHIND THE PLATE. HAND TIGHTEN THE NUT. APPLY ADDITIONAL SHOTCRETE TO ATTAIN MINIMUM COVERAGE FOR THE GROUND NAIL AND END HARDWARE.
- 2.6 ONCE THE GROUT AND SHOTCRETE OF THE CURRENT LIFT HAVE ATTAINED 50% OF THEIR SPECIFIED STRENGTHS, REPEAT CONSTRUCTION SEQUENCE TO THE BOTTOM OF THE WALL.
- AT THE BOTTOM LIFT, CONSTRUCT DRAINPIPE, FILTER MATERIAL, AND MANIFOLD GEOCOMPOSITE STRIP DRAINS AS SHOWN ON THE DRAWINGS.

3.0 GROUND NAIL WALL DESIGN PARAMETERS

3.1 THE FOLLOWING VALUES HAVE BEEN USED FOR DESIGN PARAMETERS:

Φ c γ Qd (DEG) (PSF) (PCF) (lb/ft) 36 500 120 790

ANGLE OF INTERNAL FRICTION COHESION UNIT WEIGHT DESIGN SHEAR RESISTANCE BOND STRESS (ALLOWABLE)

CO

Region 4

3.2 NO GROUNDWATER TABLE WAS ASSUMED.

3.3 FACTORS OF SAFETY

BEARING CAPACITY - FS=2.5 OVERTURNING - ECCENTRICITY<=B/6 GLOBAL STABILITY - FS=1.35 PULLOUT - FS=2.0
YIELD REDUCTION FACTOR -∞y=0.55
FACING FLEXURE FACTOR -∞f=0.67
FACING PUNCHING FACTOR -∞f=0.67


5.0 GROUND NAIL WALL SPECIAL NOTES

- THE CONTRACTOR IS RESPONSIBLE FOR MAINTAINING SLOPE STABILITY ABOVE AND BELOW THE GROUND NAIL WALL DURING CONSTRUCTION.
- 5.2 THE CONTRACTORS ARE RESPONSIBLE FOR FIELD LOCATING ALL NEARBY UTILITIES. CONFLICTING UTILITIES MAY REQUIRE GROUND NAIL WALL REDESIGN, AT ENGINEER'S DISCRETION.
- 5.3 THE BOND STRENGTHS (Qd) SHOWN ON THE PLANS ARE THE MINIMUM ASSUMED FOR DESIGN.
- 5.4 GROUND NAIL LENGTHS SHOWN ON THE PLANS ARE THE MINIMUM LENGTHS REQUIRED.
- 5.5 PRIOR TO BEGINNING EXCAVATION FOR THE GROUND NAIL WALL, THE CONTRACTOR SHALL:
 - SURVEY THE LAYOUT LINE AND TOP OF WALL LINE.
 - CONFIRM THE LINES, GRADES, AND EXCAVATION LIMITS SHOWN ON THE PLANS.
 - THE CONTRACTOR SHALL MODIFY THE PLAN WALL PROFILES USING THE FIELD SURVEY INFORMATION AND SUBMIT TO THE ENGINEER FOR REVIEW AND APPROVAL.
- 5.6 CUT STONE VENEER NOTES: SEE SHEET B1 OF B24 FOR CUT STONE VENEER NOTES.

| Print Date: 11/2/201 | 6 | | (| Sheet Revisions | |
|--------------------------|---|----|-------|-----------------|-------|
| Drawing File Name: 19888 | GNW General Notes.dgn | | Date: | Comments | Init. |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted | | | | |
| Unit Information | Unit Leader Initials | | | | |
| | eh and Associates, Inc. nsulting Engineers & Scientists | 00 | | | |



| As Constructed | BOULDER CA GROUN | | | | Project No./ | Code |
|----------------|---------------------|-----|------------|------|--------------|------|
| No Revisions: | | | NOTE | | STU C070-0 | 43 |
| Revised: | Designer: | | Structure | | 19888 | |
| | Detailer: | MJW | Numbers | | | |
| Void: | Sheet Subset: | į. | Subset She | ate. | Sheet Number | 74 |




75

Sheet Number

Sheet Subset:

Subset Sheets:

Consulting Engineers & Scientists



Void:

Sheet Subset:

ubset Sheets:

Sheet Number

76

Mike Walz 11:04:06 AM W:\2015 Projects\215-177 ES Boulder Canyon TrailExtension\7. D 11/2/2016 CDDT-PDFHighQuality_V8I.pltcfg CDDT-PenTable.tbl

Consulting Engineers & Scientists

GENERAL NOTES FOR ROCK REINFORCEMENT


- 1.1 Rock Reinforcement (Number 10): Grade 150, 1 1/4" bar (ASTM A-722), bearing plate-keyhole 8"x8"x1/2" (A-36), beveled washers (ASTM A-536), hex nut (ASTM A-29). Keyhole plate shall allow for tensioning of anchors with two (2) grout tubes that will not be pinched by washer.
- 1.2 Contractor to verify quantities prior to ordering.

INSTALLATION CONSTRUCTION SEQUENCE

- The Engineer will direct locations and orientations of the Rock Reinforcement (Number 10) in the field which may range from top of brow to roadway level.
- 2.2 Rock Reinforcement (Number 10) to be grouted in two phases to allow post tensioning of anchor. Second stage shall not be grouted until test results are accepted by Engineer.
- 2.3 Flowable non-shrink grout may be necessary behind plates and is to be included in the cost of the work. Grout shall be exterior grade with a minimim 7 day compressive strength greater than 5000 psi and a 28 day strength greater than 8000 psi. Product to be submitted to the Engineer for approval.
- 2.4 All components visible above ground after post tensioning and grouting shall be painted a color as approved by the Engineer. (See General Notes)

3.0 DESIGN ASSUMPTIONS

- The design assumes the bond zone of the rock reinforcement will be in crystalline rock with an ultimate unit bond stress of 12 ksf.
- 3.2 The Design Load (DL) for the Rock Reinforcement (Number 10) will be as directed by the Engineer, typically between 30 to 60 kips. All Rock Reinforcement (Number 10) will be proof
- 3.3 A two stage grouting process is required for anchoring along the entire free length. Single stage grouting with a bond breaker will not be accepted.



Date:

Comments

ROCK REINFORCEMENT (NUMBER 10)


NOT TO SCALE

Vert. Scale: As Noted


Yeh and Associates, Inc.


Consulting Engineers & Scientists

Unit Leader Initials










FREE LENGTH CROSS SECTION A-A'

BONDED LENGTH CROSS SECTION B-B'



TYPICAL LOAD TESTING SETUP (BAR)

NOT TO SCALE

Print Date: 11/2/2016

Horiz. Scale: 1:1

Unit Information

Drawing File Name: 19888 Rock Reinforcement.dgn

SUMMARY OF DRAINAGE STRUCTURE QUANTITIES

| | _ | | | 1 _ | T | | - | | | | | O IVIIV | | _ | | AGE 3 | | | · · | | | _ | | | | | _ | | | | 1 | |
|-----------------------|-------------|-----------------|-----------|---------------------------|---------------------------------|------------------|-----------------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|-------------|---------------|----------------|---------------|------------------|------------------------|---------------------|----------------------|----------------------|----------------------|----------------------|------------------------------|-------------------------|
| | 202-00019 | 202-00035 | 202-04001 | 206-00510 | 420-00113 | 506-00212 | 506-00424 | 603-01185 | 603-01245 | 603-01305 | 603-01365 | 603-01425 | 603-01485 | 603-05018 | 603-05024 | 603-05030 | 603-05036 | 603-05042 | 603-05048 | 603-50006 | 604-00305 | 604-00310 | 604-00505 | 604-13005 | 604-16005 | 604-25005 | 604-25010 | 604-30010 | 604-30015 | PI | FIO | |
| ber / Identifier | AL OF INLET | REMOVAL OF PIPE | CULVERT | FILTER MATERIAL (CLASS A) | DRAINAGE) ASS 2) | RIPRAP (12 INCH) | SOIL RIPRAP (24 INCH) | REI | INFORC | ED CON | NCRETE | PIPE (| CIP) | REIN | FORCE | D CONC | RETE E | ND SEC | TION | LASTIC PIPE | TYPE C (5 FT) | TYPE C (10 FT) | TYPE D (5 FT) | TYPE 13 (5 FOOT) | INLET TYPE 16 (5 FOOT) | E INLET (5 FOOT) | INLET (10 FOOT) | SLAB BASE (10 FT) | SLAB BASE (15 FT) | STRUCTURE EXCAVATION | ASS 1) | REMARKS |
| Structure Num | REMOVAL | REMOV | PLUG | FILTER MATI | GEOTEXTILE (DRAINAGE) (CLASS 2) | RIPRAF | SOIL RIPR | 18 INCH | 24 INCH | 30 INCH | 36 INCH | 42 INCH | 48 INCH | 18 INCH | 24 INCH | 30 INCH | 36 INCH | 42 INCH | 48 INCH | 6" PLA | INLET T) | INLET TY | INLET T) | INLET TYP | INLET TYP | VANE GRATE INLET (5 | VANE GRATE INLET (10 | MANHOLE SL (1 | MANHOLE SL (1 | STRUCTUR | STRUCTURE BACKFILL (CLASS 1) | |
| | EA | LF | EA | CY | SY | CY | CY | LF | LF | LF | LF | LF | LF | EA | EA | EA | EA | EA | EA | LF | EA | EA | EA | EA | EA | EA | EA | EA | EA | CY | CY | |
| TRAIL | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| I106L | | | | | | | | 22 | | | | | | 1 | | | | | | | | | | 1 | | | | | | 34 | 29 | |
| I109L | | | | | | | | 25 | | | | | | | | | | | | | 1 | | | | | | | | | 23 | 20 | |
| I109R | | | | | 4 | 3 | | 62 | | | | | | 1 | | | | | | | 1 | | | | | | | | | 108 | 97 | |
| I114L | | | | | | | | 26 | | | | | | | | | | | | | 1 | | | | | | | | | 21 | 18 | |
| I115L | | | | | 4 | 3 | | 19 | | | | | | 1 | | | | | | | 1 | | | | | | | | | 25 | 19 | |
| F114RA | | 29 | | | 21 | 14 | | | | | | 32 | | | | | | 2 | | | | | | | | | | | | 75 | 49 | |
| M116L | | 2 | | | 16 | 10 | | | | | 22 | | | | | | 1 | | | | | | | | | | | 1 | | 62 | 37 | CONNECT TO EXISTING CMP |
| I119L | | | | | | | | 25 | | | | | | | | | | | | | | 1 | | | | | | | | 33 | 30 | |
| M119R | | | | | | | | | | | | | | | | | | | | | | | | | | | | 1 | | | | CONNECT TO EXISTING CMP |
| F119R | | | | | | | | | | 19 | | | | | | 1 | | | | | | | | | | | | | | 22 | 19 | |
| I124L | | 11 | | | | | | 21 | | | | | | | | | | | | 18 | 1 | | | | | | | | | 24 | 21 | |
| I124R | | | | | | | | | | | | | | | | | | | | | | | | | | | 1 | | | | | CONNECT TO EXISTING CMP |
| I129L | | | | | | | | 14 | | | | | | | | | | | | | | | | 1 | | | | | | 13 | 11 | |
| I129R | | | | | | | | 125 | | | | | | | | | | | | | | | | | | 1 | | | | 109 | 95 | |
| I128R | 1 | | | | | | | | | | | | | | | | | | | | | | | | 1 | | | | | | | CONNECT TO EXISTING CMP |
| I133R | | | | | | | | 26 | | | | | | | | | | | | | 1 | | | | | | | | | 24 | 21 | |
| I133L | | | | | | | | | 29 | | | | | | | | | | | | | | 1 | | | | | | | 59 | 53 | |
| M134L | | 34 | 1 | | | | | | | | | | 206 | | | | | | | | | | | | | | | | 1 | 973 | 831 | |
| M136L | | | | 5 | | 19 | | | | | | | 41 | | | | | | 1 | | | | | | | | | | 1 | 120 | 68 | |
| M138L | | 29 | | | | | | | 39 | | | | | | | | | | | | | | | | | | | | 1 | 110 | 102 | CONNECT TO EXISTING CMP |
| I138L | | | | 1 | | 5 | | | 28 | | | | | | 1 | | | | | | 1 | | | | | | | | | 49 | 37 | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| PED BRIDGE PROTECTION | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WEST BANK | | | | 80 | | | 640 | | | | | | | | | | | | | | | | | | | | | | | 640 | | INCLUDES TRAIL ARMORING |
| EAST BANK | | | | 20 | | | 150 | | | | | | | | | | | | | | | | | | | | | | | 150 | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| CBC 2 PROTECTION | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WEST BANK | | | | 29 | | | 233 | | | | | | | | | | | | | | | | | | | | | | | 233 | | |
| DDO IDOT TOTAL C | | 405 | _ | 405 | 4- | F.4 | 4000 | 205 | 00 | 40 | | | 0.47 | | | | _ | _ | _ | 40 | - | _ | | _ | _ | | | _ | _ | 2024 | 4550 | |
| PROJECT TOTALS | 1 | 105 | 1 | 135 | 45 | 54 | 1023 | 365 | 96 | 19 | 22 | 32 | 247 | 3 | 1 | 1 | 1 | 2 | 1 | 18 | 7 | 1 | 1 | 2 | 1 | 1 | 1 | 2 | 3 | 2904 | 1558 | |

| Print Date: 11/16/2016 | |
|------------------------------------|-----------------------|
| Drawing File Name:19888HYDR_Tab.de | gn |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| MUL ENGINEERING | \ |

| | Sheet Revisions | |
|-------|-----------------|-------|
| Date: | Comments | Init. |
| | | |
| | | |
| | | |
| | | |



| | 7 |
|-------------------|---|
| Boulder County | |

| As Constructed | | R CANYON | | | | Project No./Code | | | |
|----------------|---------------|----------|--------------|------|--------|------------------|----|--|--|
| No Revisions: | TADOL | QUANT | STU C070-043 | | | | | | |
| Revised: | Designer: | | Structure | | | 19888 | | | |
| | Detailer: | CLJ | Numbers | | | | | | |
| Void: | Sheet Subset: | DRN TABS | Subset Shee | ets: | 1 of 1 | Sheet Number | 78 | | |

- 2. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING PIPE SIZES, LENGTHS AND LOCATIONS PRIOR TO ORDERING AND DELIVERY OF THE PIPE MATERIAL TO THE SITE.
- 3. ALL CONCRETE FLARED END SECTIONS MUST BE INSTALLED WITH JOINT FASTENERS. IN ADDITION, JOINT FASTENERS SHALL BE INSTALLED ON ALL PIPE JOINTS WITHIN 15-FEET OF THE DOWNSTREAM END OF ALL CULVERTS. (INCLUDING END SECTION LENGTH, IF APPLICABLE).
- 4. ALL PIPE SHALL BE CLASS III REINFORCED CONCRETE PIPE PER CDOT STANDARD 601.04, CONFORMING TO ASTM C76, UNLESS OTHERWISE SPECIFIED.
- 5. OTHER UTILITIES MAY BE CROSSED OR OTHERWISE IMPACT STORM SEWER CONSTRUCTION. CONTRACTOR SHALL PROTECT EXISTING UTILITIES IN PLACE. UNLESS NOTED OTHERWISE, PROTECTION OF EXISTING UTILITIES, INCLUDING INCIDENTAL SHORING THAT IS NOT INCLUDED AS A PAY ITEM, WILL NOT BE MEASURED SEPARATELY, BUT SHALL BE INCLUDED IN THE COST OF THE WORK.
- 6. RUBBER GASKETS SHALL BE USED FOR ALL RCP JOINTS IN ACCORDANCE WITH ASTM C443. THE COST OF ALL JOINT GASKETS, CRADLES, COLLARS AND PIPE CONNECTIONS FOR STORM SEWER CONSTRUCTION SHALL BE INCLUDED IN THE COST OF THE PIPE.
- 7. RIPRAP IS SHOWN ON THE DRAINAGE PLAN SHEETS, STRUCTURE PROFILES AND DRAINAGE DETAILS. GEOTEXTILE (DRAINAGE) (CLASS 2) SHALL BE USED BENEATH RIPRAP UNLESS SPECIFIED OTHERWISE.
- 8. THE TOP PORTION OF INLETS AND MANHOLES SHALL FIT THE LONGITUDINAL PROFILE SLOPE AND TYPICAL SECTION REQUIREMENTS. THE CONTRACTOR SHALL CROSS REFERENCE THIS INFORMATION PRIOR TO CONSTRUCTING INLETS AND MANHOLES TO FINAL GRADE.
- 9. STATION/OFFSET INFORMATION FOR MANHOLES (SLAB BASE AND BOX BASE) IS TO THE CENTER OF THE STRUCTURE.
- 10. TYPE C, D, & VANE GRATE INLETS AND MANHOLES SHALL BE CONSTRUCTED IN ACCORDANCE WITH CDOT M&S STANDARDS, JULY 2012 UNLESS NOTED OTHERWISE.
- 11. TYPE 13 COMBINATION INLETS SHALL BE CONSTRUCTED IN ACCORDANCE WITH BOULDER COUNTY STORM DRAINAGE CRITERIA STANDARD DETAILS, NOVEMBER 2013 UNLESS NOTED OTHERWISE. ALL TYPE 13 COMBINATION INLETS SHALL BE PAID FOR AS CDOT PAY ITEM INLET TYPE 16.
- 12. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DEWATERING AND DIVERSION INCLUDING, BUT NOT LIMITED TO, LIVE STREAM FLOW AND GROUNDWATER AND OBTAINING THE APPLICABLE DEWATERING PERMIT FOR CONSTRUCTION AT THE SITE. THIS WILL NOT BE PAID FOR SEPARATELY, BUT SHALL BE INCLUDED IN THE WORK. THE CONTRACTOR SHALL COMPLY WITH ALL PERMIT REQUIREMENTS.
- 13. DRAINAGE WORK SHALL BE PER BOULDER COUNTY STORM DRAINAGE CRITERIA STANDARD DETAILS, 2014 EDITION, UNLESS OTHERWISE MODIFIED BY THE PROJECT SPECIFICATIONS. PAY ITEM NAMES AND UNITS OF MEASUREMENT SHALL BE PER CDOT STANDARDS UNLESS NOTED OTHERWISE.


DRAINAGE LEGEND

| | CONSTRUCTION LIMITS |
|--------------------------|---------------------------------|
| | EXISTING FENCE |
| - — | EXISTING MAJOR CONTOURS |
| | EXISTING MINOR CONTOURS |
| XXXX | FINISHED MAJOR CONTOURS |
| | FINISHED MINOR CONTOURS |
| — — SA- — — | EXISTING SANITARY SEWER |
| $ \ \ W \ \ \ W \ \ \ W$ | EXISTING WATER LINE |
| —— G ——— HP —— | EXISTING HIGH PRESSURE GAS LINE |
| G G | EXISTING GAS LINE |
| EE | EXISTING ELECTRIC LINE |
| —— OH ——— E —— | EXISTING OVERHEAD ELECTRIC LIN |
| — ST — — — | EXISTING STORM SEWER |
| - T $-$ T $-$ T $ -$ | EXISTING TELEPHONE LINE |
| TVTV | EXISTING TELEVISION LINE |
| - — — FO — — — FO — — | EXISTING FIBER OPTIC LINE |
| — | EXISTING TRAFFIC ITS LINE |
| | EXISTING RIGHT OF WAY |
| < | EXISTING DITCH |
| | EXISTING PROPERTY LINE |
| \rightarrow | EXISTING TREE |
| | UTILITY EASEMENT |
| | TEMPORARY EASEMENT |
| | PERMANENT EASEMENT |
| | RIGHT OF WAY |
| | PROPOSED LIMIT OF CUT |
| | PROPOSED LIMIT OF FILL |
| | PROPOSED SANITARY SEWER |
| —— w —— w —— | PROPOSED WATER LINE |
| | PROPOSED DRAINAGE SWALE |
| | PROPOSED STORM SEWER |
| | PROPOSED RIPRAP |

DRAINAGE LEGEND, CONTINUED

STRUCTURE

| IDENTIFICATION | STRUCTURE TYPE |
|----------------|------------------------------------|
| С | INLET TYPE C |
| CH | CHASE |
| D | INLET TYPE D |
| EX | EXISTING STRUCTURE (TYPE AS NOTED) |
| FES | FLARED END SECTION |
| MB | MANHOLE BOX BASE |
| MS | MANHOLE SLAB BASE (SPECIAL) |
| os | OUTLET STRUCTURE |
| PC | PIPE CONNECTION |
| PE | PIPE END |
| RX | INLET TYPE R (X LENGTH) |
| VGS | INLET VANE GRATE (SINGLE) |
| VGD | INLET VANE GRATE (DOUBLE) |
| X | MANHOLE SLAB BASE (X DIAMETER) |
| 13S | INLET TYPE 13 (SINGLE) |
| 13D | INLET TYPE 13 (DOUBLE) |
| 13T | INLET TYPE 13 (TRIPLE) |
| 16S | INLET TYPE 16 (SINGLE) |
| 16D | INLET TYPE 16 (DOUBLE) |
| 16T | INLET TYPE 16 (TRIPLE) |
| | |




Print Date: 11/16/2016

Drawing File Name: 19888HYDR_Gen Notes.dgn

Horiz. Scale: 1:1 Vert. Scale: As Noted


Unit Information Unit Leader Initials









| As Constructed | | TRAIL EXTENSION | Project No./Code |
|----------------|-------------------------|-----------------------|------------------|
| No Revisions: | DRAINAGE GENERAI | NOTES & LEGEND | STU C070-043 |
| Revised: | | Structure | 19888 |
| | Detailer: CLJ | Numbers | |
| Void: | Sheet Subset: DRN NOTES | Subset Sheets: 1 of 1 | Sheet Number 79 |





NOT TO SCALE



AIL

1. TOEWALL SHALL BE USED FOR ALL FLARED END SECTIONS 36" DR LARGER.

2. BACKFILL BOTH SIDES OF WALL EVENLY (WITHIN 1'-0" OF EACH OTHER).

3. JOINT FASTENERS SHALL BE INSTALLED ON ALL FLARED END SECTIONS.

4. TOEWALL, STRUCTURE EXCAVATION AND BACKFILL AND ALL ASSOCIATED WORK SHALL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE COST OF THE END SECTION.

| TOEWALL DETA |
|--------------|
| NOT TO SCALE |

| Print Date: 11/16/2016 | | |
|-------------------------------------|-----------------------|---|
| Drawing File Name:19888HYDR_Details | 01.dgn | |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted | |
| Unit Information | Unit Leader Initials | c |
| /// MULI | LER | Ċ |

ENGINEERING COMPANY


| | Sheet Revisions | | | | | | | |
|----------------|-----------------|-------|--|--|--|--|--|--|
| | Date: | Init. | | | | | | |
| $\overline{0}$ | | | | | | | | |
| 0 | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |





NOTE:

| As Constructed | BOULDER CANYON TRAIL EXTENSION DRAINAGE DETAILS | | | | Project No./ | Code | |
|----------------|--|----------|------------|-------|--------------|--------------|----|
| No Revisions: | | | | | STU C070-04 | 43 | |
| Revised: | Designer: MMM Structure | | | 19888 | | | |
| | Detailer: | CLJ | Numbers | | | | |
| Void: | Sheet Subset:DRI | N DETAIL | Subset She | ets: | 1 of 1 | Sheet Number | 80 |





| Print Date: 11/16/2016 | | | | | |
|---|----------------------|--|--|--|--|
| Drawing File Name: 19888HYDR_Profile 01.dgn | | | | | |
| Horiz. Scale: 1:40 | Vert. Scale: 1:10 | | | | |
| Unit Information | Unit Leader Initials | | | | |
| MUL ENGINEERING | \ | | | | |


| | | Sheet Revisions | |
|---|-------|-----------------|-------|
| | Date: | Comments | Init. |
| 0 | | | |
| 0 | | | |
| 0 | | | |
| | | | |




| | ١ |
|-------------------|---|
| Boulder County | F |
| | , |

| As Constructed | BOULDER CANYON TRAIL EXTENSION STRUCTURE PROFILES | | | | Project No./ | Code | |
|----------------|---|----------|-------------|------|--------------|--------------|----|
| No Revisions: | | | | | STU C070-04 | 43 | |
| Revised: | Designer: | | Structure | | | 19888 | |
| | Detailer: | REW | Numbers | | | | |
| Void: | Sheet Subset: | DRAINAGE | Subset Shee | ets: | 1 of 7 | Sheet Number | 81 |

<u>I109L TO F110R</u>



<u>1114L TO F115R</u>






| Print Date: 11/16 | /2016 |
|----------------------|----------------------------|
| Drawing File Name: 1 | 9888HYDR_Profile 02.dgn |
| Horiz. Scale: 1:40 | Vert. Scale: 1:10 |
| Unit Information | Unit Leader Initials |
| | MULLER ENGINEERING COMPANY |


| | | Sheet Revisions | | | | | | | | |
|---|-------|-----------------|-------|--|--|--|--|--|--|--|
| | Date: | Comments | Init. | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| 0 | | | | | | | | | | |
| 0 | | | | | | | | | | |



| As Constructed | BOULDER CANYON TRAIL EXTENSION | | | | Project No./ | Code | |
|----------------|--------------------------------|--------------------|-------------|------|--------------|--------------|----|
| No Revisions: | STI | STRUCTURE PROFILES | | | | STU C070-04 | 43 |
| Revised: | Designer: CHH Structure | | 19888 | | | | |
| | Detailer: | REW | Numbers | | | | |
| Void: | Sheet Subset: | DRAINAGE | Subset Shee | ets: | 2 of 7 | Sheet Number | 82 |



M116L TO F116R






| Print Date: 11/16/2016 | | | | | |
|--|----------------------|--|--|--|--|
| Drawing File Name:19888HYDR_Profile 03.dgn | | | | | |
| Horiz. Scale: 1:40 | Vert. Scale: 1:10 | | | | |
| Unit Information | Unit Leader Initials | | | | |
| MUL ENGINEERING | ` | | | | |

| | | Sheet Revisions | |
|---|-------|-----------------|-------|
| | Date: | Comments | Init. |
| 0 | | | |
| 0 | | | |
| 0 | | | |
| 0 | | | |




| As Constructed | BOULDER CANYON TRAIL EXTENSION | | | | | Project No./ | Code |
|----------------|--------------------------------|--------------------|------------|------|--------|--------------|------|
| No Revisions: | STI | STRUCTURE PROFILES | | | | STU C070-04 | 43 |
| Revised: | Designer: CHH Structure | | 19888 | | | | |
| | Detailer: | REW | Numbers | | | | |
| Void: | Sheet Subset: | DRAINAGE | Subset She | ets: | 3 of 7 | Sheet Number | 83 |

<u>I119L TO M119R</u>



F119R TO M119R






| Print Date: 11/16/2016 | |
|--------------------------------------|----------------------|
| Drawing File Name: 19888HYDR_Profile | e 04.dgn |
| Horiz. Scale: 1:40 | Vert. Scale: 1:10 |
| Unit Information | Unit Leader Initials |
| MUL ENGINEERING | \ |

| | Sheet Revisions | |
|-------|-----------------|-------|
| Date: | Comments | Init. |
| | | |
| | | |
| | | |
| | | |




| As Constructed | BOULDER CANYON TRAIL EXTENSION | | | | | Project No./Co | | |
|----------------|--------------------------------|--------------------|-----------------------|----------|--------|----------------|--------------|--|
| No Revisions: | ST | STRUCTURE PROFILES | | | | | STU C070-043 | |
| Revised: | Designer: | | Structure | | | 19888 | | |
| Void: | Detailer: Sheet Subset: | | Numbers Subset She | <u> </u> | 4 of 7 | Sheet Number | 8 | |

I124L TO I124R



<u>I129L TO I128R</u>

*NOTE: INLET TYPE 16 (5 FOOT) TO BE CONSTRUCTED PER BOULDER COUNTY STANDARD DETAIL SD-4, COMBINATION INLET TYPE 13






| Print Date: 11/16/2016 | |
|--------------------------------------|----------------------|
| Drawing File Name: 19888HYDR_Profile | 05.dgn |
| Horiz. Scale: 1:40 | Vert. Scale: 1:10 |
| Unit Information | Unit Leader Initials |
| MUL ENGINEERING | \ |

| | | Sheet Revisions | |
|---|-------|-----------------|-------|
| | Date: | Comments | Init. |
| 0 | | | |
| 0 | | | |
| 0 | | | |
| | | | |



| As Constructed | BOULDER CANYON TRAIL EXTENSION | | | Project No./Code | | | |
|----------------|--------------------------------|----------|------------|------------------|--------|--------------|----|
| No Revisions: | ST | RUCTURE | PROF | ILES | | STU C070-04 | 43 |
| Revised: | Designer: CHH Structure | | 19888 | | | | |
| | Detailer: | RFW | Numbers | | | | |
| Void: | Sheet Subset: | DRAINAGE | Subset She | ets: | 5 of 7 | Sheet Number | 85 |

I133R TO F136R






| Print Date: 11/16/2016 | |
|--------------------------------------|----------------------|
| Drawing File Name: 19888HYDR_Profile | e 06.dgn |
| Horiz. Scale: 1:40 | Vert. Scale: 1:10 |
| Unit Information | Unit Leader Initials |
| MUL ENGINEERING | |

Sheet Revisions


Date: Comments Init.



| | | | | | | - | |
|----------------|--------------------------------|----------|------------|------|------------------|--------------|----|
| As Constructed | BOULDER CANYON TRAIL EXTENSION | | | | Project No./Code | | |
| No Revisions: | STRUCTURE PROFILES | | | | STU C070-043 | | |
| Revised: | Designer: | | Structure | | 19888 | | |
| | Detailer: | CLJ | Numbers | | | | |
| Void: | Sheet Subset: | DRAINAGE | Subset She | ets: | 6 of 7 | Sheet Number | 86 |



M138L TO F138R





| Print Date: 11/16/2016 | |
|--------------------------------------|----------------------|
| Drawing File Name: 19888HYDR_Profile | e 07.dgn |
| Horiz. Scale: 1:40 | Vert. Scale: 1:10 |
| Unit Information | Unit Leader Initials |
| MUL ENGINEERING | \ |

| | | Sheet Revisions | |
|---|-------|-----------------|-------|
| | Date: | Comments | Init. |
| 0 | | | |
| 0 | | | |
| 0 | | | |
| | | | |



| As Constructed | BOULDER CANYON TRAIL EXTENSION | | | Project No./Code | | | |
|----------------|--------------------------------------|--------------------|-----------|------------------|--------------|--------------|----|
| No Revisions: | STI | STRUCTURE PROFILES | | | | STU C070-043 | |
| Revised: | Designer: | | Structure | | 19888 | | |
| | Detailer: | ₽E.W | Numbers | | | | |
| L | Detailer. | 1/ L W | | | | l <u>.</u> | ~- |
| Void: | Sheet Subset: DRAINAGE Subset Sheets | | ets: | 7 of 7 | Sheet Number | 87 | |

The Contractor shall comply with all CDOT contractual requirements and all requirements associated with the CDPS-SCP on this project. The SWMP Administrator shall update to reflect current project site conditions.

- A. PROJECT SITE LOCATION: The project site is along SH 119 from approximately Chapman Drive to just west of Fourmile Canyon Drive. Specifically, the project area is in Sections 27 and 34, Township 1 North, Range 71 West of the 6th Principal Meridian in Boulder County, Colorado. The UTM coordinates of the approximate center of the project area are 472064mE, 4429043mN, Zone 13. The latitude/longitude of the project area is 0.011118°N and 105.327324°W.
- B. <u>PROJECT SITE DESCRIPTION</u>: The proposed project consists of an extension of the Boulder Canyon Trail system from Fourmile Canyon Drive to Chapman Drive along the SH 119 corridor. The project includes construction of two concrete box culvert underpasses and a pedestrian bridge over Boulder Creek just upstream of the Chapman Drive Bridge. The trail will be crusher fines or concrete. Storm drains, cross culverts and pipe extensions will be installed as needed to maintain existing drainage patterns.
- C. PROPOSED SEQUENCING FOR MAJOR CONSTRUCTION ACTIVITIES: Initial erosion control measures such as perimeter control, inlet protection, tree/landscape protection and sediment control will be installed prior to the start of clearing and grubbing. As construction of the trail, underpasses, pedestrian bridge, storm drain inlets and culverts are completed the appropriate erosion control measures will be installed. At substantial completion of project segments permanent stabilization measures will be installed. This includes permanent seeding, mulching and soil retention blanket.
- D. ACRES OF DISTURBANCE:
 - 1. Total area of construction site (LOC (PERMITTED AREA)): 7.87 acres
 - 2. Total area of proposed disturbance (LDA): 3.75 acres
 - 3. Total area of seeding: 1.87 acres
 - 4. Total area of impervious surface: 2.71 acres
 - 5. Total area of NEW impervious surface: 0.63 acres
- E. <u>EXISTING SOIL DATA</u>: Per NRCS soil mapping the project area includes Fern Cliff-Allens Oark-Rock outcrop complex which has stony sandy loam to a depth of 20 inches below the soil surface and Juget-Rock outcrop complex which has variable soil profiles with very gravelly sandy loam, very gravelly loamy sand and very gravelly sand to a depth of 11 inches below the soil surface. Soils near the wetland areas were found to be silty loam, sandy loam, sandy clay or clay in the upper 14 inches.
- F. EXISTING VEGETATION, INCLUDING PERCENT COVER:

| SWMP Administrator for Design or the SWMP Administrator will conduct the Vegetation Transects as | During design the SWMP Administrator for Design in consultation with the Engineer will determine if the |
|--|---|
| | SWMP Administrator for Design or the SWMP Administrator will conduct the Vegetation Transects as |
| outlined in Chapter 4.11.2 of the Erosion Control and Stormwater Quality Guide. | outlined in Chapter 4.11.2 of the Erosion Control and Stormwater Quality Guide. |

| Pre-Construction Date of survey: | %Density: | | | | |
|---|-------------|--|--|--|--|
| Description of existing vegetation: | | | | | |
| Map or table showing transect locations in SWMP notebo | ook tab 17: | | | | |
| Post-Construction Date of survey: | %Density: | | | | |
| Description of existing vegetation: Date of CDPS-SCP Closure: | | | | | |
| Map or table showing transect locations in SWMP notebo | ook tab 17: | | | | |

- G. <u>POTENTIAL POLLUTANTS SOURCES</u>: See First Construction Activities under Potential Pollutant Sources. The SWMP Administrator shall prepare a list of all potential pollutants and their locations in accordance with subsection 107.25.
- H. RECEIVING WATER:
 - 1. Outfall locations: There are currently 5 outfalls within the project corridor ranging in size from 24" to 36" and discharging into Boulder Creek.
 - 2. Names of receiving water(s) on site: Boulder Creek
- 3. Ultimate receiving water: South Platte River
- 4. Horizontal distance nearest water of the state is from project: 0 feet

I. NON-STORMWATER DISCHARGES:

ALLOWABLE

- 1. Groundwater and stormwater dewatering: Discharges to the ground of water from construction dewatering activities may be authorized provided that:
 - a. the source is groundwater and/or groundwater combined with stormwater that does not contain pollutants;
 - b. the source and BMPs/Control Measures are identified in the SWMP;
 - c. discharges do not leave the site as surface runoff or to surface waters;
 - d. the Contractor shall protect all work areas and facilities from water at all times. Areas and facilities subject to flooding, regardless of the source of water, shall be promptly dewatered and restored at no cost to the owner. This shall include removal of any debris caused by flooding. Any dewatering shall be done in accordance with Subsection 107.25.

CONTAMINATED

If discharges do not meet the above criteria, a separate CDPS permit shall be obtained by the Contractor from the CDPHE. See standard special provision 250 Hazardous Waste and Contaminated Water.

2. SITE MAP COMPONENTS:

Pre-construction - See SWMP Erosion Control Plans unless otherwise directed.

- A. PROJECT CONSTRUCTION POTENTIAL SITE BOUNDARIES
- B. ALL AREAS OF GROUND SURFACE DISTURBANCE
- C. AREAS OF CUT AND FILL
- D. LOCATION OF ALL STRUCTURAL BMPs/CONTROL MEASURES IDENTIFIED IN THE SWMP
- E. LOCATION OF NON-STRUCTURAL BMPs/CONTROL MEASURES AS APPLICABLE IN THE SWMP
- F. SPRINGS, STREAMS, WETLANDS AND OTHER SURFACE WATER
- G. PROTECTION OF TREES, SHRUBS, CULTURAL RESOURCES AND MATURE VEGETATION Refer to plan sheets
- H. AREAS USED FOR STORING AND STOCKPILING OF MATERIALS, STAGING AREAS (field trailer, fueling, etc.) and BATCH PLANTS

3. SWMP ADMINSTRATORS:

A. SWMP ADMINISTRATOR FOR DESIGN:

| Name/Title | Contact Information |
|------------------------|---|
| Michelle M. Morgan, PE | Muller Engineering; 303-988-4939; mmorgan@mullereng.com |

B. SWMP ADMINISTRATOR FOR CONSTRUCTION: (As defined in Subsection 208) The Contractor shall designate a SWMP Administrator for Construction upon ownership of the SWMP. The SWMP Administrator shall become the owner/operator and assume responsibility for all design changes to the SWMP implementation and maintenance in accordance to 208.03. The SWMP Administrator shall be responsible for implementing, maintaining and revising SWMP, including the title and contact information. The activities and responsibilities of the SWMP administrator shall address all aspects of the projects SWMP. (Update the information below for each new SWMP Administrator) (Copy of TECS Certification must also be included in the SWMP Notebook.)

| Name/Title | Contact Information | Certification # | Start Date | Engineer Approval |
|------------|---------------------|-----------------|------------|-------------------|
| | | | | |

Print Date: 11/16/2016


Drawing File Name: 19888SWMP_SWMP Notes.dgn

Horiz. Scale: 1:1

Unit Information

Unit Leader Initials

WULLER







| As Constructed | BOULDER CANYON TRAIL EXTENSION STORMWATER MANAGEMENT PLANS | | | | Project No./Code | | |
|----------------|--|------|--------------|------|------------------|--------------|----|
| No Revisions: | | | STU C070-043 | | | | |
| Revised: | Designer: | MMM | Structure | | | 19888 | |
| | Detailer: | REW | Numbers | | | | |
| Void: | Sheet Subset: | SWMP | Subset She | ets: | 1 of 7 | Sheet Number | 88 |

C. <u>EROSION CONTROL INSPECTOR</u>: (As defined in Subsection 208) The Contractor may designate an Erosion Control Inspector. The Erosion Control Inspector shall complete duties in accordance with subsection 208.03 (c) (Copy of TECS Certification must also be included in the SWMP Notebook.)

| Name/Title | Contact Information | Certification # | Start Date | Engineer Approval |
|------------|---------------------|-----------------|------------|-------------------|
| | | | | |
| | | | | |
| | | | | |

4. STORMWATER MANAGEMENT CONTROLS FIRST CONSTRUCTION ACTIVITIES

THE CONTRACTOR SHALL PERFORM THE FOLLOWING:

A. POTENTIAL POLLUTANT SOURCES

Evaluate, identify, locate and describe all potential sources of pollutants at the site in accordance with Subsection 107.25, CDPS-SCP and place in the SWMP notebook. All BMPs/Control Measures related to potential pollutants shall be shown on the SWMP site map by the Contractor's SWMP Administrator.

B. OFFSITE DRAINAGE (RUN ON WATER)

1. Describe and record BMPs/Control Measures on the SWMP site map that have been implemented to address off site run-on water in accordance with subsection 208.03.

C. VEHICLE TRACKING PAD/VEHICLE TRACKING CONTROL

1. BMPs/Control Measures shall be implemented in accordance with subsection 208.04.

D. PERIMETER CONTROL

- 1. Perimeter control shall be established as the first item on the SWMP to prevent the potential for pollutants leaving the construction site boundaries, entering the stormwater drainage system, or discharging to state waters.
- 2. Perimeter control may consist of vegetation buffers, berms, silt fence, erosion logs, existing landforms, or other BMPs/Control Measures as approved.
- 3. Perimeter control shall be in accordance with subsection 208.04.

5. DURING CONSTRUCTION

RESPONSIBILITIES OF THE SWMP ADMINISTRATOR DURING CONSTRUCTION

The SWMP should be considered a "living document" that is continuously reviewed and modified.

During construction, the following items shall be added, updated, or amended as needed by the SWMP Administrator in accordance with Section 208.

During construction, indicate how items that have not been addressed during design are being handled in construction. If items are covered in the template or other sections of the SWMP notebook indicate below what section the discussion takes place.

- A. STOCKPILE MANAGEMENT: Shall be done in accordance with subsections 107.25 and 208.07.
- B. CONCRETE WASHOUT: Concrete wash out water or waste from field laboratories and paving equipment shall be contained in accordance with subsection 208.05.
- C. SAW CUTTING: Shall be done in accordance with subsections 107.25, 208.04, 208.05.
- D. STREET CLEANING: Shall be done in accordance with subsection 208.04.

6. INSPECTIONS

A. Inspections shall be in accordance with subsection 208.03 (c).

7. BMP/CONTROL MEASURE MAINTENANCE

A. Maintenance shall be in accordance with subsection 208.04 (f).

8. RECORD KEEPING

A. Records shall be kept in accordance with subsection 208.03 (d).

9. INTERIM AND FINAL STABILIZATON

A. SEEDING PLAN

Soil preparation, soil conditioning or topsoil, seeding (native), mulching (weed free) and mulch tackifier will be required for an estimated 1.87 acres of disturbed area within the right-of-way limits which are not surfaced. The following types and rates shall be used:

| COMMON NAME | BOTANICAL NAME | LBS. PLS PER ACRE |
|-------------|----------------|----------------------|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| TOTAL | | |

- B. SEEDING APPLICATION: Drill seed 0.25 inch to 0.5 inch into the soil. In small areas not accessible to a drill, hand broadcast or hydroseed at double the rate and rake 0.25 inch to 0.5 inch into the soil per subsection 212.
- C. MULCHING APPLICATION: Apply a minimum of 2 tons of certified weed free hay or 2 1/2 tons of certified weed free straw per acre and in accordance with Section 213, and mechanically crimp it into the soil in combination with an organic mulch tackifier.
- 1. Prior to winter shutdown or the summer seeding window closure: Uncompleted slopes shall be mulched with 2 tons of mulching (weed free) per acre, mechanically crimped into the topsoil in combination with an organic mulch tackifier per subsections 208 and 213.

D. SPECIAL REQUIREMENTS:

- 1. Due to high failure rates, hydroseeding will not be allowed for permanent stabilization.
- E. SOIL CONDITIONING AND FERTILIZER REQUIREMENTS: Minimum requirements for all disturbances to receive seeding (native).

| Soil conditioner paid for as Item 212- Soil Conditioning (Acre) | | | | | |
|---|----------------------|----------------------------------|--|--|--|
| Biological nutrient organic based fertilizer (lbs/acre)* | Humate (lbs/acre) | Compost (cy/acre) All areas <2:1 | | | |
| 300 | 200 | 65 | | | |

^{*}Biological nutrient shall not exceed 8-8-8 (N-P-K).

Humate based material shall be in accordance to Standard Special Provision 212 and compost shall be in accordance to Standard Special Provision 212.

- F. SOIL RETENTION COVERING: On slopes and ditches requiring a blanket or turf reinforcement mat (trm), the blanket/trm shall be placed in lieu of mulch and mulch tackifier and placed after seeding (native). See SWMP site map for blanket/trm locations.
- G. RESEEDING OPERATIONS/CORRECTIVE STABILIZATION

Prior to final acceptance

- 1. All seeded areas shall be reviewed during the 14 day inspections by the SWMP Administrator and/or Erosion Control Inspector for bare soils caused by surface or wind erosion. Bare areas caused by surface or gully erosion, blown away mulch, etc. shall be re-graded, seeded, and have the designated mulching applied as necessary, at no additional cost to the project.
- 2. The Contractor shall maintain seeding/mulch/tackifier/blanket/TRM, mow to control weeds or apply herbicide to control weeds in the seeded areas until Partial Acceptance of the stormwater construction

| Print Date: 11/16/2016 | | Г |
|-----------------------------------|-----------------------|---|
| Drawing File Name: 19888SWMP_SWMP | Notes.dgn | ı |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted | ı |
| Unit Information | Unit Leader Initials | ı |
| MMULI | LER | |

| Sheet Revisions | | | | | | |
|-----------------|-------|--|--|--|--|--|
| Date: | Init. | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Ch - - L D - - : - : - : -





| As Constructed | BOULDER CANYON TRAIL EXTENSION STORMWATER MANAGEMENT PLANS | | | · | Project No./Co | | |
|----------------|--|------|--------------|------|----------------|--------------|----|
| No Revisions: | | | STU C070-043 | | | | |
| Revised: | Designer: | MMM | Structure | | | 19888 | |
| | Detailer: | REW | Numbers | | | 1000 | |
| Void: | Sheet Subset: | SWMP | Subset She | ets: | 2 of 7 | Sheet Number | 89 |

10. PRIOR TO PROJECT FINAL ACCEPTANCE

- A. Partial Acceptance shall be in accordance with subsection 107.25 (d), 208.10 and 214.04 at the Partial Acceptance of the project, it shall be determined by the SWMP Administrator and the Engineer which temporary BMPs/Control Measures shall remain until 70% revegetation is established or which shall be removed.
- B. At the end of the project, all ditch checks shall either consist of temporary erosion logs (or equivalent) or permanent riprap.
- C. All storm drains shall be cleaned prior to the Final Acceptance of the project. Work shall be included in 202 Clean Culvert.

11. NARRATIVES:

A. ADDITIONAL BMPS/CONTROL MEASURES AND NARRATIVES:

BMP/Control Measure details and narratives not covered by the SWMP or Standard Plan M-208, M-216 shall be added to the SWMP notebook by the SWMP Administrator

BMP Matrix:

- M-Standards have been included along with standard BMP narratives. If a Non-Standard BMP will be
 used or the standard narrative does not apply, the SWMP Administrator shall write a Non-Standard BMP
 narrative, place an "X" in the column and complete a Non-Standard BMP Specification and Narrative for
 the SWMP notebook.
- 2. The SWMP Administrator shall place an "X" in the column In Use on Site when the BMP/Control Measure has been installed.
- 3. Place an "X" in the column BMP/Control Measure to be located by SWMP Administrator if the SWMP Administrator shall locate the BMP/Control Measure during construction. These BMP/Control Measures are not currently located on SWMP Plans but are anticipated to be used during construction (i.e. Vehicle Tracking Pad, Batch Plants, etc.). The SWMP Administrator shall locate these prior to or during construction and reflect on SWMP Map.
- 4. Place an "X" in the column Installation BMP/Control Measure Pre-Construction if the BMP/Control Measure is to be installed prior to construction activity.

| Print Date: 11/16/2016 | |
|-----------------------------------|-----------------------|
| Drawing File Name: 19888SWMP_SWMP | Notes.dgn |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| MUL ENGINEERING | , |

| | Sheet Revisions | | | | | | | | |
|---|-----------------|----------|-------|--|--|--|--|--|--|
| | Date: | Comments | Init. | | | | | | |
| 0 | | | | | | | | | |
| 0 | | | | | | | | | |
| 0 | | | | | | | | | |
| 0 | | | | | | | | | |





| As Constructed | BOULDE | R CANYON STORM | | | | Project No./ | Code |
|----------------|---------------|-------------------|----------------|--|--------|--------------|------|
| No Revisions: | MA | NAGEME | | | | STU C070-0 | 43 |
| Revised: | Designer: | MMM | Structure | | | 19888 | |
| | Detailer: | REW | / Numbers | | | | |
| Void: | Sheet Subset: | SWMP | Subset Sheets: | | 3 of 7 | Sheet Number | 90 |

| | | | SITE | SURE BY ATOR | J SURE ION | ВМР/СС | NTROL ME | ASURE |
|---|--|-------|------|--|---|---|---------------------------------------|----------------------------|
| APPLICATION, BMP/CONTROL MEASURE | NARRATIVE | | | BMP/CONTROL MEASURE TO BE LOCATED BY SWMP ADMINSTRATOR | INSTALLATION BMP/CONTROL MEASURE PRE-CONSTRUCTION | FIRST/INITIAL CONSTRUCTION ACTIVITIES | INTERIM CONSTRUCTION ACTIVITIES | PERMANENT STABILIZATION |
| PROTECTION OF EXISTING WETLANDS Fence (plastic) and erosion logs | Fence (plastic) shall be placed in combination with erosion logs to prevent encroachment of construction traffic and sediment into state waters prior to start of construction disturbances. Fence (plastic) shall be placed adjacent to the wetlands; erosion logs shall be placed between the plastic fence and disturbance area. Logs shall be placed to direct flows away from or filter water running into wetlands from disturbance areas. | | | | | x | х | |
| PROTECTION OF EXISTING TREES/LANDSCAPING Fence (plastic) | Fence (plastic) shall be used in areas indicated in the plans to prevent encroachment of construction traffic and sediment for the protection of mature trees and/or existing landscaping prior to start of construction disturbances. | | | х | х | × | х | |
| CHECK DAM/DITCH CHECK Erosion log, silt berm, silt dike, rock check dam | Placed in ditches immediately upon completion of ditch grading to reduce velocity of runoff in ditch. For existing ditches, place prior to start of construction disturbances. | M-208 | | | | Х | х | х |
| TYPE R AND TYPE 16 INLET PROTECTION Storm drain inlet protection (Type 1,2 and 3) | Placed prior to construction disturbances as detailed in M-208-1, to protect existing inlets or immediately upon completion of new inlets to prevent sediment from entering the inlet throughout construction. | M-208 | | | | Х | х | х |
| CULVERT INLET/OUTLET PROTECTION Erosion logs, aggregate bags | aced at mouth of culvert inlets and over top of culvert at inlet and outlet where disturbance may be occurring lijacent to pipe to prevent sediment laden water from entering pipe or drainage. Place prior to start of instruction disturbances. | | | | x | × | х | x |
| TYPE C, TYPE D AND TYPE 13 PROTECTION Erosion logs, aggregate bags, erosion bales | Placed around inlet grate or slope and ditch paving to prevent sediment from entering inlet. Place prior to start of construction disturbances. | M-208 | | | х | х | х | х |
| STOCKPILE PROTECTION Temporary berm, erosion logs, aggregate bags* | Placed within specified distance, in accordance with subsection 208.06, from toe to contain sediment around stockpile. *Aggregate bags are easily moved and replaced for access during the work day. Place prior to start of stock pile, increase control as stock pile increases size. | M-208 | | x | | | х | |
| TOE OF FILL PROTECTION Erosion logs, temporary berm, silt fence, topsoil windrow* | Place prior to slope/embankment work to capture sediment and protect and delineate undisturbed areas. *Can be used to stockpile topsoil for salvage. | M-208 | | | | х | х | |
| PERIMETER CONTROL Erosion logs, silt fence, temporary berm, topsoil windrow* | Placed prior to construction commencing to address potential run-on water from off site, and to divert around disturbed area. *Can be used to stockpile topsoil for salvage. | M-208 | | | х | x | х | |
| SEDIMENT CONTROL/SLOPE CONTROL Silt fence, erosion logs | Placed on the contour of a slope to contain and slow down construction runoff. Place prior to start of construction disturbances. | M-208 | | | х | Х | х | |
| TEMPORARY SEDIMENT TRAP (SWMP Administrator shall add locations to SWMP site maps) | Used to capture sediment laden runoff from disturbed areas < 5 acres during construction. Place prior to start of construction disturbances. | M-208 | | | | Х | х | |
| PERMANENT SEDIMENT BASIN Extended detention basin or other Permanent Water Quality features | Constructed early in project, prior to storm sewer/ditches to capture storm flow as a temporary sediment trap. Outlet structure shall be modified for contaminants of construction runoff a non-standard detail is needed. | | | | | х | х | |

| Print Date: 11/16/2016 | | Γ |
|-----------------------------------|-----------------------|---|
| Drawing File Name: 19888SWMP_SWMP | Notes.dgn | |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted | |
| Unit Information | Unit Leader Initials | l |
| /// MULI | LER | |
| ENGINEERING | COMPANY | |

| | | Sheet Revisions | | | | | | | | | |
|---|-------|-----------------|-------|--|--|--|--|--|--|--|--|
| | Date: | Comments | Init. | | | | | | | | |
| 0 | | | | | | | | | | | |
| 0 | | | | | | | | | | | |
| 0 | | | | | | | | | | | |
| 0 | | | | | | | | | | | |





| As Constructed | BOULDER CANYON TRAIL EXTEN | | | | ructed BOULDER CANYON TRAIL EXTENSION STOPMWATER | | | | | Project No./Code | | | | |
|----------------|----------------------------|------|-------------|-----|---|--------------|----|--|--|------------------|--|--|--|--|
| No Revisions: | | | NT PL | ANS | | STU C070-0 | 43 | | | | | | | |
| Revised: | Designer: | MMM | Structure | | | 19888 | | | | | | | | |
| | Detailer: | REW | Numbers | | | | | | | | | | | |
| Void: | Sheet Subset: | SWMP | Subset Shee | ts: | 4 of 7 | Sheet Number | 91 | | | | | | | |

| | APPLICATION, BMP/CONTROL MEASURE NARRATIVE | | IN USE ON SITE | MEASURE TED BY STRATOR | ION IEASURE CTION | BMP/C | ONTROL MEASURE PHASING | | |
|--|--|-------|----------------|--|--|---|---------------------------------------|----------------------------|--|
| | | | | BMP/CONTROL MEASURI TO BE LOCATED BY SWMP ADMINSTRATOR | INSTALLATION BMP/CONTROL MEA: PRE-CONSTRUCTI | FIRST/INITIAL CONSTRUCTION ACTIVITIES | INTERIM CONSTRUCTION ACTIVITIES | PERMANENT STABILIZATION | |
| EMBANKMENT PROTECTION OR TEMPORARY SLOPE DRAIN | Placed as a conduit or chute to drain runoff down slope and to prevent erosion of slope. | M-208 | | | | | × | × | |
| OUTLET PROTECTION Riprap, or approved other | Material placed as energy dissipater to prevent erosion at outlet structure. | | | | | | x | х | |
| CONCRETE WASHOUT In-ground or fabricated | Construction control, used for waste management of concrete and concrete equipment cleaning. Place prior to start of concrete activities. | M-208 | | х | | х | х | | |
| VEHICLE TRACKING PAD | Source control, placed to prevent tracking of sediment from disturbed area to offsite surface. Place prior to start of construction disturbances. | M-208 | | х | | Х | x | | |
| SWEEPING | Source control, used to remove sediment tracked onto paved surfaces and to prevent sediment from entering drainage system. Sweep daily and at the end of the construction shift as needed. Kick brooms shall not be permitted. | | | | | х | х | | |
| DEWATERING (Contractor is responsible for obtaining a permit from Colorado Department of Health and Environment.) | Shall be done in such a manner to prevent potential pollutants from entering state waters. | | | x | | х | х | | |
| TEMPORARY STREAM CROSSING (SWMP Administrator shall add locations to SWMP site maps) | Constructed over stream or drainage to prevent discharge of pollutants from construction equipment into water. | | | | | х | х | | |
| CLEAN WATER DIVERSION | Placed to divert clean surface or ground water around disturbance area to prevent it from mixing with construction runoff. | | | х | | х | × | | |
| OTHER | | | | | | | | | |

| Print Date: 11/16/2016 | | Γ |
|-----------------------------------|-----------------------|---|
| Drawing File Name: 19888SWMP_SWMP | Notes.dgn | |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted | |
| Unit Information | Unit Leader Initials | |
| M MULI | _ER | |
| ENGINEERING | COMPANY | ı |

| | Sheet Revisions | |
|-------|-----------------|-------|
| Date: | Comments | Init. |
| | | |
| | | |
| | | |
| | | |



| As Constructed | BOULDER CANYON TRAIL EXTENSION STORMWATER MANAGEMENT PLANS | | | | Project No./Cod | | | | |
|----------------|--|---|------------------------|--|-----------------|--------------|----|--|--|
| No Revisions: | | | | | STU C070-043 | | | | |
| Revised: | Designer: | | Structure | | | 19888 | | | |
| Void: | Detailer: Sheet Subset: | .,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | Numbers Subset Shee | | 5 of 7 | Sheet Number | 92 | | |

NON-STRUCTURAL BMPs/Control Measures that may be potentially used on the project for erosion and sediment control; practices may include, but are not limited to: Erosion control devices are used to limit the amount of soil loss on site.

Sediment control devices are designed to capture sediment on the project site.

Construction controls are BMPs/Control Measures related to construction access and staging. BMP/Control Measure locations are indicated on the SWMP site map.

| | NARRATIVE | | | E TO | ITROL | ВМР/СС | BMP/CONTROL MEASUR PHASING | | | |
|---|---|-------|--|---|--|---|---------------------------------------|----------------------------|--|--|
| APPLICATION, BMP/CONTROL MEASURE | | | | BMP/CONTROL MEASURE BE LOCATED BY SWMP ADMINSTRATOR | INSTALLATION BMP/CONTROL MEASURE PRE- CONSTRUCTION | FIRST/INITIAL CONSTRUCTION ACTIVITIES | INTERIM CONSTRUCTION ACTIVITIES | PERMANENT STABILIZATION | | |
| VEGETATIVE BUFFER STRIP Fence (plastic) | Filter sediment laden runoff from disturbance area. Area to be identified on SWMP prior to construction starting. | | | | | х | х | х | | |
| LANDFORM (SWMP Administrator shall add locations to SWMP site maps) | Existing landforms may be used as a BMP/Control Measure if they prevent sediment from entering or leaving the disturbance area. If a landform directs flow of water to a concentrated outfall point, the outfall point shall be protected to prevent erosion. Area to be identified on SWMP prior to construction starting. | | | | | х | х | | | |
| TOPSOIL MANAGEMENT STOCKPILE/ SALVAGE Windrow or stockpile | Prior to embankment work commencing, existing topsoil shall be scraped to a depth of 4 inches, and placed in stockpiles or windrows. Upon completion of slope work/final grading (less 4 inches), topsoil shall be evenly distributed over embankment to a depth of 4 inches. | | | | | х | х | | | |
| SURFACE ROUGHENING / GRADING TECHNIQUES Blading, Backhoe, Dozing, Combination Loader | Temporary stabilization of disturbance and to minimize wind and erosion. | | | | | | х | | | |
| SEEDING (TEMPORARY) | Temporary stabilization used for over wintering of disturbance or used to control erosion for areas scheduled for future construction. | | | | | | х | | | |
| BONDED FIBER MATRIX/HYDRAULIC MULCH | Not to be used in areas of concentrated flows, i.e. ditch lines. To be used in combination with surface roughening for temporary stabilization of disturbed soils, when work is temporarily halted and as approved by the Engineer. May be used as surface cover for temporary topsoil stockpiles | | | | | | х | | | |
| MULCH/MULCH TACKIFIER | Temporary or Final Stabilization placed as a surface cover for erosion control and or seeding establishment. To be installed as temporary surface cover when work is temporarily halted and as approved by the Engineer | | | | | | х | х | | |
| SPRAY-ON MULCH BLANKET (Not to be used in areas of concentrated flows, i.e. ditch lines.) | Temporary or Final Stabilization placed as a surface cover for erosion control and or seeding establishment. To be installed as temporary surface cover when work is temporarily halted and as approved by the Engineer | | | | | | х | х | | |
| SEEDING PERMANENT (NATIVE) | Final Stabilization of disturbance and to reduce runoff and control erosion on disturbed areas. | | | | | | | х | | |
| SOIL RETENTION BLANKET (SRB) | Final Stabilization of disturbance and to reduce runoff and control erosion on disturbed areas. | M-216 | | | | | х | x | | |
| TURF REINFORCEMENT MAT (TRM) | Final Stabilization of disturbance and to reduce runoff and control erosion on disturbed areas. Placed in channels or on slopes for erosion control, channel liner and seeding establishment. | M-216 | | | | | х | х | | |
| OTHER | | | | | | | | | | |

| Print Date: 11/16/2016 | |
|----------------------------------|-----------------------|
| Drawing File Name:19888SWMP_SWMP | ' Notes.dgn |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| MUL ENGINEERING | , |

| | | Sheet Revisions | | | | | | | | | |
|---|-------|-----------------|-------|--|--|--|--|--|--|--|--|
| | Date: | Comments | Init. | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| 0 | | | | | | | | | | | |
| | | | | | | | | | | | |





| As Constructed | BOULDE | R CANYON | | | | Project No./ | Code |
|----------------|--------------------------------|----------|------------|------|------------|--------------|------|
| No Revisions: | STORMWATER MANAGEMENT PLANS | | | | STU C070-0 | 43 | |
| Revised: | Designer: | | Structure | | | 19888 | |
| | Detailer: | REW | Numbers | | | | |
| Void: | Sheet Subset: | SWMP | Subset She | ets: | 6 of 7 | Sheet Number | 93 |

- A. BMP/Control Measure sediment removal and disposal shall be paid for as: 208 Removal and Disposal of Sediment (Equipment) and 208 Removal and Disposal of Sediment (Labor). All other BMP/Control Measure maintenance shall be included in the cost of the BMP/Control Measure
- B. It is estimated that 60 hours of labor, combination loader (90 horsepower) and/or backhoe (200 horsepower) may be required for miscellaneous erosion control work as directed by the Engineer. Work shall be paid for as: 203 Labor, 203 Combination Loader or 203 Backhoe.
- C. Establishment of seeded areas shall be paid for as: Included in the price of the work. This shall include mowing, weed control, reseeding/mulch/tackifier.

| Pay Item | Description | Pay Unit | Initial Const. | Interim Const. | Permanent Stabilization | *Total Quantity |
|-----------|--|-------------|-------------------|-------------------|----------------------------|--------------------|
| 203-01510 | Backhoe | Hour | | 60 | | 60 |
| 203-01594 | Combination Loader | Hour | | 60 | | 60 |
| 203-02330 | Laborer | Hour | | 60 | | 60 |
| 207-00205 | Topsoil | CY | | | 1000 | 1000 |
| 207-00210 | Stockpile Topsoil | CY | | 1000 | | 1000 |
| 208-00002 | Erosion Log Type 1 (12 inch) | LF | 2370 | 990 | | 3360 |
| 208-00035 | Aggregate Bag | LF | | 64 | | 64 |
| 208-00045 | Concrete Washout Structure | Each | | 4 | | 4 |
| 208-00052 | Storm Drain Inlet Protection (Type II) | Each | | 1 | | 1 |
| 208-00056 | Storm Drain Inlet Protection (Type III) | Each | | 2 | | 2 |
| 208-00070 | Vehicle Tracking Pad | Each | | 4 | | 4 |
| 208-00103 | Removal and Disposal of Sediment (Labor) | Hour | | 40 | | 40 |
| 208-00105 | Removal and Disposal of Sediment (Equipment) | Hour | | 40 | | 40 |
| 208-00106 | Sweeping (Sediment Removal) | Hour | | 40 | | 40 |
| 208-00107 | Removal of Trash | Hour | | 30 | | 30 |
| 208-00207 | Erosion Control Management (ECM) | Day | | 180 | | 180 |
| 212-00006 | Seeding (Native) | Acre | | | 1.81 | 1.81 |
| 212-00009 | Seeding (Temporary) | Acre | | 0.53 | | 0.53 |
| 213-00002 | Mulching (Weed Free Hay) | Acre | | | 1.29 | 1.29 |
| 213-00061 | Mulch Tackifier | LB | | | 258 | 258 |
| 214-00000 | Landscape Maintenance | LS | | | 1 | 1 |
| 216-00201 | Soil Retention Blanket (Straw/Coconut) (Biodegradable Class 1) | SY | | | 2501 | 2501 |
| 607-11525 | Fence (Plastic) | LF | 1400 | 600 | | 2000 |
| 700-70380 | Erosion Control | FA | | 1 | | 1 |

*It is anticipated that additional BMPs/Control Measures and BMP/Control Measure quantities not shown on the SWMP Site Maps shall be required on the project for unforeseen conditions and replacement of items that are beyond their useful service life, see subsection 208.03 and 208.04. Quantities for all BMPs/Control Measures shown above are estimated, and have been increased for unforeseen conditions and normal BMP/Control Measure life expectancy. Quantities shall be adjusted according to the conditions encountered in the field as directed and approved by the Engineer. Payment shall be for the actual work completed and material used.

13. BIOLOGIC IMPACT

A. ENVIRONMENTAL IMPACTS:

1. Wetland Impacts: NO

2. Stream Impacts: YES

- 3. Threatened and Endangered Species: None
- 4. If YES to any of the above items, are any permits required or additional actions needed (404, etc.): Floodplain permit

14. NOTES

- A. Stormwater Management Plan (SWMP) information shown is based upon existing conditions. The Contractor is responsible for making determination as to the accuracy of BMP types and locations shown. The contracted Erosion Control Supervisor shall coordinate with the superintendent and engineer as to the appropriate BMPs and their locations and shall make the updates to the SWMP sheets as soon as the changes are known.
- B. Contractor shall use construction fence and barriers around limits of work as necessary to keep pedestrians out of work area and construction vehicles within work area shown on plans. For the tabulation of stormwater quantities it was assumed that 2000 LF of Fence (Plastic) is needed.
- C. Vehicle tracking pad and concrete washout area locations shall be determined by the Contractor and drawn on the plans. For the tabulation of stormwater quantities it was assumed that four vehicle tracking pads and four concrete washout areas are needed.
- D. If stabilized staging area is used by the Contractor, the location shall be shown on the plans, with appropriate BMPs.
- E. Inlet protection shall be installed on existing inlets at the start of construction. Protection for proposed inlets shall be installed once the inlet is in place.
- F. Road shall be swept prior to striping to minimize the transport of sediment.

EROSION CONTOL LEGEND

EROSION CONTOL LEGEND, CONTINUED

---- TOE OF FILL

PHASE: INTIAL, INTERIM, AND/OR FINAL

— — — — — TOP OF CUT

— — XXXX—

-xxxx-

SOIL RETENTION BLANKET

AND SEEDING

--- PROPOSED CONTOUR

FLOW ARROW

EXISTING CONTOUR

WETLANDS BOUNDARY

EXISTING WETLANDS




(EL)


(IP#)

(SM)


















7777777

EROSION LOG TYPE (12 INCH) 1 CULVERT INLET/OUTLET PROTECTION

STORM DRAIN INLET PROTECTION (TYPE I, II OR III)

STORM DRAIN (DROP) INLET PROTECTION EROSION LOG TYPE 1 (12 INCH) DR AGGREGATE BAG






PLASTIC FENCE

LIMITS OF CONSTRUCTION



RDCK CHECK DAM



SILT FENCE

-BMP IDENTIFICATION -OUANTITY OF BMP

SEEDING AND MULCHING

| Print Date: 11/16/2016 | |
|-----------------------------------|-----------------------|
| Drawing File Name: 19888SWMP_SWMP | Notes.dgn |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| MUL ENGINEERING | ` |


| | | Sheet Revisions | |
|---|-------|-----------------|-------|
| | Date: | Comments | Init. |
| 0 | | | |
| 0 | | | |
| 0 | | | |
| | | | |


Chart Davisians








| | As Constructed | BOULDE | R CANYON STORM | | | | Project No./ | 'Code |
|----------|----------------|---------------|-------------------|-------------|------|--------|--------------|-------|
| Ν | lo Revisions: | MAI | NAGEME | | | | STU C070-0 | 43 |
| R | Revised: | Designer: | | Structure | | | 19888 | |
| \vdash | | Detailer: | REW | Numbers | | | | |
| ٧ | oid: | Sheet Subset: | SWMP | Subset Shee | ets: | 7 of 7 | Sheet Number | 94 |

















TABULATION OF SIGNS

| | | | | | | | | DEMOVAL | DEGET | SIGN PANEL | 1005 | un. v | | | 07FF1 010N | STEEL | SIGN SUPPO | RT | |
|----------|---------|----------------------|------|-----------|--------------------|---------------------|--------------------------------|-----------------------------|-------------------------|------------|---------------------|-----------|-----------|--------------|------------------------------------|--|-----------------------------|-------------------------------|----------|
| SIGN NO. | STATION | LOCATION | SIDE | SIGN CODE | SIGN PANEL SIZE | BACKGROUND COLOR | LEGEND | REMOVAL OF SIGN PANEL | RESET GROUND SIGN | CLASS I | ASSEI GRO SIZ | OUP ZE | POST SIZE | NO. POSTS | STEEL SIGN POST (2X2 TUBING) | STEEL SIGN POST (2.25X2.25 TUBING) | (2-INCH ROUND) (POST) | (2-INCH ROUND) (SOCKET) | COMMENTS |
| | | | | | W" x H" | | | EA | EA | SF | WIDTH | HEIGTH | | | LF | LF | LF | EA | |
| 1 1 | 104+60 | BOULDER CANYON TRAIL | Rt | W7-5 | 18 x 18 | YELLOW | HILL | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| 2 | 105+18 | SH 119 | Rt | W1-8 | 18 x 24 | YELLOW | CURVE CHEVRON | | 1 | | | | | | | | | | |
| 3 | 105+45 | BOULDER CANYON TRAIL | Rt | W1-11L | 18 x 18 | YELLOW | HAIRPIN CURVE (LEFT) | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| 4 | 105+65 | BOULDER CANYON TRAIL | Rt | W12-51 | 18 x 18 | YELLOW | TUNNEL | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| 5 | 106+80 | BOULDER CANYON TRAIL | Lt | W1-11R | 18 x 18 | YELLOW | HAIRPIN CURVE (RIGHT) | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| 6 | 109+75 | BOULDER CANYON TRAIL | Rt | W8-3 | 18 x 18 | YELLOW | PAVEMENT ENDS | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| 7 | 114+18 | PRIVATE DRIVE | Lt | | X | | NO PARKING SIGN | 1 | | | | | | | | | | | |
| 8 | 114+37 | BOULDER CANYON TRAIL | Rt | R1-1 | 18 x 18 | RED | STOP | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| 9 | 114+73 | BOULDER CANYON TRAIL | Lt | R1-1 | 18 x 18 | RED | STOP | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| 10 | 116+80 | BOULDER CANYON TRAIL | Lt | W8-3 | 18 x 18 | YELLOW | PAVEMENT ENDS | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| 11 | 119+50 | BOULDER CANYON TRAIL | Rt | R1-2 | 18 x 18 | RED | YIELD | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| 12 | 120+20 | BOULDER CANYON TRAIL | Lt | R1-2 | 18 x 18 | RED | YIELD | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| 13 | 124+25 | BOULDER CANYON TRAIL | Rt | W16-1 | 24 x 24 | WHITE | SHARE THE ROAD | | | 4.00 | 24 | 24 | S | 1 | 10 | 3 | | | |
| 14 | 124+35 | BOULDER CANYON TRAIL | Lt | R5-3 | 24 x 24 | WHITE | NO MOTOR VEHICLES | | | 4.00 | 24 | 24 | S | 1 | 10 | 3 | | | |
| 15 | 128+35 | BOULDER CANYON TRAIL | Lt | W16-1 | 24 x 24 | WHITE | SHARE THE ROAD | | | 4.00 | 24 | 24 | S | 1 | 10 | 3 | | | |
| 16 | 129+15 | BOULDER CANYON TRAIL | Lt | R5-3 | 24 x 24 | WHITE | NO MOTOR VEHICLES | | | 4.00 | 24 | 24 | S | 1 | 10 | 3 | | | |
| 17 | 129+75 | BOULDER CANYON TRAIL | Lt | W8-14 | 18 x 18 | YELLOW | FALLEN ROCKS | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| 18 | 130+15 | BOULDER CANYON TRAIL | Lt | W7-5 | 18 x 18 | YELLOW | HILL | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| 19 | 130+60 | BOULDER CANYON TRAIL | Rt | R10-15 | 30 x 30 | WHITE | TURNING VEHICLES YIELD TO PEDS | | | 6.25 | 30 | 30 | P1 | 1 | | | 10 | 1 | |
| 20 | 131+95 | BOULDER CANYON TRAIL | Lt | W8-14 | 18 x 18 | YELLOW | FALLEN ROCKS | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| 21 | 135+75 | BOULDER CANYON TRAIL | Rt | W8-3 | 18 x 18 | YELLOW | PAVEMENT ENDS | | | 2.25 | 18 | 18 | S | 1 | 10 | 3 | | | |
| | | | | | | | PROJECT TOTALS | 1 | 1 | 53.75 | | | | 19 | 180 | 54.0 | 10 | 1 | |

TABULATION OF PAVEMENT MARKINGS

| | | | | | | | М | DDIFIED EPO | XY | | ED PLASTIC)(INLAID) |
|----------------------|---------|----|---------|-----------------------|-----------|-----------------|------------------|-----------------|------------------|---------------------|-------------------------|
| | | | | PAVEMENT | | | | CENTERLINE | | | |
| LOCATION | STATION | то | STATION | N TYPE SIDE DIRECTION | DIRECTION | YELLOW SOLID | YELLOW BROKEN | WHITE DOTTED | WORD - SYMBOL | XWALK - STOPLINE | |
| | | | | | | | 4 INCH | 4 INCH | 4 INCH | | |
| BOULDER CANYON TRAIL | 105+20 | TO | 109+30 | New Concrete | Lt | | 375 | | | | |
| BOULDER CANYON TRAIL | 124+25 | TO | 124+68 | New Concrete | Lt | | 43 | | | | |
| BOULDER CANYON TRAIL | 125+33 | TO | 126+52 | New Concrete | Lt | | 115 | | | | |
| BOULDER CANYON TRAIL | 126+52 | TO | 127+82 | New Concrete | Lt | | | 130 | | <u> </u> | ľ |
| BOULDER CANYON TRAIL | 127+82 | TO | 128+32 | New Concrete | Lt | | 50 | | | | * |
| BOULDER CANYON TRAIL | 128+32 | TO | 129+25 | New Concrete | Lt | | | | 90 | | |
| BOULDER CANYON TRAIL | 129+25 | TO | 129+75 | New Concrete | Lt | | 50 | | | | |
| BOULDER CANYON TRAIL | 132+00 | TO | 136+25 | New Concrete | Lt | | 440 | | | | |
| BOULDER CANYON TRAIL | 124+25 | TO | 126+55 | New Concrete | PAVEMENT | SYMBOLS | | | | 160.13 | |
| | | | | | | TOTAL (LF) | 1073 | 130 | 90 | | |
| | | | | | | TOTAL (SF) | | | | 160.13 | 0.00 |
| | | | | | | TOTAL (GAL) | 4.21 | 0.13 | 0.07 | | |


NOTES: CONSULT WITH PROJECT ENGINEER FOR APPROVAL OF STRIPE TYPE PRIOR TO PLACING FINAL PAVEMENT MARKINGS.

SUMMARY OF PAVEMENT MARKING QUANTITIES

| | MODIFIE | D EDOVY | DESCRIPTION ACTIONAL PROPERTY MADICING | | | | | |
|----------------|-----------|---------|--|------------------|--|--|--|--|
| | MODIFIE | | PREFORMED PLASTIC PAVEMENT MARKING | | | | | |
| | (G | AL) | (TYPE I)(INLAID) (SF) | | | | | |
| | YELLOW | WHITE | WORD - SYMBOL | XWALK - STOPLINE | | | | |
| | 4.34 0.07 | | | | | | | |
| PROJECT TOTALS | 4. | 41 | 160.13 | 0.00 | | | | |




| Print Date: 11/16/2016 | |
|------------------------------------|-----------------------|
| Drawing File Name:19888TRAF_Tab.dg | ın |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| MAMUL | LER |
| ENGINEERING | COMPANY |











| | | | | | | Can before y | ou aigi | |
|----------------|--|-----------|------------------|------|--------|--------------|---------|--|
| As Constructed | | ER CANYON | Project No./Code | | | | | |
| No Revisions: | TABULATION OF SIGNS AND PAVEMENT MARKINGS | | | | | STU C070-043 | | |
| Revised: | Designer: | CZC | Structure | | | 19888 | | |
| | Detailer: | CZC | Numbers | | | | | |
| Void: | Sheet Subset: | TRAF TAB | Subset Shee | ets: | 1 of 1 | Sheet Number | 102 | |

















CONSTRUCTION TRAFFIC CONTROL NOTES

- 1. IT IS THE INTENT OF THE TRAFFIC CONTROL NOTES AND PLANS TO CONVEY TO THE CONTRACTOR THE GENERAL, BUT ESSENTIAL, DESIGN ELEMENTS REQUIRED TO CONSTRUCT THE PROJECT. OTHER MINIPHASES (NOT INDICATED IN THE PLAN SET) USING TEMPORARY LANE CLOSURES MAY BE NECESSARY TO CONSTRUCT THE PROPOSED IMPROVEMENTS. THE CONTRACTOR SHALL SUBMIT TO BOULDER COUNTY AND CDOT FOR REVIEW AND APPROVAL, A METHOD OF HANDLING TRAFFIC (MHT) CONFORMING TO CDOT'S STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION AND M&S STANDARDS TWO WEEKS PRIOR TO RELATED CONSTRUCTION ACTIVITY.
- 2. ALL CONSTRUCTION TRAFFIC CONTROL SHALL CONFORM TO THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, 2009 EDITION, AND APPLICABLE STANDARDS IN THE 2011 COLORADO DEPARTMENT OF TRANSPORTATION STANDARDS AND SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION AND THE JULY 2012 COLORADO DEPARTMENT OF TRANSPORTATION STANDARD PLANS M&S STANDARDS.
- 3. REFER TO CDOT M&S STANDARD PLAN S-630-1, REVISED JUNE 23, 2016, FOR STANDARD TRAFFIC CONTROL CASES THAT WILL BE REQUIRED TO IMPLEMENT PHASES AND OTHER TRAFFIC CONTROL CONDITIONS. ALL TRAFFIC CONTROL DEVICES SHALL BE PLACED IN ACCORDANCE WITH THE CONSTRUCTION TRAFFIC CONTROL PLANS, THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, 2009 EDITION, AND CDOT M&S STANDARD PLAN S-630-1.
- 4. THE CONTRACTOR SHALL BEAR RESPONSIBILITY AND EXPENSE FOR MAINTAINING ADEQUATE DRAINAGE AND SAFE DRIVING CONDITIONS AT ALL TIMES. THIS WORK SHALL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE COST OF RELATED WORK.
- 5. APPROPRIATE ADVANCE WARNING SIGNS SHALL BE PLACED AS NEEDED. THESE SHALL BE SHOWN IN THE MHT TO BE APPROVED BY THE ENGINEER.
- 10' MINIMUM WIDTH FOR LANES SHALL BE MAINTAINED AT ALL TIMES UNLESS APPROVED BY THE ENGINEER.
- 7. A MINIMUM SHOULDER WIDTH OF 2 FEET SHALL BE PROVIDED BETWEEN THE CHANNELIZING DEVICE AND EDGE OF TRAVEL LANE AT ALL TIMES.
- UNLESS SHOWN OTHERWISE, MINIMUM REDIRECT TAPER RATES SHALL BE 25:1 AND BAY TAPER RATES SHALL BE 12:1.
- 9. SLOPES WITHIN THE CLEAR ZONE SHALL BE 3:1 OR FLATTER UNLESS PROTECTED BY CONCRETE BARRIER (TEMPORARY). CONCRETE BARRIER (TEMPORARY) SHALL HAVE BOTH ENDS PROTECTED WITH AN IMPACT ATTENUATOR (TEMPORARY), UNLESS FLARED OUTSIDE OF THE CLEAR ZONE.
- 10. REMOVAL OF TEMPORARY PAVEMENT MARKINGS FOR TEMPORARY LANES WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE COST OF PAVEMENT MARKING PAINT. PAINT REMOVALS MUST BE DISPOSED OF PROPERLY OFF-SITE. TEMPORARY TRANSITION MARKINGS SHALL BE REMOVED AND PAID FOR BASED ON THE SQUARE FEET OF SWATH REQUIRED FOR REMOVAL.
- 11. CONTRACTOR SHALL MAINTAIN SAFE AND REASONABLE ACCESS TO PRIVATE PROPERTIES AT ALL TIMES, UNLESS OTHERWISE APPROVED BY THE ENGINEER AND THE PROPERTY OWNER IN WRITING.
- 12. EXISTING SIGNS IN CONFLICT WITH THE TEMPORARY LANES SHALL BE COVERED OR RESET AS CONDITIONS REQUIRE FOR EACH CONSTRUCTION PHASE AND AS DIRECTED BY THE ENGINEER. MASKING OF EXISTING SIGNS, INCLUDING THE COVERING MATERIALS AND FASTENING DEVICES, WILL NOT BE MEASURED AND PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE COST OF THE WORK.
- 13. CONTRACTOR SHALL REFER TO COLORADO DEPARTMENT OF TRANSPORTATION REGION 4 LANE CLOSURE STRATEGY SECOND EDITION, 2013 FOR WORK HOUR AND LANE CLOSURE RESTRICTIONS. THE SPRING/SUMMER ALLOWED HOURS FOR LANE CLOSURES LESS THAN 0.5 MILE IN LENGTH IS ANYTIME ON WEEKDAYS AND 9PM TO 6AM ON WEEKENDS.
- 14. TEMPORARY TRAFFIC SIGNALS ARE ESTIMATED TO OPERATE A TOTAL OF 180 DAYS ON THE PROJECT. PHASING ASSUMED A MAXIMUM OF TWO PAIRS OF PORTABLE TRAILER TEMPORARY SIGNALS OPERATING CONCURRENTLY WITHIN THE CORRIDOR.

SUGGESTED CONSTRUCTION PHASING WORK ITEMS

(REFER TO CONSTRUCTION PHASING SHEETS FOR ADDITIONAL DETAILS.)

GENERAL PHASING:

- 1. IT IS ANTICIPATED THAT TRAFFIC CONTROL FOR CONSTRUCTION OF CBC 1 AND CBC 2 CAN BE HANDLED THROUGH USE OF CDOT S-630-1 STANDARD PLAN CASE 17.
- 2. IT IS ANTICIPATED THAT WORK DIRECTLY ADJACENT TO SH 119 THAT IMPACTS TRAFFIC CAN BE HANDLED THROUGH USE OF CDOT S-630-1 STANDARD PLAN CASES 15, 17, AND 24. THIS WORK INCLUDES:
 - a. GUARDRAIL INSTALLATION
 - b. RETAINING WALL CONSTRUCTION
 - c. CURB AND GUTTER INSTALLATION AT ALPS INN
 - d. RECONSTRUCTION OF DRIVEWAY AT ALPS INN
 - e. ROCK EXCAVATION (MAY REQUIRE BLASTING)
- CONSTRUCTION OF BRIDGE OVER BOULDER CREEK AT CHAPMAN DRIVE IS NOT ANTICIPATED TO IMPACT TRAFFIC.
- 4. THE ROCK EXCAVATION WORK MAY BE CONDUCTED IN COORDINATION WITH THE CONSTRUCTION OF CBC 2 IF THE TOTAL LENGTH OF THE WORK ZONE CAN BE MAINTAINED AT A LENGTH OF 0.15 MILE OR LESS. IF THE RESULTING WORK ZONE LENGTH IS LONGER THAN 0.15 MILE, THE ROCK EXCAVATION WORK SHOULD PRECEDE OR FOLLOW THE CONSTRUCTION OF CBC 2. THE TEMPORARY TRAFFIC SIGNAL FROM CBC 2 SHOULD BE UTILIZED TO MAINTAIN AN ALTERNATING LANE OF TRAFFIC THROUGH THE WORK ZONE.

CBC 1 PHASE 1:

- 1. INSTALL DETOUR PAVEMENT ON WEST SIDE OF SH-119 AT CBC 1 LOCATION
- 2. INSTALL TEMPORARY SIGNALS AND TRAFFIC CONTROL AS SHOWN IN THE PLANS TO DIVERT TRAFFIC TO WEST-BOUND LANE/DETOUR PAVEMENT
- 3. CLEAR AND GRUB AREAS NEAR EAST SIDE OF CBC 1 CROSSING.
- COMPLETE PRELIMINARY GRADING AT EASTSIDE OF CBC 1 CROSSING LOCATION IN PREPARATION FOR INSTALLATION
- 5. EXCAVATE AREA AND INSTALL TEMPORARY SHORING
- 6. REMOVE EXISTING CBC FROM THE EAST HALF OF SH-119
- 7. $\,$ INSTALL 6 PRECAST SECTIONS OF CBC 1 ON THE EAST HALF OF SH-119 AS SHOWN IN PHASING PLANS.
- INSTALL WALLS 3 AND 5 AND COMPLETE ALL EMBANKMENT WORK FOR FUTURE BIKE PATH ON THE EAST SIDE OF SH-119
- 9. REMOVE DETOUR AND SHIFT TRAFFIC BACK ONTO SH-119.

CBC 1 PHASE 2:

- 1. INSTALL DETOUR PAVEMENT ON EAST SIDE OF SH-119 AT CBC 1 LOCATION
- 2. INSTALL TEMPORARY SIGNALS AND TRAFFIC CONTROL AS SHOWN IN THE PLANS TO DIVERT TRAFFIC ONTO DETOUR PAVEMENT
- 3. CLEAR AND GRUB AREAS ON WEST SIDE OF CBC 1 CROSSING.
- 4. COMPLETE PRELIMINARY GRADING ON WEST SIDE OF CBC 1 CROSSING LOCATION IN PREPARATION FOR INSTALLATION.
- 5. EXCAVATE AREA AND INSTALL TEMPORARY SHORING
- 6. REMOVE EXISTING CBC FROM THE WEST HALF OF SH-119
- 7. INSTALL REMAINING 6 PRECAST SECTIONS OF CBC ON THE WEST HALF OF SH-119 AS SHOWN IN PHASING PLANS.
- . INSTALL WALLS 6 AND 7
- 9. INSTALL PERMANENT TYPE 3 GUARDRAIL ON WEST SIDE OF SH-119
- 10. INSTALL PERMANENT PAVEMENT MARKINGS. REMOVE DETOUR AND SHIFT TRAFFIC BACK ONTO SH 119.

| Horiz. Scale: 1:1 Unit Information | Vert. Scale: As Noted Unit Leader Initials | _ |
|---------------------------------------|--|---|
| /// MULI | ER | |

| | Sheet Revisions | | | | | | | |
|---------------|-----------------|----------|-------|--|--|--|--|--|
| | Date: | Comments | Init. | | | | | |
| \bigcup | | | | | | | | |
| \bigcup | | | | | | | | |
| \bigcup | | | | | | | | |
| $\overline{}$ | | | | | | | | |

Charle Davids





| As Constructed | | | | | Project | | Project No., | /Code |
|----------------|-----------------------|-----|-------------|------|---------|--------------|--------------|-------|
| No Revisions: | TRAFFIC CONTROL NOTES | | | | | STU C070-043 | | |
| Revised: | Designer: | | Structure | | | 19888 | | |
| | Detailer: | CZC | Numbers | | | | | |
| Void: | Sheet Subset: | TC | Subset Shee | ets: | 1 of 2 | Sheet Number | 110 | |

- 1. IF NECESSARY TO COMPLETE CONSTRUCTION ACTIVITIES INSTALL TEMPORARY SIGNALS.
- 2. CLEAR AND GRUB AREA ON EAST SIDE OF CBC 2 CROSSING.
- 3. COMPLETE PRELIMINARY GRADING AT EAST SIDE OF CBC 2 CROSSING LOCATION IN PREPARATION FOR INSTALLATION.
- 4. EXCAVATE AREA AND INSTALL TEMPORARY SHORING.
- 5. INSTALL WALL 10.

CBC 2 PHASE 2:

- 1. REMOVE EXISTING GUARDRAIL AND INSTALL DETOUR PAVEMENT ON WEST SIDE OF SH-119 AT CBC 2 LOCATION
- 2. INSTALL TEMPORARY SIGNALS AND TRAFFIC CONTROL AS SHOWN IN THE PLANS TO DIVERT TRAFFIC ONTO DETOUR PAVEMENT.
- 3. EXCAVATE AREA AND INSTALL TEMPORARY SHORING.
- 4. INSTALL 16 PRECAST SECTIONS OF CBC ON THE EAST HALF OF SH-119 AS SHOWN IN PHASING PLANS.
- 5. INSTALL PORTION OF STORM LINE LOCATED IN EXCAVATED AREA NEXT TO CBC 2.
- 6. INSTALL PERMANENT TYPE 3 GUARDRAIL ON EAST SIDE OF SH-119.
- 7. REMOVE DETOUR AND SHIFT TRAFFIC BACK ONTO SH-119.

CBC 2 PHASE 3:

- 1. INSTALL TEMPORARY SIGNALS AND TRAFFIC CONTROL AS SHOWN IN THE PLANS TO DIVERT TRAFFIC TO EAST-BOUND LANE.
- 2. CLEAR AND GRUB AREA NEAR WEST SIDE OF CBC 2 CROSSING.
- 3. COMPLETE PRELIMINARY GRADING AT WEST SIDE OF CBC CROSSING LOCATION IN PREPARATION FOR INSTALLATION
- 4. EXCAVATE AREA AND INSTALL TEMPORARY SHORING.
- 5. INSTALL REMAINING 4 PRECAST SECTIONS OF CBC ON THE WEST HALF OF SH-119 AS SHOWN IN PHASING PLANS.
- 6. INSTALL REMAINING PORTION OF STORM LINE LOCATED IN EXCAVATED AREA NEXT TO CBC 2.
- 7. INSTALL WALLS 8 AND 9 AND PERMANENT TYPE 3 GUARDRAIL ON WEST SIDE OF SH-119
- 8. INSTALL PERMANENT PAVEMENT MARKINGS. REMOVE DETOUR AND SHIFT TRAFFIC BACK ONTO SH 119.

| MUL ENGINEERING | \ |
|-------------------------------------|-----------------------|
| Unit Information | Unit Leader Initials |
| Horiz. Scale: 1:1 | Vert. Scale: As Noted |
| Drawing File Name:19888TRAF_Traffic | c Control Notes.dgn |
| Print Date: 11/16/2016 | |

| | Sheet Revisions | | | | | | | |
|-----------|-----------------|----------|-------|--|--|--|--|--|
| | Date: | Comments | Init. | | | | | |
| \bigcap | | | | | | | | |
| \bigcap | | | | | | | | |
| \bigcap | | | | | | | | |
| \neg | | | | | | | | |





| As Constructed | BOULDER CANYON TRAIL EXTENSION | | | Project No./Code | | | |
|----------------|--------------------------------|-----|------------|------------------|--------|--------------|-----|
| No Revisions: | TRAFFIC | COI | NTROL | NOTES | | STU C070-0 | 043 |
| Revised: | Designer: | | Structure | | | 19888 | |
| | Detailer: | CZC | Numbers | | | | |
| Void: | Sheet Subset: | TC | Subset She | ets: | 2 of 2 | Sheet Number | 111 |

zadkison 3:32:20 PM Q:\2015 Project 11/16/2016 — CDNT-DefaultPrinter VB

TABULATION OF CONSTRUCTION TRAFFIC CONTROL ITEMS

| ITEM NO. | ITEM | UNIT | TOTALS |
|-----------|---|------|--------|
| 621-00425 | DETOUR (CBC 1) ¹ | LS | 1 |
| 621-00425 | DETOUR (CBC 2) ² | LS | 1 |
| 627-00011 | PAVEMENT MARKING PAINT (WATERBORNE)[TEMPORARY] | GAL | 15 |
| 630-00000 | FLAGGING | HOUR | 500 |
| 630-00003 | UNIFORMED TRAFFIC CONTROL | HOUR | 16 |
| 630-00007 | TRAFFIC CONTROL INSPECTION | DAY | 51 |
| 630-00012 | TRAFFIC CONTROL MANAGEMENT | DAY | 129 |
| 630-80341 | CONSTRUCTION TRAFFIC SIGN (PANEL SIZE A) | EA | 40 |
| 630-80342 | CONSTRUCTION TRAFFIC SIGN (PANEL SIZE B) | EA | 12 |
| 630-80350 | VERTICAL PANEL | EA | 150 |
| 630-80355 | PORTABLE MESSAGE SIGN PANEL | EA | 2 |
| 630-80360 | DRUM CHANNELIZING DEVICE | EA | 100 |
| 630-80364 | DRUM CHANNELIZING DEVICE (WITH LIGHT) (STEADY BURN) | EA | 20 |
| 630-80370 | CONCRETE BARRIER (TEMPORARY) | LF | 2,000 |
| 630-85010 | IMPACT ATTENUATOR (TEMPORARY) | EA | 6 |
| 630-86810 | TRAFFIC SIGNAL (TEMPORARY) ³ | EA | 2 |

NOTES (FOR INFORMATION ONLY):

- 1. DETOUR (CBC 1) (LUMP SUM) SHALL CONSIST OF ALL WORK NECESSARY TO CONSTRUCT AND REMOVE TEMPORARY DETOURS DURING PHASE 1 AND PHASE 2. IT IS ESTIMATED THAT THIS WORK SHALL CONSIST OF 950 CY EMBANKMENT MATERIAL, 180 SY DETOUR PAVEMENT, AND REMOVAL OF EMBANKMENT MATERIAL AND DETOUR PAVEMENT.
- 2. DETOUR (CBC 2) (LUMP SUM) SHALL CONSISTS OF ALL WORK NECESSARY TO CONSTRUCT AND REMOVE TEMPORARY DETOUR DURING PHASE 2. IT IS ESTIMATED THAT THIS WORK SHALL CONSIST OF 870 CY EMBANKIMENT MATERIAL, 450 SY DETOUR PAVEMENT, 25 LF OF 48" DRAINAGE PIPE, PROTECTING EXISTING STONE HEADWALL IN PLACE, AND REMOVAL OF DETOUR PAVEMENT, EMBANKMENT MATERIAL, 48" DRAINAGE PIPE, AND HEADWALL PROTECTION.
- 3. TRAFFIC SIGNAL (TEMPORARY) CONSISTS OF TWO TRAILER MOUNTED TRAFFIC SIGNALS.
- 4. TRAFFIC CONTROL DEVICES AND MARKINGS ARE NOT INCLUDED IN DETOUR (LUMP SUM) AND SHALL BE PAID FOR SEPARATELY AS SHOWN ON THE PLANS.

SCHEDULE OF CONSTRUCTION TRAFFIC CONTROL SIGNS

| | | | F | ANEL SIZ | <u>'</u> E | |
|-----------|--|-----------|----|----------|------------|---------|
| SIGN CODE | LEGEND | DIMENSION | Α | В | С | SPECIAL |
| | | WxH | EA | EA | EA | SF |
| G20-10 | XYZ CONSTRUCTION THANKS YOU | 48 x 48 | | 2 | | |
| G20-11 | CDOT LOGO ROAD WORK MMM YY-MMM YY FOR INFO | 48 x 48 | | 2 | | |
| G20-5aP | WORK ZONE | 24 x 18 | 8 | | | |
| R2-1(20) | SPEED LIMIT 20 | 24 x 30 | 2 | | | |
| R2-1(25) | SPEED LIMIT 25 | 24 x 30 | 6 | | | |
| R2-1(40) | SPEED LIMIT 40 | 24 x 30 | 2 | | | |
| R10-6 | STOP HERE ON RED | 24 x 36 | 4 | | | |
| R52-6a | BEGIN FINES DOUBLE ZONE | 36 x 48 | • | 2 | | |
| R52-6b | END FINES DOUBLE ZONE | 36 x 48 | | 2 | | |
| W3-3 | TRAFFIC SIGNAL | 36 x 36 | 4 | | | |
| W3-5a | 20 MPH SPEED ZONE AHEAD | 36 x 36 | 1 | | | |
| W3-5a | 25 MPH SPEED ZONE AHEAD | 36 x 36 | 1 | | | |
| W20-1 | ROAD WORK AHEAD | 36 x 36 | 3 | | | |
| W20-4 | ONE LANE ROAD AHEAD | 36 x 36 | 4 | | | |
| W20-7A | FLAGGER | 36 x 36 | 2 | | | |
| W20-7 | FLAGGER (SYMBOL) | 36 x 36 | 1 | | | |
| W22-1 | BLASTING ZONE AHEAD | 36 x 36 | 2 | | | |
| W22-2 | TURN OFF 2-WAY RADIO AND CELL PHONE | 42 x 36 | • | 2 | | |
| W22-3 | END BLASTING ZONE | 42 x 36 | • | 2 | | |
| TOTALS | 3 | | 40 | 12 | 0 | 0 |



| Print Date: 11/16/2016 | | | | Sheet Revisions | |
|---|----------------|--|-------|-----------------|-------|
| Drawing File Name:19888TRAF_Const Control Tab.dgn | | | Date: | Comments | Init. |
| Horiz. Scale: 1:1 Vert. Scale: | As Noted (| | | | |
| Unit Information Unit Lead | ler Initials (| | | | |
| ///MULLER | | | | | |
| ENGINEERING COMPANY | | | | | |





| As Constructed | | ER CANYON | | | ואר | Project No., | /Code |
|----------------|--|-----------|------------|------|--------|--------------|-------|
| No Revisions: | TABULATION OF CONSTRUCTION TRAFFIC CONTROL ITEMS | | | | | STU C070-04 | |
| Revised: | Designer: | | Structure | | | 19888 | |
| | Detailer: | CZC | Numbers | | | | |
| Void: | Sheet Subset: | PHASING | Subset She | ets: | 1 of 1 | Sheet Number | 112 |

CBC 1 - PHASE 1

ALL WORK NECESSARY FOR CONSTRUCTION OF DETOUR INCLUDING PLACEMENT AND REMOVAL OF TEMPORARY EMBANKMENT SLOPE AND DETOUR PAVEMENT SHALL BE PAID FOR AS 621-00425 DETOUR (CBC 1) (LUMP SUM). IT IS ESTIMATED THAT 740 CY OF EMBANKMENT AND 115 SY OF DETOUR PAVEMENT WILL BE REQUIRED IN PHASE 1.



| Print Date: 11/16/2016 | |
|--------------------------------|-----------------------|
| Drawing File Name: 19888TRAF_P | hasingTypicals.dgn |
| Horiz. Scale: 1:10 | Vert. Scale: As Noted |
| Unit Information | Unit Leader Initials |
| MU ENCINE | ILLER |

| | Sheet Revisions | | | | | | | |
|---|-----------------|----------|-------|--|--|--|--|--|
| | Date: | Comments | Init. | | | | | |
| 0 | | | | | | | | |
| 0 | | | | | | | | |
| 0 | | | | | | | | |
| | | | | | | | | |



| | Α |
|-------------------|-----|
| | No |
| Boulder County | Rev |
| | Voi |

| As Constructed | BOULDER CANYON SUGGESTE | Project No./Code | |
|----------------|----------------------------|-----------------------|------------------|
| No Revisions: | | SECTIONS | STU C070-043 |
| Revised: | | Structure | 19888 |
| | Detailer: ZDA | Numbers | |
| Void: | | Subset Sheets: 1 of 4 | Sheet Number 113 |

CBC 1 - PHASE 2

ALL WORK NECESSARY FOR CONSTRUCTION OF DETOUR INCLUDING PLACEMENT AND REMOVAL OF TEMPORARY EMBANKMENT SLOPE AND DETOUR PAVEMENT SHALL BE PAID FOR AS 621-00425 DETOUR (CBC 1) (LUMP SUM). IT IS ESTIMATED THAT 210 CY OF EMBANKMENT AND 65 SY OF DETOUR PAVEMENT WILL BE REQUIRED IN PHASE 2.



| Print Date: 11/16/2016 | | | | | |
|--|-----------------------|--|--|--|--|
| Drawing File Name: 19888TRAF_PhasingTypicals.dgn | | | | | |
| Horiz. Scale: 1:10 | Vert. Scale: As Noted | | | | |
| Unit Information | Unit Leader Initials | | | | |
| | JLLER | | | | |
| ENGIN | FEDING COMPANY | | | | |

| | | Sheet Revisions | | |
|---|-------|-----------------|-------|---|
| | Date: | Comments | Init. | |
| 0 | | | | |
| 0 | | | | |
| 0 | | | | 4 |
| | | | | |



| I | As Constructed | BOULDER CANYON TRAIL EXTENSION SUGGESTED PHASING TYPICAL SECTIONS | | | | Project No./Cod | | /Code |
|---|----------------|---|---------|-------------|------|-----------------|--------------|-------|
| I | No Revisions: | | | | | | STU C070-0 | 043 |
| ſ | Revised: | Designer: | | Structure | | | 19888 | |
| ŀ | | Detailer: | ZDA | Numbers | | | | |
| | Void: | Sheet Subset: | PHASING | Subset Shee | ets: | 2 of 4 | Sheet Number | 114 |

1. CBC 2 - PHASE 1 NOT SHOWN AS IT DOES NOT IMPACT TRAFFIC.
2. ALL WORK NECESSARY FOR CONSTRUCTION OF DETOUR INCLUDING PLACEMENT AND REMOVAL OF TEMPORARY EMBANKMENT SLOPE, DETOUR PAVEMENT, 48" PIPE, AND HEADWALL PROTECTION SHALL BE PAID FOR AS 621-00425 DETOUR (CBC 2) (LUMP SUM). IT IS ESTIMATED THAT 870 CY OF EMBANKMENT, 450 SY OF DETOUR PAVEMENT, AND 25 LF OF 48 INCH CMP WILL BE REQUIRED. CONTRACTOR SHALL REMOVE TEMPORARY EMBANKMENT AND EXPOSE STONE HEADWALL AT END OF THIS PHASE. THIS WORK SHALL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE COST OF THE WORK.



| Print Date: 11/16/2016 | | | Sheet Revisions | |
|-----------------------------|------------------------|-------|-----------------|-------|
| Drawing File Name: 19888TRA | AF_PhasingTypicals.dgn | Date: | Comments | Init. |
| Horiz. Scale: 1:10 | Vert. Scale: As Noted | | | |
| Unit Information | Unit Leader Initials | | | |
| /// M | ULLER | | | |
| | INEERING COMPANY | | | |





| As Constructed | BOULDER CANYON TRAIL EXTENSION SUGGESTED PHASING | | | | | | Project No., | /Code |
|----------------|--|------------------|-------------|------|--------|--------------|--------------|-------|
| No Revisions: | | TYPICAL SECTIONS | | | | STU C070-043 | | |
| Revised: | Designer: | | Structure | | | 19888 | | |
| | ┛ Detailer: | ZDA | Numbers | | | | | |
| Void: | Sheet Subset: | PHASING | Subset Shee | ets: | 3 of 4 | Sheet Number | 115 | |



Print Date: 11/16/2016
Drawing File Name: 19888TRAF_PhasingTypicals.dgn
Horiz. Scale: 1:10 Vert. Scale: As Noted
Unit Information Unit Leader Initials


Sheet Revisions

Date: Comments Init.





| SUGGESTED PHASING TYPICAL SECTIONS | | | | 43 |
|---------------------------------------|----------------|---------------------------|------------------------------|---------------------------------|
| | | | 19888 | |
| | | | Sheet Number | 116 |
| | CZC S ZDA N | CZC Structure ZDA Numbers | CZC Structure ZDA Numbers | CZC Structure 19888 ZDA Numbers |



Region 4

Void:


Sheet Subset:

PHASING Subset Sheets:

117

Sheet Number

zadkison 3:32:58 PM 0:\2015 Projects\15-025.01 Boulder Canyon Trail 11/16/2016 CDDT-DefaultPrinter_V8i.pltcfg CDDT V81 BW.tbl



Region 4

Void:


Sheet Subset:


PHASING Subset Sheets:


118

Sheet Number

Projects\15-025.01 Boulder Canyon ter_V8i.pltcfg CDDT V8I BW.tbl







Traffic Information (From OTIS SH 119A Station ID 104339, June 24 & 25, 2013)

| | Peak Hourly Volume | | 15-Minute Volum | | |
|------|-------------------------|-----|-----------------|-----|--|
| AADT | EB | WB | EB | WB | |
| 6400 | 433 | 478 | 108 | 120 | |
| | 911 Bi-direction Volume | | | | |

| Platoon Capacity - CBC 1 | | | | | | | | |
|--------------------------|--------|-------------|-----------|---------|------------|------------|----------------|--|
| Segment | Travel | Lead Car | | Platoon | Last Car | Last Car | Bi-directional | |
| Length | Speed | Travel Time | Headway | Length | Entry Time | Total Time | Capacity | |
| (mi) | (mph) | (min) | (sec/veh) | (veh) | (min) | (min) | (vph) | |
| 0.10 | 20 | 0.300 | 2.5 | 15 | 0.63 | 0.93 | 973.0 | |
| 0.10 | 25 | 0.240 | 2.5 | 15 | 0.63 | 0.87 | 1040.5 | |
| 0.15 | 20 | 0.450 | 2.5 | 15 | 0.63 | 1.08 | 837.2 | |
| 0.15 | 25 | 0.360 | 2.5 | 15 | 0.63 | 0.99 | 913.7 | |

Timing Recommendations

Segment Length = 0.10 miles Assumed Travel Speed = 25 mph

Vert. Scale: As Noted

Unit Leader Initials

| | Green | Yellow | All Red | Total Split |
|-----------|-------|--------|---------|--------------------|
| Direction | (sec) | (sec) | (sec) | (sec) |
| WB | 40 | 3 | 14 | 57 |
| EB | 40 | 3 | 14 | 57 |
| | | | | |

Boulder Canyon Trail Extension Segment A CBC 1 - SH 119 - Chapman Drive

Sheet Revisions

Comments

Init.

Region 4

Date:

SEGMENT B

Traffic Information (From OTIS SH 119A Station ID 104339, June 24 & 25, 2013)

| | Peak Hourly Volume | | eak Hourly Volume 15-Minute Volume | | | |
|------|--------------------|-------------------------|------------------------------------|-----|--|--|
| AADT | EB | WB | EB | WB | | |
| 6400 | 433 | 478 | 108 | 120 | | |
| | | 911 Bi-direction Volume | | | | |

Segment B

CBC 2

| Platoon Capacity - CBC 2 | | | | | | | | |
|---------------------------|--------------------------|----------------------------------|----------------------|----------------------------|---------------------------------|---------------------------------|-------------------------------------|--|
| Segment Length (mi) | Travel Speed (mph) | Lead Car Travel Time (min) | Headway (sec/veh) | Platoon Length (veh) | Last Car Entry Time (min) | Last Car Total Time (min) | Bi-directional Capacity (vph) | |
| 0.10 | 20 | 0.300 | | , , | 0.63 | , , | | |
| 0.15 | 20 | 0.450 | 2.5 | 15 | 0.63 | 1.08 | 837.2 | |
| 0.20 | 20 | 0.600 | 2.5 | 15 | 0.63 | 1.23 | 734.7 | |
| 0.25 | 20 | 0.750 | 2.5 | 15 | 0.63 | 1.38 | 654.5 | |

Timing Recommendations

Segment Length = 0.10 miles Assumed Travel Speed = 20 mph

| | Green | Yellow | All Red | Total Split |
|-----------|-------|--------|---------|-------------|
| Direction | (sec) | (sec) | (sec) | (sec) |
| WB | 40 | 3 | 18 | 61 |
| ED. | 40 | 2 | 10 | 61 |





| I | | Know what's below Call before you dig |
|----------|--------------------------------|--|
| structed | BOULDER CANYON TRAIL EXTENSION | Project No./Cod |


As Constructed TRAFFIC SIGNAL (TEMPORARY)
SUGGESTED TIMINGS No Revisions: STU C070-043 Designer: CZC Structure 19888 Revised: CZC Numbers Detailer: Void: 122 Sheet Number Sheet Subset: TC Subset Sheets:


4-Mile Canyon Drive


Horiz. Scale: 1:1
























































| Print Date: 11/16/2016 | | | | | |
|---|-----------------------|--|--|--|--|
| Drawing File Name:19888DES_Cross Sections.dgn | | | | | |
| Horiz. Scale: 1:20 | Vert. Scale: As Noted | | | | |
| Unit Information | Unit Leader Initials | | | | |
| MULLER ENGINEERING COMPANY | | | | | |

zadkison 3:35:20 PM 0:\2015 Projects\15-025.01 Boulder Conyon TrailExter 11/16/2016 CD0T-DefaultPrinter_V8i.pltcfg CD0T V81 BW.tbl

| | Sheet Revisions | | | | | | |
|-----------|-----------------|----------|-------|--|--|--|--|
| | Date: | Comments | Init. | | | | |
| \bigcup | | | | | | | |
| \bigcup | | | | | | | |
| \bigcup | | | | | | | |
| | | | | | | | |





| As Constructed | BOULDER CANYON TRAIL EXTENSION | | | | Project No./Code | | |
|----------------|--------------------------------|------|-------------|--------------|------------------|--------------|-----|
| No Revisions: | CROSS SECTIONS | | | STU C070-043 | | | |
| Revised: | Designer: | | Structure | | | 19888 | |
| | Detailer: | REW | Numbers | | | | |
| Void: | Sheet Subset: | XSEC | Subset Shee | ets: | 18 of 18 | Sheet Number | 140 |